



HALE TRAILER BRAKE & WHEEL

XL SPECIALIZED TRAILERS™ A023872-A023881

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 **Little Rock, AR:** 833-424-8944
Baltimore, MD: 888-601-7500 **Portland, ME:** 800-325-4253
Concord, NC: 800-438-2250 **Raleigh, NC:** 833-418-9777
Delmar, DE: 866-486-1400 **Scranton, PA:** 800-569-1400
Des Moines, IA: 888-673-5011 **Springfield, MA:** 800-854-5306
Elkton, MD: 800-544-7127 **Voorhees, NJ:** 866-315-0235
Jacksonville, FL: 800-828-3055 **Walpole, MA:** 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

XL SPECIALIZED TRAILERS

XL 55 MFG: Mini-Deck

OVERALL LENGTH	53'
OVERALL WIDTH	102"
CAPACITY	55,000 LB DISTRIBUTED
WEIGHT +/- 3%	0,000 LB
GOOSENECK	
LENGTH	9' 6" FULL-WIDTH NECK
KINGPIN SETTING	16"
SWING CLEARANCE	78"
5TH WHEEL HEIGHT	50"
	SHIMMABLE NECK - SHIMS INCLUDED
	QUICK COUPLER ON FRONT OF MAIN DECK
	GLAD HANDS ON THE SIDE OF THE UPPER DECK
	WELD HOSE CAGE TO SIDE OF GOOSENECK
DECKING	1 1/8" ALUMINUM DECKING WITH 1-1/8" APITONG NAILER FLUSH
CHAIN SLOTS	(5) TK STYLE CHAIN SLOTS IN LIEU OF LIGHTING HOLES
D-RINGS	NO BENT PER SIDE
D-RINGS	(2) PAIR OF PAN STYLE D-RINGS ONE IN EACH CORNER
MUD FLAPS	ALUMINUM MUD FLAPS SET FORWARD
TOOLBOX	TOOLBOX AT REAR OF GOOSENECK WITH CHAIN RACK, NO LIGHT
MAIN DECK	
	(3) BEAM DESIGN
	RADIUS PER ENGINEERING
LENGTH	34' 11" (33' 11" CLEAR)
LOADED DECK HEIGHT	12" W 4" GROUND CLEARANCE
	1/4" WEAR PLATE FULL LENGTH ON BEAMS
DECKING	STEEL DECKING BETWEEN MAIN BEAMS WITH DURBAK
	1 3/8" APITONG DECKING, RAISED BETWEEN MAIN BEAMS AND OUTER BEAMS
	(3) TUBES ON OUTSIDES OF MAIN BEAM (ADDS ABOUT 730 LBS.)
CROSSMEMBER	4" JR. I-BEAM ON 18" CENTERS
BEAMS	(3) 8" FAB BEAMS
TIE DOWNS	3/8" STIFFENERS ON 18" CENTERS WITH 1/2" X 2 1/2" BAR UNDER FLANGE
CHAIN DROPS	CHAIN DROPS ON 18" CENTERS - NO LIGHTS BELOW
OUTRIGGERS	NONE
RAMPS	TAPERS TO 4"
	HOSE CAGE PLATE ON MAIN DECK
REAR DECK	
LENGTH	8' 7"
LOADED DECK HEIGHT	42" - SET RIDE HEIGHT 2" HIGHER THAN STANDARD
AXLES	(2) 25,000 LBS. NOMINAL (5/8" WALL)
SUSPENSION	HENDRICKSON / 25,000 CAPACITY / AIR RIDE
AXLE SPACING	49"
ABS	4S2M WITH SPRING BRAKES ON (2) AXLES
TIRES	255 / 70R / 22.5 (H)
WHEELS	8.25 X 22.5 10-HOLE PILOT MOUNT POLISHED ALUMINUM OUTSIDE, MILLED ALUMINUM INSIDE DISC
BRAKES	16 1/2" X 7"
DRUMS	OUTBOARD
ELECTRICAL	12V SEALED GROTE SYSTEM WITH (3) TAIL LIGHT ALUMINUM PACKAGE
	4" AMBER STROBE TO BE USED AS 3RD TAIL LIGHT
	1 1/8" ALUMINUM DECKING WITH 1-1/8" APITONG NAILER FLUSH
DECKING	(0) BENT D-RINGS PER SIDE
D-RINGS	(2) PAIR OF PAN STYLE D-RINGS ONE IN EACH CORNER
D-RINGS	(2) BENT D-RINGS IN TAIL CHANNEL
PAINT	
	BLACK
ADDITIONAL	
	TRIPLE DONUT FRONT CONNECTOR PLATE, WELD INDICATORS NUMBERS ON THE HOLES
	MANUAL RIDE HEIGHT CONTROL
	NO AXLE STOPS
	(9) TOTAL TRUCKLITE LIGHTS AND CONNECTORS
	(2) ON UPPER DECK, (4) ON MAIN DECK AND (2) ON REAR DECK (REAR CLEARANCE LIGHTS TO BE BEEHIVE LOOK
	LOOM AROUND TRUCKLITE LIGHTS AND CONNECTORS
	LIGHTS AND WIRING ABOVE CROSSMEMBERS
	CLOSE FRONT TROUGH SECTION UNDER GOOSENECK BETWEEN MAIN BEAMS W/ DRAIN HOLES
	NYLON LIMIT STRAPS
	RAISE AND LOWER VALVE
	GREASE HUBS IN LIEU OF OIL
	ADD FORMED 3/8" PLATE TO FRONT 6" OF MAIN DECK TO DEFLECT DECK OVER OBSTACLES
	SPACE OUT STIFFENERS ON THE MAIN DECK WITH THE CHAIN DROPS, ADD A STIFFENER AT THE REAR OF THE MAIN DECK
	(2) TK STYLE CHAIN SLOTS IN LIEU OF LIGHTING HOLES IN WHEEL AREA
	(1) SINGLE CHAIN SLOT AT REAR OF WHEEL AREA NEAR ABS LIGHT
	(4) SINGLE CHAIN DROPS IN CENTER OF TRANSITION OF THE WHEEL AREA
	LIQUID FILLED AIR GAUGE
	4-WAY AT REAR
	REF 23910

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.