

HALE

TRAILER

BRAKE & WHEEL

EAST UNLOADER TRAILER

OPEN TOP ☒



A023914-A023916
VINS: 89228-89230

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

BODY:		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	TANDEM
LENGTH (FEET)	45	TYPE	SINGLE	TYPE	ALUM SUB FRAME
HEIGHT (INCHES)	100	STYLE	SHEET & POST	AXLE TO AXLE	52"
SIDE MAT'L	3/16"	MAT'L THICKNESS	3/16"	REAR AXLE SETTING	26.5"
TOP RAIL	UNLOADER	S / S HINGE ON	PASS. SIDE 4-3-4	5TH WHEEL HT	49"
ROOF	NONE	GATESEAL	NONE	PIN SETTING	36" + 3/8" KP (8)
ROOF MAT'L	NONE	GATE LADDER	CAST-CENTER	SUSPENSION	AAT30K/E2-1 (5)
BULKHEAD	3/16" (1)	TARP HOOKS	NONE	SPRINGS	AIR
TARP HOOKS	NONE	WINDERS	ONE	AXLES	TP - HXL-5;GREASE
TARP BASKET	NONE	GATE GUIDE	YES	BRAKES	16-1/2" x 7"
TARP	NONE	GATE CONTROL	MECHANICAL	DUSTSHIELDS	YES
CATWALK	YES-STD EAST	POCKETS	EXTRUDED	BRAKE CHAMBERS	STD
B.H. LADDER	D/S - CAST STEPS	CROSSPIPE (S)	TWO	ABS	2S / 1M
CROSSMEMBER	"I" BEAM -12" C/L		MIDDLE - TUBE TYPE	HUBS	10 S STEEL
FLOOR MAKE	KEITH - 3.5" DRIVES		REAR - TUBE TYPE		CAST
FLOOR MAT'L	2299 - 1/2" SLATS	COMPACTOR:		WHEELS	8.25 X 24.5 (6)
WEARPADS	CWS	SIDE LATCH	NONE		4STL / 4HP ALUM
HORIZONTALS	NONE	CENTER LATCH	NONE	TIRES	11R 24.5 R196A
45° DIRT SHEDDERS	8" SMOOTH	PIN DIA.	NONE		BRIDGESTONE
TARP BAR	YES - SINGLE	HYDRAULICS:		DOLLIES	2 SPD JOST HX151
TAPE COLOR	BLUE	HOSES	TWO-4000 PSI	LOCATION	D/S CRANK (7)
LIGHT PANEL	LED IN TAILGATE	LENGTH	144"	BUMPER	STEEL
MARKER LIGHTS	LED -(2)	FITTINGS	PUSH-PULL	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	LED - MODEL 60	HP	1" MALE	PUSH BLOCKS	YES
MUDFLAPS	STD	LP	1" FEMALE	PAINT	SILVER
HOSE HANGER	ON BULKHEAD	HOSE LOCATION	CENTER		
TIRE CARRIER	NONE	AIR & ELECTRICAL	CENTER		

REMARKS: PRICE SUBJECT TO CHANGE 12 WEEKS PRIOR TO ESTIMATED BUILD DATE

CHANGE 1

1. YES INSIDE BULKHEAD STEPS.
2. 3 PAIR PER SIDE LED TOP & BOTTOM. GROMMET IN ALL CONNECTIONS WHERE WIRE PASSES THROUGH METAL
3. ADD ACCESS HOLE IN FRONT DRIVER SIDE OF BULKHEAD THROUGH 5TH WHEEL PLATE BAND FOR FUTURE ACCESS TO STEEL HYDRAULIC TUBES. FINISH OFF WITH SMALL COVER PLATE SECURED WITH TEC SCREWS
4. ADD REAR CENTER MUDFLAP
5. MANUAL EXHAUST SWITCH ON D/S SUBFRAME
- 6.ADD PLASTIC INSULATORS BETWEEN STEEL & ALUM WHEELS
7. ADD REGISTRATION HOLDER TO D/S LANDING GEAR BRACKET - TRUCKLITE
8. REPLACEABLE KINGPIN
9. GALVANIZED HANGERS

OVERALL HEIGHT (FT) 12.92 **EMPTY WEIGHT (#)** 16,365 **CUBIC YARDS** 108
(EMPTY WEIGHT VARIANCE +/- 3%)

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.