

# HALE

## TRAILER

### BRAKE & WHEEL



A024143-A024146  
VINS: A4952-A4955

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b> 800-383-8894	<b>Little Rock, AR:</b> 833-424-8944
<b>Baltimore, MD:</b> 888-601-7500	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Raleigh, NC:</b> 833-418-9777
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235
<b>Jacksonville, FL:</b> 800-828-3055	<b>Walpole, MA:</b> 800-854-5310

haletrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

Traverse HT (Consult FHH For Pricing) (Model: TRAVERSE TRV4048HT)	
THT4048F*838493	Est. Wt.: 17,653# +/- 3%
<b>Capacity:</b> 40 tons distributed evenly, 25 tons in 10-foot - GAWR and tire ratings determine legal loads -	
<b>Load Base:</b> 10-foot rigid 2-point load centered in deck	
<b>Framework:</b> All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
<b>Width:</b> 102 inches wide	
<b>Length:</b> 47 feet 11 inches	
<b>Gooseneck Design:</b> Fixed full width with slope	
<b>Gooseneck Platform:</b> Full-width gooseneck platform with 1 3/8 inch wood floor	
<b>Front Gooseneck Ramp:</b> Hydraulic front ramp with traction plate (8ft 5in) 13 degree loading angle	
<b>Loaded Fifth Wheel Height:</b> 49 inches	
<b>Swing Radius:</b> 85 inches	
<b>Power Source:</b> Set up for wet line operation	
<b>Winch:</b> 18,000 lb. WARN winch with air clutch, located at front of gooseneck with 75 feet of cable	
<b>Winch Guard:</b> None Standard	
<b>Radio Remote Control:</b> 4 function (winch, main tail, flip tail, locks)	
<b>Controls:</b> Dual controls located on side of gooseneck	
<b>Landing Gear:</b> 2 Speed OEM Standard with road-side crank handle	
<b>Tool Box:</b> Dual toolboxes located in gooseneck	
<b>Deck Design:</b> Flat level deck design	
<b>Deck Length:</b> 38 feet 2 inches clear deck length	
<b>Loaded Deck Height:</b> 35 inches	
<b>Flooring:</b> 1 3/8 inch nominal wood (full width)	
<b>Crossmembers:</b> 18 inch centers	
<b>Tie Downs:</b> Alternating combo stake pockets/chain hook slot and double key hole chain slots on 18 inch center. Four way key hole slots down the center of the trailer and gooseneck ramp. Two way key hole slots on main tail	
<b>Deck to Bogie Connection:</b> Fixed	
<b>Number of Axles:</b> 2	
<b>Axle Capacity:</b> 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
<b>Brakes:</b> 12.25 inches x 7.5 inches with 6 inches autoslacks - heavy duty brake drums - outboard mount	
<b>Axle Spread:</b> 49 inches (between axles)	
<b>Spring Brakes:</b> Spring brakes (2 axles)	
<b>Framework:</b> All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
<b>Suspension:</b> Air ride with automatic height controls	
<b>ABS:</b> 4S/2M system without diagnostic tool and cable	
<b>Air Weigh Scale:</b> Air weigh scale installed	
<b>Wheels:</b> 6.75 x 17.5 LVL one buffed outside/steel inside - hub-piloted	
<b>Tires:</b> 235/75R 17.5 H ply Economical OEM Standard	
<b>Hubdrometer:</b> None Standard	

<b>Tire Inflation: Tire Inflation System installed</b>	
<b>Electrical System:</b> DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
<b>Marker Lights:</b> 3 marker lights per side including mid-turn	
<b>Additional Marker Lights: None Standard</b>	
<b>Auxiliary Electrical Connection:</b> 4 Pin socket on curb-side rear of deck	
<b>LED Work Lights: LED work lights on gooseneck drop</b>	
<b>Electrical Receptacle:</b> J560 7-pin connector	
<b>Hydraulic Tail:</b> Full width hydraulic tail with star plate and cleat bars(11 degree loading angle) with amber swing out lights	
<b>Main Tail Length:</b> 10ft 5in	
<b>Flip Tail Length:</b> 4ft 0in	
<b>Tail Height:</b> Tail raises to 72 inches	
<b>Tail Capacity:</b> Tail can lift 25,000# evenly distributed	
<b>Bumper:</b> DOT compliant with 3 lights per side and 3 center lights	
<b>Paint: Fontaine black polyurethane enamel</b>	
<b>Non Skid Paint: Non Skid Paint on outer top flanges</b>	
<b>VIN Plate:</b> Bilingual VIN plate	
<b>Registration/Document Holder:</b> Registration/document holder mounted in tool box on road-side	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.