

HALE

TRAILER

BRAKE & WHEEL

A024284-A024340
VIN: 233332-233381



SALES | RENTALS | PARTS | SERVICE

| | |
|---------------------------------------|--------------------------------------|
| Allentown, PA: 800-383-8894 | Little Rock, AR: 833-424-8944 |
| Baltimore, MD: 888-601-7500 | Portland, ME: 800-325-4253 |
| Concord, NC: 800-438-2250 | Raleigh, NC: 833-418-9777 |
| Delmar, DE: 866-486-1400 | Scranton, PA: 800-569-1400 |
| Des Moines, IA: 888-673-5011 | Springfield, MA: 800-854-5306 |
| Elkton, MD: 800-544-7127 | Voorhees, NJ: 866-315-0235 |
| Jacksonville, FL: 800-828-3055 | Walpole, MA: 800-854-5310 |

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

| ITEM | DESCRIPTION |
|--------------------------|--|
| TYPE | SEMI-TRAILER, STEEL PLATFORM LEGEND SD |
| DIMENSIONS | |
| LENGTH | 48'-0" |
| WIDTH | 102", 97" between side rails. |
| HEIGHT | Floor, approximately 59 1/2" high at front and 54" at rear. |
| COUPLING | |
| COUPLER PLATE | 3/8", plug welded structure. |
| KING PIN LOCATION | 30" from front. |
| COUPLER HEIGHT | 48". |
| STRUCTURE | 44" c/c frame with "CAMBER". |
| FLANGES | 3/8" x 5", high tensile. |
| WEB | 1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel. 27" high at the peak. with holes, parachute shaped, to lighten trailer. |
| GOOSENECK | 11 1/4" high, with integrated nose ramp and 48" straight behind king pin. |
| CROSSMEMBERS | I beams, 4" @ 3.2 lbs/ft, 80 000 psi steel, galvanised, 12" c/c. |
| FLOOR | Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative. |
| FLOOR FASTENING | Screws |
| SIDE RAILS | 10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" height. |
| SIDE BOXES | 3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions). Cargo pockets. |
| RUB RAILS | 3/8" x 2 1/2" shaped steel. |
| CORNERS | Bevelled. |
| X BRACES | Between main beams, full length. |
| ENDS | |
| FRONT RAIL | Formed steel, bolted. |
| BUMPER | CMVSS 223-RIG approved (in accordance with Canada & USA regulation). Galvanized (G164) steel, bolted uprights to frames, 4" x 4" cross bar formed tubing at a maximum height of 22" from under tubing to ground. |
| HEADBOARD | 48" high, steel, 4 uprights and top made of tubing and 11 gauge steel plate installed inside with retroreflective tapes. (this bulkhead is NOT D.O.T.) *** Galvanized *** |
| POCKETS | 2 bolted galvanised pockets at front for removable headboard. |
| BUMPER | 2 rubber dock, at the end of rear rail. |
| REAR RAIL | Formed steel. |
| ELECTRICAL | |
| FRONT CONNECTOR | 7 way (SAE J560). |
| ELECTRICAL SYSTEM | Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. |
| MAIN SYSTEM | Grote Ultra Blue LED, sealed beams, tail lights, markers lights "Dot", identification lights (2 1/2" dia.), licence light. |
| FLASHERS | Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber. |
| TAIL LIGHTS | Sealed beams (Grote DEL #54332) red. Qty: 1 additional each side. |

| ITEM | DESCRIPTION |
|--|--|
| | From outside, tail lights and flasher, flasher with parking, brake with parking. |
| LANDING GEAR SAND SHOES CRANK | AXN, (LG50DUN) 10" x 10". Road side. |
| BOGIE BASIC MECHANICAL BOGIE | Slider, Hutch H-9000, "UHMV" slider plastic pads, 4 locking pins, For 49" spread tandem spring suspension. 6" c/c between locating holes, (48" travel). |
| MECHANICAL (GROUND AXLES) SUSPENSION U-BOLTS SPRINGS AXLE(S) CAM SHAFTS TRACK DUST SHIELDS BRAKES BEARINGS SLACK ADJUSTERS SEALS BRAKE CHAMBERS HUBS AND DRUMS RIMS TIRES | Hutch H-9700, tandem, under mount, 49" spread. With nuts at bottom. 3 leaves, model TRA 2741, 12 000 lbs capacity. Meritor, TN 467_L, 22 500 lbs. capacity. 28 splines. 77 1/2". None (Meritor axles). 16 1/2" standard, FRAS-LE MA212Q+ extended life lining. HM 218248 and HM 212049 Meritor, automatic, 28 splines. Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. T.S.E. brake, "Omnibrake" (30-30). (4 years warranty by T.S.E. for parts only). 10 stud disc hubs, balanced drums outboard mount, 285.75mm B.C., single flange nuts. For dual aluminum wheels. 22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes. Doublecoin, 11 R 22.5 TR100 14 ply (41.0") |
| AIR SYSTEM GLAD HANDS GLAD HANDS AIR VALVES | Fixed. With filter. Meritor Wabco, ABS, 2 sensors 1 modulator. |
| ACCESSORIES REGISTRATION HOLDER MUD FLAPS SLIDING TRACK WINCHES | One plastic, Betts-PS-1 or equivalent. One set, rubber with moose logo and vertical grooves to reduce spray. Full length, "LL" extruded aluminum, road side. Qty: 12, ANCRA #49207-137-XZ, zinc plated slider (low profil 5 7/8"). |
| FINISHING PAINT BOGIE | Shot blasted, one coat of epoxy primer and one acrylic polyurethane top coats Color: black, code: PPG CCA947255-55. One coat of epoxy primer and one acrylic urethane top coats, Color: black, code: PPG CCA947255-55. |



| ITEM | DESCRIPTION |
|---|--|
| RETROREFLECTIVE TAPES WHEELS OR RIMS | Axles (wheel end) included. (Tandem). Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar. White (power top coat). |
| ADDITIONAL OPTIONS | Estimated weight is 11,955 LBS +/- 3% |
| CONFORMITY | This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer. |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.