

# HALE

## TRAILER

### BRAKE & WHEEL



A024664-A024666  
VIN: 000639-000641

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b> 800-383-8894	<b>Little Rock, AR:</b> 833-424-8944
<b>Baltimore, MD:</b> 888-601-7500	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Raleigh, NC:</b> 833-418-9777
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235
<b>Jacksonville, FL:</b> 800-828-3055	<b>Walpole, MA:</b> 800-854-5310

haletrailer.com | @haletrailer   
**800-232-6535** \*FINANCING AVAILABLE

### 22.5 ANR 22.5 Ton Tandem Air Tilt/No Ramp Tags

**Base Weight:** 10,220

#### TRAILER

<b>Overall Length</b>	34 ft. 7 in.
<b>Overall Width</b>	102 in.
<b>Weight lbs +/- 2%</b>	10333, including options
<b>A-Frame</b>	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
<b>Hitch</b>	3 in. pintle eye, adjustable 7 position, 15 in. to 28 1/2 in.

#### DECK

<b>Deck Length</b>	21 ft.
<b>Loaded Deck Height</b>	34 in.
<b>Main Frame</b>	Hi-Tensile Wide Flange 14 in. @ 26
<b>Cross Members</b>	Hi-Tensile 6 in. Channel @ 8.2
<b>Side Rail</b>	Hi-Tensile 8 in. Channel @ 11.5 open on inside
<b>Air Tilt Deck</b>	*NPO*: * 4 Air Bags
<b>Floor</b>	1 3/8 in. x 7 in. Keruing Shiplapped
<b>Landing Gear</b>	Dual Holland Mark V 2 Speed
<b>Rear</b>	Wedge Style bumper with air assisted tilt deck for ground loading
<b>Step</b>	*NPO*: Bolt on, Located on Front Corner of deck, Driver side , and 1 Step on Passenger Side in front of Lead Axle

#### SUSPENSION/AXLES

<b>Axles</b>	25,000 lbs Capacity 77.5 in. Track
<b>Spread</b>	49 in.
<b>Suspension</b>	Heavy Duty spring ride
<b>Alum Air Tank</b>	*NPO*: Drain Plug with Cable
<b>Brakes</b>	Quick Change 12 1/4 in. x 7 in.
<b>Brake Chamber</b>	#3030, All Axles
<b>Air Brake System</b>	2S/1M
<b>Air Tank(s)</b>	Aluminum
<b>Bearings</b>	Oil Bath
<b>Slack Adjusters</b>	Automatic
<b>Hubs &amp; Drums</b>	8 Stud Unimount C / W Cast Drums
<b>Tires</b>	235/75R17.5 16 ply
<b>Wheels</b>	Alum. Wheel Pkg. 17.5 (4 Steel, 4 Polished)

#### BEAVERTAIL

<b>Length</b>	6 ft. @ 8 degree slope, Self Cleaning Outside , Planked in inside
---------------	---

#### GENERAL SPECIFICATIONS

<b>Electrical System</b>	Modular, Vapor Proof GROTE Ultra Blue
<b>Lights</b>	LED CMVSS 108 / FMVSS 108
<b>Lights</b>	Amber Flashing Strobe Lights (Mounted in Bumper)
<b>Front Connector</b>	SAE J560 7 Pin
<b>Finishing</b>	Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
<b>Color</b>	Black

**GENERAL SPECIFICATIONS**

<b>Mudflaps</b>	1 set of BWS at rear
<b>Toolbox</b>	Full A Frame mounted with solid bottom and cover
<b>Load Securement</b>	9 pair of D-rings: 7 pr on main deck evenly spaced, 1 pr on main beam at headboard, 1 pr on top of A Frame on both sides of toolbox
<b>Fenders</b>	3/16 in. deck plate

**GVWR Rating is based on standard configuration and a 15% Tongue weight distribution**

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.