

HALE

TRAILER

BRAKE & WHEEL

A024716-A024724



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	TELESCOPIC SEMI-TRAILER, STEEL PLATFORM.
DIMENSIONS	
LENGTH	53'-0" closed.
LENGTH	90'-0" open
OPENINGS	5'-0" increments in closed position.
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 61 1/4" high at front and 58" at rear.
COUPLING	
COUPLER PLATE	5/16", plug welded structure.
KING PIN LOCATION	18" from front.
COUPLER HEIGHT	49".
STRUCTURE	
FLANGES	Frame with "CAMBER".
FLANGES	Female section, (exterior), 3/8" x 6", 100 000 psi steel, 24" high.
WEB	Male section (interior), 1/2" x 6", 100 000 psi steel, 17 5/8" high.
GOOSENECK	1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel.
CROSSMEMBERS	12" high, with integrated nose ramp and 48" straight behind king pin.
FLOOR	I beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, 12" centre to centre.
FLOOR FASTENING	Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative.
SIDE RAILS	Two screws per board at each crossmember.
SIDE BOXES	Formed channel 6" @ 4.6 lbs/ft.
RUB RAILS	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high.
CORNERS	(USA Dimensions).
DIAGONAL BRACES	3/8" x 2 1/2" shaped steel.
X BRACES	Bevelled.
LOCKS	2" x 2" x 3/16" angles, welded in web and to a crossmember, located each side.
ROLLERS	Between main beams, full length, sheet metal with cutting holes at front and rear between male main beams.
SPACERS FOR RUB RAILS	Air operated with a third glad hand at front.
ENDS	
FRONT RAIL	4, 2 on female sections of frames and 2 on male sections.
BUMPER	Double between side boxes.
BUMPER	9 gauge formed steel.
POCKETS	CMVSS 223-RIG approved (in accordance with Canada & USA regulations).
REAR RAIL	Uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground.
ELECTRICAL	
FRONT CONNECTOR	Aluminum plate, bolted between bumper uprights to close rear.
ELECTRICAL SYSTEM	2 welded pockets at front for removable headboard.
	11" high, 9 gauge formed steel, including 3 boxes at rear and 3/8" x 2 1/2" shaped steel.



ITEM	DESCRIPTION
<p>MAIN SYSTEM</p> <p>TURN SIGNAL</p> <p>REAR ADD. CONNECTOR</p>	<p>Grote Ultra Blue LED, grounded to front connector, sealed beams Grote. (tail lights with male pins #54332, markers #47122, 47233 (2 1/2" dia.), licence light #60280-M, with vapor proof junction box Truck-Lite #50400).</p> <p>Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber.</p> <p>4 way.</p>
<p>LANDING GEAR</p> <p>SAND SHOES</p> <p>CRANK</p>	<p>Holland, Mark V (LGS-4F115), with mounting plate.</p> <p>10" x 11 1/2".</p> <p>Road side.</p>
<p>BOGIE</p> <p>BASIC SUSPENSION</p> <p>BOGIE</p> <p>SUSPENSION</p> <p>U-BOLTS</p> <p>SPRINGS</p> <p>AXLE(S)</p> <p>SPIDERS</p> <p>CAM SHAFTS</p> <p>TRACK</p> <p>DUST SHIELDS</p> <p>BRAKES</p> <p>BEARINGS</p> <p>SLACK ADJUSTERS</p> <p>SEALS</p> <p>BRAKE CHAMBERS</p> <p>HUBS AND DRUMS</p> <p>RIMS</p> <p>TIRES</p> <p>MANUAL STOP BAR(S)</p>	<p>Slider, Hutch H-9801, "UHMV" slider plastic pads, 4 locking pins, For 49" spread tandem spring suspension.</p> <p>4" c/c between locating holes, (48" travel).</p> <p>Hutch H-9700, tandem, underslung, under mount, 49" spread.</p> <p>With nuts at bottom.</p> <p>3 leaves, model TRA 2740 or 365-00, 12 000 lbs capacity.</p> <p>5" round, 22 500 lbs. capacity.</p> <p>Welded.</p> <p>28 splines.</p> <p>77 1/2".</p> <p>Steel, bolted.</p> <p>16 1/2" standard, extended life lining.</p> <p>HM 218248 and HM 212049.</p> <p>Meritor, automatic, 28 splines.</p> <p>Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90.</p> <p>T.S.E. brake, "Omnibrake" (30-30).</p> <p>(4 years warranty by T.S.E. for parts only).</p> <p>10 studs disc hubs, outboard mount, 285.75mm B.C., single flange nuts.</p> <p>For dual steel wheels or single wheels.</p> <p>22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes.</p> <p>Standard duty with light steel.</p> <p>General, 11 R 22.5 HT+ 14 ply (41.1")</p> <p>One, Hutch.</p>
<p>AIR SYSTEM</p> <p>GLAD HANDS</p> <p>AIR VALVES</p> <p>VALVE</p>	<p>Fixed.</p> <p>Meritor Wabco, ABS, 2 sensors 1 modulator.</p> <p>Fast-brake kit.</p>
<p>ACCESSORIES</p> <p>REGISTRATION HOLDER</p> <p>WINCHES</p> <p>SLIDING TRACK</p> <p>MUD FLAPS</p>	<p>One plastic, Betts-PS-1 or equivalent.</p> <p>Qty: 12, ANCRA #49207-137-XZ, zinc plated slider (5 7/8").</p> <p>Full length, "LL" extruded aluminum, road side.</p> <p>One set, rubber with Manac logo and vertical grooves to reduce spray.</p>



ITEM	DESCRIPTION
FINISHING PAINT BOGIE AXLE(S) PAINTED HUBS WHEELS OR RIMS RETROREFLECTIVE TAPES	Shot blasted, one coat of epoxy primer and two polyurethane acrylic top coats Color: black, code: PPG AU37-FP908. Bogie painted same color as trailer. Same color as trailer. Same color as trailer. White. Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar.
ADDITIONAL OPTIONS	Same as U#186625 except 53'-90' Estimated empty weight is 16,742 LBS +/- 3%
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.