

# HALE

## TRAILER

### BRAKE & WHEEL



**A024817-A024819**  
**VIN: 00007-00009**

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b> 800-383-8894	<b>Little Rock, AR:</b> 833-424-8944
<b>Baltimore, MD:</b> 888-601-7500	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Raleigh, NC:</b> 833-418-9777
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235
<b>Jacksonville, FL:</b> 800-828-3055	<b>Walpole, MA:</b> 800-854-5310

haletrailer.com | @haletrailer   
**800-232-6535** \*FINANCING AVAILABLE

<b>Base Weight:</b> 11,820	<b>30NTT 30 Ton Tridem Non Tilt Tags</b>
<b>TRAILER</b>	
Overall Length	37 ft. 7 in.
Overall Width	102 in.
Weight lbs +/- 2%	13102, including options
A-Frame	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
Hitch	3 in. pintle eye, adjustable 7 position, 19 in. to 33 in.
Deck Length	24 ft.
Loaded Deck Height	34 in.
Main Frame	Hi-Tensile Wide Flange 14 in. @ 26
Cross Members	Hi-Tensile 6 in. Channel @ 8.2
Side Rail	Hi-Tensile 8 in. Channel @ 11.5 open on inside
Floor	1 3/8 in. x 7 in. Keruing Shiplapped
Landing Gear	Dual Holland Mark V 2 Speed
Step	*NPO*: Bolt on, Located on Front Corner of deck, Driver side and 1 on Passenger side ahead of lead axle
<b>SUSPENSION/AXLES</b>	
Axles	25,000 lbs Capacity 77.5 in. Track ,1 Lift Axle with Control Box
Spread	49 in.
Suspension	Heavy Duty spring ride., 1 Ridewell RAR 260 Underslung Air ride 25,000lbs. (includes air gauge)
Alum Air Tank	*NPO*: Drain plug with cable
Brakes	Quick Change 12 1/4 in. x 7 in.
Brake Chamber	#3030, All Axles
Air Brake System	2S/1M
Air Tank(s)	Aluminum
Bearings	Oil Bath
Slack Adjusters	Automatic
Hubs & Drums	8 Stud Unimount C / W Cast Drums
Tires	235/75R17.5 16 ply
Wheels	Alum. Wheel Pkg. 17.5 (6 steel, 6 polished)
<b>BEAVERTAIL</b>	
Length	6 ft. Beavertail, Planked
<b>RAMPS</b>	
Length	* 38 in. x 76 in. Wood Filled Air Operated Ramp
Ramp Support	*NPO*: Ramp Support
Brackets	*NPO*: To hold ramp brace when not in use, 1 per side
<b>GENERAL SPECIFICATIONS</b>	
Electrical System	Modular, Vapor Proof GROTE Ultra Blue
Lights	LED CMVSS 108 / FMVSS 108
Lights	*NPO*: Amber Flashing Strobe Lights(Mounted in Ramps)

**GENERAL SPECIFICATIONS**

<b>Lights</b>	<u>*NPO*: Switch for strobes mounted in toolbox</u>
<b>Front Connector</b>	SAE J560 7 Pin
<b>Finishing</b>	Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
<b>Color</b>	Black
<b>Mudflaps</b>	1 set of BWS at rear
<b>Toolbox</b>	Full A Frame mounted with solid bottom and cover
<b>Load Securement</b>	11 pair of D-rings: 9 pr on main deck, evenly spaced, 1 pr on top of main beam at headboard, 1 pr on top of A Frame top flange on each side of toolbox
<b>Fenders</b>	3/16 in. deck plate

**GVWR Rating is based on standard configuration and a 15% Tongue weight distribution**

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.