

# HALE

## TRAILER

### BRAKE & WHEEL



A025218-A025226

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b> 800-383-8894	<b>Little Rock, AR:</b> 833-424-8944
<b>Baltimore, MD:</b> 888-601-7500	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Raleigh, NC:</b> 833-418-9777
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235
<b>Jacksonville, FL:</b> 800-828-3055	<b>Walpole, MA:</b> 800-854-5310

haletrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

#### Infinity Flat 48' Air Slider (Model Code: HAICF12SAT)

<b>Length / Width:</b> 48 feet x 102 inches
<b>Suspension Type:</b> Sliding air tandem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements
<b>Frame Rating:</b> 80,000 lbs distributed - GAWR and tire ratings determine legal payloads
<b>Flooring:</b> 1 1/8 inch aluminum with 4 wood nailer strips
<b>Crossmembers:</b> 12 inch centers - 4 inch jr. I-steel
<b>Single Coil Hauling Package:</b> Included
<b>Side Rails:</b> Exclusive <b>Revolutionary RASR Rail Technology</b> -- one piece routed aluminum designed for strength and impact
<b>Chain Cargo Tie Downs:</b> 15 pair recessed in siderails
<b>Stake Pockets:</b> Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)
<b>Rubrail:</b> Integrated with siderail
<b>Main Beams:</b> 130K load bearing flanges
<b>Kingpin:</b> 30 inches
<b>Loaded Fifth Wheel Height:</b> 49 inches
<b>Landing Gear:</b> OEM Standard with Forward & Rear Bracing
<b>Knee Braces:</b> Fabricated on approx. 60 inch C/C
<b>Bulkhead Pockets:</b> 4 DOT type bulkhead pockets only - welded to front
<b>Bulkheads:</b> <b>Removable steel 4 post DOT type bulkhead - no turnback - 48 inches high with front pockets</b>
<b>Number of Axles:</b> 2
<b>Axle Spindle:</b> Tapered
<b>Brakes:</b> Spring brakes, auto slacks
<b>Air Line Filters:</b> (2) Meritor In-line type installed
<b>ABS:</b> <b>Meritor Wabco iABS 2S/1M Basic System Requested by Customer- no cable or tool</b>
<b>Axle Spread:</b> 49 inches
<b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums
<b>Wheel Ends:</b> Grease in hubs - *** 5-year wheel end warranty ***
<b>Wheels:</b> 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD
<b>Tires:</b> <b>11R 22.5 14PR GENERAL HT+</b>
<b>Tire Inflation System:</b> None standard
<b>Suspension Detail:</b> Hendrickson AAZNT46K Intraax air ride slider - 60 inches adjustable
<b>Air Assist Slide Box Pins:</b> Standard mount of controls on slider frame
<b>Auto Glad Hand Dump :</b> Installed
<b>Front Corners:</b> Tapered steel
<b>Electrical System:</b> LED: 3 lights/side, 3 lights/side on rear - STANDARD
<b>Paint:</b> Black urethane on steel parts with Infinity decals - STANDARD
<b>Conspicuity Tape:</b> Per NHTSA specs - installed in recess on rubrails
<b>Bumper:</b> Weld-on type - meets underride requirements - painted steel
<b>Mudflaps:</b> 1 set OEM standard behind rear axle
<b>Spare Tire Carrier:</b> None standard
<b>Winch Track:</b> Full length integrated double L type aluminum on both sides -- STANDARD
<b>Sliding Winches:</b> 12: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers -- STANDARD
<b>27 foot Winch Straps:</b> None standard
<b>30 foot Winch Straps:</b> None standard
<b>Dock Bumpers:</b> 1 pair rubber on rear
<b>Hubodometer:</b> None standard
<b>Registration Holder:</b> Install registration holder - OEM standard
<b>Tool Box:</b> None standard
<b>VIN Plate:</b> Bilingual US/Canadian VIN plate

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.