

HALE

TRAILER

BRAKE & WHEEL



A025531-A025535
VIN:412046-412050

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

GWR

GVWR:	Trailer to meet 68,000 Pound GVWR
VIN PLATE:	US - VIN Plate to Read in English (Standard)
* Product Type:	HT HyCube

GEOMETRY

Length - Exterior:	53'-0"
** Length - Interior:	52'-6" Nominal Lining To Lining
Width - Exterior:	102.36"
** Width - Interior:	101" Nominal Lining To Lining
Height - Exterior:	13'-6"
Height - Interior:	110" Nominal
Deck Height:	Standard application
Fifth Wheel Height:	47"
King Pin Location:	36"
Landing Gear Location:	107" from King Pin (+ 1"/-1/4")

TIRES & WHEELS

Tire Furnished:	Factory Furnished
* Tire Manufacturer:	Hankook TL21(G), Low Rolling Resistance Tire
Tire Size:	295/75R22.5
Wheel Furnish:	Factory Furnished
Wheel Material:	All Steel Wheel
Wheel Manufacturer:	HT Standard (TCC 361)
Wheel Size:	8.25 x 22.5, 5-Hand Hole (Steel, Inner & Outer)
* Wheel Finish for Steel:	Hot Dip Galvanized.
Tire Stem Valve Position:	Dual Wheel Steel / Aluminum / Combo (STD 180°outboard & straight inboard)
Wheel Finish for Aluminum:	None (Due to All Steel Wheel Application)
* Valve Stem & Cap:	TR-572 Valve Stem# 8900HALNC for use w/PSI; w/o Cap

UPPER COUPLER

Approach Plate:	7/32" THICK 80,000 LB YIELD - 6 SUPPORT CHANNELS
King Pin (BTM Main) Plate:	1/4" thick 80,000 Lb Yield
King Pin & Manufacturer:	Standard (Jost) AAR Cruciform King Pin
Front Bottom Rail:	Galvanized-Whole Upper Coupler section, w/ Pick-Up plate Striker Angle
Upper Coupler Tube Qt'y:	(1) Tubing Application - Joggled
* Front Bottom Rail External Routing Holes:	1 Slot Hole for Harness and Hoses External Routing

BODY/BASE

Forward Crossmember:	Steel Hat Shaped Upper Coupler to Landing Gear : 12" C/L
Landing Gear Crossmember:	4" Steel I-Beams (80,000 PSI) : 12" C/L (5ea)
Bay Area Crossmember:	4" Steel I-Beams (80,000 PSI) : 12" C/L
Running Gear Crossmember:	4" Steel I-Beams (80,000 PSI) : 12" C/L with 8" C/L Last 3.4'
Slider Body Rail (VT):	208" Rail Length
Slider Rail Supplier:	Hutchens Slider Rails

FLOOR

Upper Coupler Type:	3.40" Joggled with Exposed Coupler Top Plate (New STD)
* Floor Specification:	1.38" (1-3/8") Net Domestic Laminated Oak Hardwood - Havco Brand Only (10 years)

	warranty)
* Floor Ratings - VT:	20,000 lbs Rated Floor per TTMA
Floor- Assembly Method:	Wood Floor Assembly
Floor Screws:	(3) 0.31" Dia. screws per Board on I beams
Threshold-Finish:	Hot Dip Galvanized
Threshold Plate:	0.13" X 12" Deep Steel Diamond Plate w/ Screws and Nuts
Threshold-Application:	Standard Application

FRONT

Front Corner Radius:	4" Extruded Aluminum
Front Panel & Color - Dry:	0.05" Aluminum Prepainted White w/ natural color rivets
Front Corner Mat'l - Dry:	Extruded Aluminum
Front Posts:	(4) 2.5" Deep (16Ga) Steel Hats - Non AAR
* Gladhands:	Phillips Qwik-E with Filters Control Line Only. Overlaid (Bottom Open)
Front Receptacle(7-Way):	Phillips 7-Way without Circuit Breakers, Split Pins with QCS plug
Front Receptacle(7-Way) - Options:	Phillips QCS Plug connector
* Gladhand/7-Way Location:	(Exterior Harness Routing) Overlaid on Lower Roadside Front (STD) - Mounted on external overlaid HDG mounting bracket
* Corner Radius Protector:	(2) 0.125" X 12" SMOOTH Alum Each Side at Top

SIDE

* Side Material:	0.05" Aluminum Prepainted White w/ natural color rivets
* Side Posts:	0.45" Deep 14 Gauge Galv Steel "A" Slotted Logistic Posts
* Side Post Centers:	16" C/L with 12" C/L @ Upper Coupler and Support Gear
* Side Top Rail:	Shallow Post Side Top Rail
* Side Bottom Rail:	Side Bottom Rail STD
Fasteners to Bottom Rail:	Standard Rivets to attach C/Members to the Side Bottom Rail
* Side Sub Options:	Additional A-Slotted holes in Rearmost Position to use as Logistic Slots

REAR

Rear Frame:	Swing Door, 2.5" New Door Header Standard Trailers (with 1 Lock Rod Per LH & RH Door)
Rear Door Opening Spec.:	Standard Application
Floor Level:	Door to be Flush with Floor (STD)
Door Type for Dry Van - SW:	0.5" Composite Swing Door. Galvanized Prepainted White Interior & Exterior Skin
Option - Door (Main Line):	Install Standard Anti-Theft Hardware
Option - Door Install Instruct:	Standard Door Installation per Manufacturer's Recommendation
Option - Door & Hardware:	One(1) Rubber Door Bumper (1.25" Deep) on Hinge of each Swing Door
Door Holder Type for Swing Door:	Standard Door Holdback
Hinges:	Four (4) Aluminum Hinges per Door (3" Height)
* Additional Hinge Option:	Additional One(1) Aluminum Hinge (Total 5 Per Door)
* Rear Underride Guard:	4" Tube Bolt on Assembly w/ Welded Perforated(Poached) Horizontal. Rear Impact Guard (RIG30-NEW)
Option - Horiz Member/Other:	One piece roll formed w/continuous welding
Underide Bolt Spec.:	Geomet bolts & nuts - Standard
Dock Bumper:	Pair 3" X 6" Mold Bolted Bumper
Rubber Bumper Location:	Inboard of Light Protector Bars (Standard)
Rear Frame Design:	Rear Frame Open Door Sill New Design

LIFT GATE

ROOF

Roof Panel:	0.040" Aluminum
Roof Bow:	16 Gauge Galvanized Steel Anti-Snag
Roof Bow Centers:	24" Centers Full Length

LINING/SCUFF

* Side Lining:	0.235" HDPE Recycled Plastic Installed between Posts
Front Lining:	0.25" Top and 0.5" Bottom plywood Mounted to Front Posts Full Height
* Base Side Scuff:	0.63" x 12" High White Recycled Plastic

- * Side Scuff Band Mounting Method: Mounted Directly to Posts
- * Front Scuff: 0.63" x 12" High White Recycled Plastic Mounted Over Lining to Front Posts (Overlaid)
- * Front Corner Lining Support: Galv Steel Front Corner Liners

LANDING GEAR

- L/Gear Spec.: Jost HT421.G3.17.157 5 Year Warranty Full HDG
- L/Gear Mt'g Method: Inboard Mounting (Standard)
- L/Gear Shoes: 10" X 10" RCF (Removable Cushion Foot) Low Profile
- L/Gear Ground Clearance: Nom. 12" Ground Clearance
- L/Gear Mt'g Bracket: Hot Dip Galvanized Large Wing Plate
- L/Gear Crank Handle: Roadside
- L/Gear Options: None (HT STD)
- L/Gear Cross Brace Design: HT Standard Cross Brace attachment Design

RUNNING GEAR

- Bogie Type: Sliding Tandem(2) Axle Bogie
- Axle Spacing: 49" Axle Spacing
- Axle ABS System: Tandem Axle w/2S1M ABS System
- Bogie & Axle Location: Location to be Sliding Tandem Axle for specified slider Length w/Stop Bars @ Front & Rear
- Option-Related Bogie Stopper Feature: STD plug stopper
- Susp. Manufacturer: Hendrickson
- Suspension Capacity: Standard Duty
- Hendrickson Susp. Specification: Hendrickson Vantraxx HKANT40K Air Ride
- Surelok (Anti-Dock): Surelok (Anti-Dock) Installed
- Locking Pin Mechanism: Air-Assist Pin Puller or Quik Draw
- * Susp. Sub-Frame: Hendrickson K-2 Heavy Duty (Vantraxx, Intraxx)
- * Susp. Misc. Option: Hendrickson to Hot Dip Galvanize Bogie Box
- Type of Susp Spring: Air Bag
- Spring Specification: Air Bag
- Axle Diameter: 5.75"
- Axle Supplier: Hendrickson
- Axle-General Spec.: Axle - Tandem (2) Axle included in Suspension (For 2S1M or 2S2M System)
- Axle-Track Length: 77-1/2"
- Axle-Spindle Type: Tapered Spindle
- Brake Lining Size: 16.5" X 7" Drum Brakes
- Brake Lining Spec.: Hendrickson Extended Service (Abex-3030-197)
- * Brake Control System: 2S/1M Wabco iABS
- Spring Brake Control: Sealco 110500 Springbrake Priority
- Brake Cont-Hose & etc...: Standard Air Line & Hose Application (US&Canada)
- * Slack Adjuster Spec.: Wabco Auto-5.5", 28 Spline EasyFit (No Grease)
- * Brake Chamber Spec.: Wabco Premium Chamber
- * Stroke Length: 3" Long Stroke Length
- Hub Specification: Conmet 10 Stud Hub Piloted Outboard Iron Hub with Casting 10083937
- Drum Specification: Conmet Cast Drum
- Hub/Drum-Opt(Nut&Other): Standard
- Bearing Specification: Stemco
- * Lubrication Spec.: Chev Delo (Syn) Grease
- * Wheel Seals Spec.: Stemco Discover Seals, Hub Cap included in tire inflation system, Pro-Torq Nut
- * Tire Inflation Spec.: Hendrickson Tire Maax Inflation System for Undressed Axle (This kit include Hendrickson Hub Cap for TireMaax)
- Tire Inflation Pressure: 100 PSI
- * Tire Inflation Lamp Location: Indicator PSI Light at Roadside Mounted at 24.6" from bottom of front panel over corner radius. (STD location)
- * Tire Inflation Lamp Spec.: 33 Series Lamp
- * Axle Configuration: Axle included in Suspension

Rev.B

Rev.C

Rev.C

ELECTRICAL

* Harness-General Spec.:	Molded Color Code Phillips Harness with QCS Plug
Harness-Special Feature:	Manufacturer's Standard Feature
* Front Light:	(2) Trucklite 33275Y LED PC Rated Mounted with Grommet
* Rear ID Header Light:	(5) Trucklite Dual Function 33204R LED (Cluster of 3 & 1 Each Outboard)
* Rear ID-Special Feature:	Dual Function Rear Header Lights - 3 Lamps at center with Marker & Stop functionality, 2 Lamps outboard with Marker & Turn functionality
Rear Side Marker Type(Shape):	Mini Button Style Lamp with Antitheft Bracket
* Rear Side Marker Detail Spec:	(2) Trucklite 33275R LED PC Rated Flush w/ Grommet 33725 w/ anti-theft hardware
Rear Side Marker MT'G Location:	Mounted on Standard Location on Rear Corner Post - HT STD
S/T/Tail Light-Quantity & Type:	(4) Trucklite 40 or 44 Series (Round Style) or Equivalent
* S/T/Tail Light-Detail Spec:	(4) Trucklite 44331R LED (Super 44 Grey) Flange Mounted w/ Stainless Steel Rivets
Main Mid-Turn Light:	Install the Mid turn lamp
Mid-Turn Mounting Method:	Mounting Bracket
* Main Mid-Turn Light-Detail Spec:	(2) Trucklite 60272Y LED Gray Flange Mounted with Stainless Steel Rivets & Anti-theft brackets
* ABS Light Detail Spec:	(1) Trucklite 33275Y LED PC Rated w/ Grommet 33725 w/ anti-theft hardware
ABS Light MT'G Location:	Mounted on Standard Location on Rear Corner Post - HT STD
* License Light:	(1) Trucklite 33210C LED with 33815 Anti-Theft Flange
Option Related Harness/Wiring:	Standard
Electrical Related Regulation:	Standard Application

MARKING/DECALS

HT & Product Type Decal Package:	Hyundai Logo & Product Type Decals Application(For not having pre-painted white panels for side/door/front, Apply white HT Corporate decals)
Decal Package:	Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes
Decal Opt 2-Decal Location:	Standard Application
Decal Opt 3-Decal Installation:	Standard Application
Conspicuity Vendor:	3M
Conspicuity Markings:	Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail
License Plate:	Temporary For Delivery. Fasten On HDG Mounting Plate
License Plate Brk't Install:	Standard Install Location - Roadside Below Door Sill
Furnish Document Holder:	Factory Furnished
Document Holder Detail Spec:	(1) Phillips 16-802
* Document Holder/Manifest Loc.:	Overlaid on Lower R/S Front. 18" from the bottom of the front sheet between the front post & corner radius on the roadside

PAINT/FINISH

Upper Coupler Finish:	Galvanized-Whole upper coupler section
Crossmembers Finish:	HDG : ALL Steel Crossmembers including Hat C/M, L/G & Bogie Area (Except any Aluminum)
Axle & Components Finish:	Black Undercoating
* Susp. Sub-Frame Finish:	Hot Dip Galvanized for Tandem or Tridem Suspension Sub-Frame
L/Gear(K-Bracing) Finish:	Hot Dip Galvanized
L/Gear(Upper Leg) Finish:	Hot Dip Galvanized
Rear Frame-Finish:	Hot Dip Galvanized
Rear Frame-Paint Color:	None (For Galvanized or Stainless Steel)
Rear Underride-Finish & Spec.:	Hot Dip Galvanized & Welded Horizontal Member
Rear Underride-Paint Color:	None (For Galvanized or Stainless Steel)

MISCELLANEOUS

Mudflap Provider:	Factory Furnished Mudflaps
Mudflap Specification:	24"x30" White Plain Plastic with Hyundai Logo 3/8# thick with Anti-spray ribs
Mudflap Mounting Location:	Suspension frame (Tandem/Single axle frame without P.H.)
Mudflap Mounting Method/Install:	STD Location w/ H.D Washer Retainer
Mudflap Bracket design:	1 Piece Bracket
* Lift Pad Spec.:	Install HT Occasional use lift pads for delivery
* Import export Decals:	With HYUZ Decals

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.