

HALE TRAILER BRAKE & WHEEL

A025585-A025589
VIN: 66066-66070

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE



PEERLESS TRANSPORT SEMI: Dual Axle, Live Floor, 45' Length, 14.2 Units

STANDARD SPECIFICATIONS: **CTSSF-45**

Type: Peerless dual axle, transport semi-trailer

Design: Box design, flat floor, end dump, live floor

Construction: **.063 skin stressed aluminum with aluminum exterior posts on 21.5" centers, bevelled corners**

Unloading Time: Approximately 8 minutes

Capacity: 14.2 units (105 cu yd)

Dimensions: **45' long, 8' 0" wide, 13' 3" high**, 37" king pin location, 36" rear axle from rear of trailer

Tires: Eight (8) **11:00 x 22.5** radial tires

Wheels: Eight (8) 22.5 x 8.25 - 10 hole, 11 1/4" B.C. hi-tensile steel, Unimount

Axles: 22,500# cap. , **71 1/2" track**, 10 stud, 11 1/4" B.C. hubs, outboard drums, oil seals, quick change brake shoes, auto slacks

Brakes: 16 1/2" x 7" air, CM18 lining, type 3030 air chambers, DOT relay emergency system

A.B.S.: 2 sensor - 1 module

Suspension: Four spring three leaf tandem,(**Hutch H9700T**)

Landing Gear: Two speed, crank on driver's side (**Holland Atlas 55**)

King Pin: Standard SAE, heat treated, 37" setting, 51" height, **5/16" plate – 2 beam**

Cross Sills & Decking: Keith 7/32" with wear strips, 3" cylinder, rubber seals, standard live floor, **4" Jr. I-Beams on 22" centers** with aluminum sub-deck, wear strips on one end

Top: Flat design, open top, single center tie

Top Cover: **Shur-lok roll over tarp – with telescoping pole “wil-slip” cap, rear crank - handle holders on both sides – black vinyl - Flat caps**

Tarp Bows: **Ten (10) 3” arched tarp bows (trailer height overall 13’6” w/ 3” arch bows)**

Safety Screens: **Expanded metal over drive and under front**

Rear Door: Full opening, side hinged, **skinned with solid aluminum**

Ladders: One located at front **with safety loop** and one located at rear (**front ladder mounted to headboard**)

Rope Hooks: Furnished

Mud Flaps: Legal, rubber

Wiring: Unitized wiring system, 12 volt

Glad Hands: Standard mounted on road side of headboard

Lights: Four (4) legal DOT combination stop, tail and directional lights. Legal DOT clearance lights **all lights to be LED**

Reflectors: Legal DOT

Paint: Aluminum natural, steel components primed and painted Black

Weight: Approximately 13,420#

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.