



Base Weight: 12,300

A025902-A025904 VIN: 0088-0090

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: Raleigh, NC 833-418-9777 800-438-2250 Delmar. DE: 866-486-1400 Scranton, PA: 800-569-1400 Des Moines, IA: Springfield, MA: 800-854-5306 888-673-5011 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

30 ANR 30 Ton Tridem Air Tilt/No Ramp Tags

TRAILER

Overall Length 37 ft. 6 in.
Overall Width 102 in.

Weight lbs +/- 2% 13024, including options

A-Frame 6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam

Hitch 3 in. pintle eye, adjustable 7 position, 15 in. to 28 1/2 in.

DECK

Deck Length 24 ft. Loaded Deck Height 34 in.

Main FrameHi-Tensile Wide Flange 14 in. @ 30Cross MembersHi-Tensile 6 in. Channel @ 8.2

Side Rail Hi-Tensile 8 in. Channel @ 11.5 open on inside

Air Tilt Deck * 4 Air Bags

Floor 1 3/8 in. x 7 in. Keruing Shiplapped

Rear Wedge Style bumper with air assisted tilt deck for ground loading

Landing Gear *NPO*: Dual 2 Speed , Galvanized Landing Gear

Step *NPO*: Bolt on, Located on Front Corner of deck, Driver side and 1 on Passenger side

ahead of lead axle

SUSPENSION/AXLES

Axles 25,000 lbs Capacity 77.5 in. Track ,1 Lift Axle with Control Box

Spread 49 in.

Suspension Heavy Duty spring ride., 1 Ridewell RAR 260 Underslung Air ride 25,000lbs. (includes

air gauge)

Alum Air Tank *NPO*: Drain plug with cable

Brakes Quick Change 12 1/4 in. x 7 in.

Brake Chamber #3030, All Axles

Air Brake System 2S/1M
Air Tank(s) Aluminum
Bearings Oil Bath
Slack Adjusters Automatic

Hubs & Drums 8 Stud Unimount C / W Cast Drums

Tires 235/75R17.5 16 ply

Wheels Alum. Wheel Pkg. 17.5 (6 steel, 6 polished)

BEAVERTAIL

Length 6 ft. @ 8 degree slope, Self Cleaning Outside , Planked in inside

GENERAL SPECIFICATIONS

Electrical System Modular, Vapor Proof GROTE Ultra Blue

Front Connector SAE J560 7 Pin

Lights LED CMVSS 108 / FMVSS 108

Lights Amber Flashing Strobe Lights(Mounted in Bumper)

Color Galvanized

GENERAL SPECIFICATIONS

Mudflaps 1 set of BWS at rear

Toolbox Full A Frame mounted with solid bottom and aluminum cover

Load Securement 11 pair of D-rings: 7 pr on main deck, evenly spaced, 2 pr B/T, 1 pr on top of main

beam at headboard; 1 pr on top of A frame top flange, one on each side of toolbox

(Ref - wo#10015744-47)

Fenders 3/16 in. Deck plate

GVWR Rating is based on standard configuration and a 15% Tongue weight distribution