



A025933-A025935
VIN: 234800-234802



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE APPLICATION	SEMI-TRAILER, STEEL PLATFORM LEGEND SD GALVANIZED SEE SECTION
DIMENSIONS	
LENGTH	53'-0"
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 59" high at front and 52" at rear.
COUPLING	
COUPLER PLATE	3/8", plug welded structure.
KING PIN LOCATION	30" from front.
COUPLER HEIGHT	48".
STRUCTURE	44" c/c frame with "CAMBER".
FLANGES	1/2" x 5", 100 000 psi steel.
WEB	1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel, with holes, parachute shaped, to lighten trailer.
GOOSENECK	11 1/4" high, with integrated nose ramp and 48" straight behind king pin.
CROSSMEMBERS	I beams, 4" @ 3.2 lbs/ft, 80 000 psi steel, galvanised, 12" c/c.
FLOOR	Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative.
FLOOR FASTENING	Screws
SIDE RAILS	10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" height.
SIDE BOXES	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions). Cargo pockets.
RUB RAILS	3/8" x 2 1/2" shaped steel.
CORNERS	Bevelled.
X BRACES	Between main beams, full length.
ENDS	
FRONT RAIL	Formed steel, bolted.
BUMPER	CMVSS 223-RIG approved (in accordance with Canada & USA regulation). Galvanized (G164) steel, bolted uprights to frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground.
POCKETS	2 bolted galvanised pockets at front for removable headboard.
BUMPER	2 rubber dock, at the end of rear rail.
REAR RAIL	Formed steel.
ELECTRICAL	
FRONT CONNECTOR	7 way (SAE J560).
ELECTRICAL SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.
MAIN SYSTEM	Grote Ultra Blue LED, sealed beams, tail lights, markers lights "Dot", identification lights (2 1/2" dia.), licence light.
FLASHERS	Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber. Warning lamp Tiremaax installed on road side front rail.
LANDING GEAR	Holland, Mark V (LGS-4F315), with mounting plate & solid axles. ***fully galvanized***
SAND SHOES	10" x 11 1/2".



ITEM	DESCRIPTION
CRANK	Road side.
BOGIE	
BASIC MECHANICAL	
BOGIE	Slider, Hutch H-9000, "UHMV" slider plastic pads, 4 locking pins, For 49" spread tandem spring suspension. 6" c/c between locating holes, (48" travel).
MECHANICAL (GROUND AXLES)	
SUSPENSION	Hutch H-9700, tandem, under mount, 49" spread.
U-BOLTS	With nuts at bottom.
SPRINGS	3 leaves, model TRA 2741, 12 000 lbs capacity.
AXLE(S)	Meritor, TN 467_L, 22 500 lbs. capacity.
CAM SHAFTS	28 splines.
TRACK	77 1/2".
DUST SHIELDS	None (Meritor axles).
BRAKES	16 1/2" standard, FRAS-LE MA212Q+ extended life lining.
BEARINGS	HM 218248 and HM 212049
SLACK ADJUSTERS	Meritor, automatic, 28 splines.
SEALS	Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90.
BRAKE CHAMBERS	T.S.E. brake, "Omni brake" (30-30). (4 years warranty by T.S.E. for parts only).
HUBS AND DRUMS	10 stud disc hubs, balanced drums outboard mount, 285.75mm B.C., single flange nuts. For dual aluminum wheels.
RIMS	22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes.
TIRES	Continental, 11 R 22.5 HT3 ECO-PLUS 14 ply (41.2") Automatic Tire inflation System Hendrickson Tiremaax.
AIR SYSTEM	
GLAD HANDS	Fixed.
AIR VALVES	Meritor Wabco, ABS, 2 sensors 1 modulator.
AUTOMATIC TIRE INFLATION	Automatic Tire inflation System Hendrickson Tiremaax PRO. For axles with bearings HM 218248 and HM 212049, dual tires. NOTE: Axles prep. fees included for undressed axle. *** Maximum allowable tire pressure for this device is 120psi *** (tandem application) "Automatic Tire Inflation Systems", REMARK: Make sure the system is adjusted to the same tires pressure written on the serial plate.
ACCESSORIES	
REGISTRATION HOLDER	One plastic, Betts-PS-1 or equivalent.
MUD FLAPS	One set, rubber black with moose and vertical grooves to reduce spray.
SLIDING TRACK	Full length, "LL" extruded aluminum, road side.
WINCHES	Qty: 12, ANCRA #49207-137-XZ, zinc plated slider (low profil 5 7/8").
FINISHING	
PAINT	Ready for Galvanized plateform.
BOGIE	One coat of epoxy primer and one acrylic urethane top coats,



ITEM	DESCRIPTION
RETROREFLECTIVE TAPES	Color: GREY metallic, code: Q37-939514.
WHEELS OR RIMS	Axles (wheel end) included. (Tandem).
PAINT	Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar.
	White (power top coat).
	Vin plate to be made of metal. Pre-drill the web prior to galvanizing
ADDITIONAL OPTIONS	Estimated empty weight is 12,951 LBS +/- 3%
GALVANIZED CHOICES	Galvanized choices.
PLATFORM	Galvanized platform. (no paint)
	** WARNING: holes parachute shaped required for dripping **
CROSSMEMBERS	Galvanized
FRONT RAIL	Galvanized
SIDE RAIL	Galvanized
REAR RAIL	Galvanized
BUMPER	Galvanized
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.