

Length 34' STEEL TUB Tarp Bar NONE Body NONE Width Tarp NONE Accessories Side Height 66" + ANGLE ON TOP (1) **Bow Holders** NONE Top Rail 1/4" x 4" x 8" Tarp Bows NONE Tarp Baske Side Material 1/4" AR450 NONE Tarp Hooks REMARK (2) **TAILGATE** Bulkhead Mat'l 1/4" AR450 (SLOPE NOSE) **FULL** Height 1/4" ALUM S & P **Side Options** 3"x3" ANGLE ON TOP RAILS Bulkhead Mat'l Thkness NONE 1/4" AR450 NONE Floor Mat'l Options Slope FLOOR LENGTH - 33'-1" Body Fenders SQUARE OFF - WITH FLAP **OVERSLUNG** Hinges Crsmbr Spacing 12" Ladders (Out) D/S-FRONT & REAR Side Swing YES W/ IGC-P/S HINGE D/S-BH - BOLT ON LADDER Gateseal NONE Floor Options NONE Inside NONE Full Longitudinal 1/4" X 4" X 4" Safety Latch ONE EACH SIDE FRONT P/S Shovel Hgr Tailgate Control AIR / FRAME SWITCH Dirt Shedders N/A Coal/Grain Door NONE Body Pkg STEEL SIDE SKIRT Light Panel FULL - LED - NOTCHED **FULL LENGTH Options** Coal Chute NONE Vibrator NONE LED - FRONT & REAR + STRAP ACROSS BOTTOM Marker Lights **Gate Options** STD+ Mudflaps MMTS LED-CNTR MRKR/TURN COMBO **ACROSS REAR CHASSIS** Apron

833-418-9777

800-569-1400

800-854-5306

866-315-0235

800-854-5310

AVAILABLE

(in (ii)

CHASSIS SPECIFICATIONS			
TANDEM	ABS 4S/2M	Tire Carrier	ONE - P/S ACCESS
ALUMINUM		Landing Gear	2 SPEED JOST A450
34'			D/S CRANK-BLACK
96"	Independ. Susp(s)	Chassis Lights	NONE
85-265	X-MBR ONLY FOR 3RD AXLE		
STD	HT250	Elec Coupler	7 WAY + STD 7 WAY
18"	Distance: 103"		
1/2" W/ 3/8" MOUNT	From: REAR AXLE	Hyd Tank	NONE
49"		Hyd Hose Fitting	WINGNUT
6"	Controls	Hyd Hose Length	108"
21.5"		Tow Hooks	NONE
368.5"		Paint	EAST BLACK BODY
AAT30K/E2-1	Location		EAST BLACK FRAME
FRAME & ELEC CC(AUX)	Axle(s)	Tarp Bar Tape	NONE
52"			
NONE	Accessories	Chassis	
AIR		Options:	
TP - HXL-5	Brakes		
25K - RATED (3)	Drums		MUDFLAP ON CHASSIS
16-1/2" x 7"	Hubs		
CAST			
10 STUD STEEL	Wheels		
GREASED			
8.25 x 24.5 8 STEEL	Tires		
	ALUMINUM 34' 96" 85-265 STD 18" 1/2" W/ 3/8" MOUNT 49" 6" 21.5" 368.5" AAT30K/E2-1 FRAME & ELEC CC(AUX) 52" NONE AIR TP - HXL-5 25K - RATED (3) 16-1/2" x 7" CAST 10 STUD STEEL GREASED	TANDEM ABS 4S/2M ALUMINUM 34' 96" Independ. Susp(s) 85-265 X-MBR ONLY FOR 3RD AXLE STD HT250 18" Distance: 103" 1/2" W/ 3/8" MOUNT From: REAR AXLE 49" Controls 21.5" 368.5" AAT30K/E2-1 Location FRAME & ELEC CC(AUX) Axle(s) 52" NONE AIR TP - HXL-5 25K - RATED (3) Drums 16-1/2" x 7" Hubs CAST Wheels GREASED Wheels	TANDEM ABS 4S/2M Tire Carrier ALUMINUM Landing Gear 34' Chassis Lights 85-265 X-MBR ONLY FOR 3RD AXLE STD HT250 Elec Coupler 18" Distance: 103" Hyd Tank 49" Hyd Hyd Hose Fitting 6" Controls Hyd Hose Length 21.5" Tow Hooks 368.5" Paint AAT30K/E2-1 Location FRAME & ELEC CC(AUX) Axle(s) Tarp Bar Tape 52" Tow Hooks AIR Options: TP - HXL-5 Brakes Options: 25K - RATED (3) Drums Chassis 16-1/2" x 7" Hubs Hubs CAST Wheels Image: Complex of the

REMARKS: CHANGE 1

1. NO CENTER BOLSTER

Tires

TARP HOOKS: BURNOUT DESIGN-REF 54643 FOR LOCATIONS - 8 EACH SIDE + 4 FRONT & 4 REAR

17,874 WEIGHT:

25,000 # - RATED LONG STROKE CHAMBERS AND SLACKS

11R 24.5 R268 ECOPIA 16PLY

4. ANGLE IS ON TOP OF TOP RAIL-NOT FLUSH WITH BULKHEAD OR TAILGATE.