

# HALE TRAILER BRAKE & WHEEL



A025965-A025969  
VIN: A5739-A5743

## SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

### Renegade N12 Air Tandem, 12 inch Loaded Deck Height, Narrow Hydraulic Gooseneck (Model: RENEGADE N12)

RENXLN12F\*833542

Est. Wt.: 20,385# +/- 3%

#### TRAILER - GENERAL

**Capacity:** 30 tons in 16-foot length - GAWR and tire ratings determine legal loads- 30 tons in 20 foot with 3rd axle

**Load Base:** 16-foot rigid 2-point load centered in deck

**Length (Trailer Only):** 53 feet 0 inches

**Width:** 8 feet 6 inches

**Compatibility:** Designed to accept optional low profile third flip axle

#### GOOSENECK

**Gooseneck Design:** Narrow hydraulic removable non-ground bearing - swing radius of 96 inches (11 ft 2 in overall gooseneck length) - set up for wet line operation

**Loaded Fifth Wheel Height:** 50 in nominal loaded fifth wheel height via dual cam pawl arm assembly with 7 ride height positions

**Power Source:** None

#### DECK

**Deck Design:** Flat level deck design

**Deck Length:** 32 feet 11 inches clear deck length

**Loaded Deck Height:** 12 inches with 4 inch ground clearance (Fully Loaded)

**Crossmembers:** On 18 inch centers

**Flooring:** 1 3/8 inch nominal Apitong wood (full width)

**Recessed Floor Mounted D-Ring Package:** None

**Front Ramps:** None, front of deck sloped top down to assist in loading with traction cleats

**Extension Brackets:** None

**Front Bogie Ramp:** Sloped steel bogie ramp (full width)

**Deck to Bogie Connection:** Fixed

#### AXLES

**Number of Axles:** 2

**Axle Capacity:** 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.

**Axle Spread:** 50 inches (between axles)

**Brakes:** 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount

**Spring Brakes:** Spring brakes (2 axles)

**Dust Shields:** None

#### SUSPENSION

**Framework:** All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs

**Suspension:** Air ride with automatic controls

**ABS:** 4S/2M system without diagnostic tool and cable

**Load Scale:** None Standard

#### WHEELS AND TIRES

**Wheels:** 8.25 x 22.5 Lvl One buffed outside/steel inside - hub-piloted

**Tire Brand:** OEM Standard

**Tires:** 255/70R 22.5 H ply OEM Standard

<b>Hubodometer: None Standard</b>	
<b>Tire Inflation: None Standard</b>	
<b>REAR BRIDGE</b>	
<b>Covered Rear Bogie:</b> Rear bogie platform with 1 1/8 inch wood floor	
<b>Rear Bogie Height:</b> 41.5 inches	
<b>Bumper:</b> 3 tail light package	
<b>Connections for Future Axle Attachment:</b> Air and electrical connections to go along with connecting ears	
<b>Mini Boom Trough &amp; Traction Cleats: None</b>	
<b>Liquid Filled Gauge:</b> Standard	
<b>LIGHTING</b>	
<b>Electrical System:</b> DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
<b>Marker Lights:</b> 6 marker lights per side including mid-turn	
<b>Electrical Receptacle:</b> J560 7-pin connector	
<b>Additional Marker Lights: None Standard</b>	
<b>PAINT</b>	
<b>Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001</b>	
<b>MISCELLANEOUS</b>	
<b>Lash Rings:</b> 12 pair - 24 total	
<b>Flag Holders:</b> 2 pair flag holders	
<b>Registration/Document Holder:</b> Registration/document holder installed	
<b>Please Note:</b> Price includes commodity surcharges	
<b>Commercial Terms:</b> Ex Works- Springville, AL, USA	
<b>AVAILABLE COMPONENTS</b>	
<b>Flip Axle: None</b>	
<b>Dust Shields on Flip Axle: None</b>	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.