



A026072-A026077 VIN: 44414-44419

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Raleigh, NC 833-418-9777 800-569-1400 Delmar, DE: 866-486-1400 Scranton, PA: Des Moines, IA: Springfield, MA: 800-854-5306 888-673-5011 Elkton, MD: Voorhees, NJ: 800-544-7127 866-315-0235 Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer f 쭞 🛅 🎯 🔠

800-232-6535 *FINANCING AVAILABLE

Model: AC-20 Capacity in tons: 20

1. TONGUE

Pintle eye (3" ID) with 48" chain and grab hooks

Tongue 5'-6" with lockable tool box with aluminum diamond plate lid - move hinge 4" forward

Drop leg 2-speed, 50,000# crank down dual landing leg, mounted to main beams and

headboard

Electrical receptacle Seven pin connector Headboard 8" high full width

2. DECK

Deck section length

Deck section design One piece tongue, main beam and beavertail (cold formed)

27'-0" (21'-0" flat with 6'-0" beavertail)

Deck section width 8'-6" Loaded deck height 32-1/4"

Flooring 1-1/2" apitong - individual wheel well covers

Lash rings 10 total

4 each side on flat deck (straight style), 8 total 1 each side on beavertail (straight style), 2 total

Main beams12" deep hi-tensileCross members6" deep hi-tensileSide members8" deep hi-tensile

Beavertail 6'-0" Double break with wood flooring full width

5'-0" with wood flooring with 3 springs per ramp and grab handles

3. RUNNING GEAR

Ramps

Number of axles

Axle capacity 25,000# Full width track

Brakes 12-1/4" x 7-1/2" air with 2S/1M ABS. Spring brakes on both axles.

Wheels Steel disc with oil seals (6.75 x 17.5)

Tires Eight (8) 215/75R17.5 (H) 16PR radials
Use valve stem extensions on inside wheels

Suspension 44,800# Hutch spring

4. GENERAL

Lights and wiring 12 volt LED system (license plate regular), supplied with female 7-way plug on

tongue, SUPPLY JUMPER CORD FOR TRUCK

Paint Valspar standard Talbert black, R-Cure 800 series paint Additional general specifications Formed step in front of 1st axle both sides of trailer