



A026078-A026081 VIN: 44407-44410

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Raleigh, NC 833-418-9777 800-569-1400 Delmar, DE: 866-486-1400 Scranton, PA: Des Moines, IA: Springfield, MA: 800-854-5306 888-673-5011 Elkton, MD: Voorhees, NJ: 800-544-7127 866-315-0235 Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer f 쭞 🛅 🎯 🔠

800-232-6535 *FINANCING AVAILABLE

Model: AC-20-AR Capacity in tons: 20

1. TONGUE

Pintle eye (3" ID) with 48" chain and grab hooks

Tongue 5'-6" with lockable tool box with aluminum diamond plate lid - move hinge 4" forward

Drop leg 2-speed, 50,000# crank down dual landing leg, mounted to main beams and

headboard

Electrical receptacle Seven pin connector Headboard 8" high full width **2. DECK**

Deck section design One piece tongue, main beam and beavertail (cold formed)

Deck section length 27'-0" (21'-0" flat with 6'-0" beavertail)

Deck section width 8'-6"
Loaded deck height 32-1/4"

Flooring 1-1/2" apitong with individual wheel wells

Lash rings 10 total -

4 each side on flat deck (straight style), 8 total 1 each side on beavertail (straight style), 2 total

Cross members 6" deep hi-tensile
Main beams 12" deep hi-tensile
Side members 8" deep hi-tensile

Beavertail 6'-0" Double break with wood flooring full width

Ramps 38" wide x 6'-6" long air ramps with wood flooring, stored vertically with lock bar

3. RUNNING GEAR

Number of axles 2

Axle capacity 25,000#, full width track

Brakes 12-1/4" x 7-1/2" air with 2S/1M ABS. Spring brakes on both axles.

Wheels Steel disc with oil seals (6.75 x 17.5)

Tires Eight (8) 215/75R17.5 (H) 16PR radials

Use valve stem extensions on inside wheels

Suspension 44,800# Hutch spring

4. GENERAL

Lights and wiring 12 volt LED system (license plate regular), supplied with female 7-way plug on

tongue, SUPPLY JUMPER CORD FOR TRUCK

Paint Valspar standard Talbert black

Estimated empty weight 9,140#

Additional general specifications Formed step in front of 1st axle both sides of trailer