

HALE

TRAILER

BRAKE & WHEEL



A026118-A026120
VIN: 00117, 00123,
00124

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Baltimore, MD: 888-601-7500

Concord, NC: 800-438-2250

Delmar, DE: 866-486-1400

Des Moines, IA: 888-673-5011

Elkton, MD: 800-544-7127

Jacksonville, FL: 800-828-3055

Little Rock, AR: 833-424-8944

Portland, ME: 800-325-4253

Raleigh, NC: 833-418-9777

Scranton, PA: 800-569-1400

Springfield, MA: 800-854-5306

Voorhees, NJ: 866-315-0235

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Base Weight: 12,760

30ART 30 Ton Tridem Air Tilt/Air Ramp Tags

TRAILER

Overall Length 39 ft. 6 in.
Overall Width 102 in.
Weight lbs +/- 2% 13406, including options
A-Frame 6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
Hitch 3 in. pintle eye, adjustable 7 position, 15 in. to 28 1/2 in.

DECK

Deck Length 26 ft.
Loaded Deck Height 34 in.
Main Frame Hi-Tensile Wide Flange 14 in. @ 30
Cross Members Hi-Tensile 6 in. Channel @ 8.2
Side Rail Hi-Tensile 8 in. Channel @ 11.5 Open on Inside
Air Tilt Deck * 4 Air Bags
Floor 1 3/8 in. x 7 in. Keruing Shiplapped
Landing Gear Dual Holland Mark V 2 Speed
Step *NPO*: Bolt on, Located on Front Corner of Deck, Driver Side and 1 on Passenger side ahead of lead axle

SUSPENSION/AXLES

Axles 25,000 lbs Capacity 77.5 in. Track ,1 Lift Axle with Control Box
Spread 49 in.
Suspension Heavy Duty spring ride., 1 Ridewell RAR 260 Underslung Air ride 25,000lbs. (includes air gauge)
Alum Air Tank *NPO*: Drain plug with cable
Brakes Quick Change 12 1/4 in. x 7 in.
Brake Chamber #3030, All Axles
Air Brake System 2S/1M
Air Tank(s) Aluminum
Bearings Oil Bath
Slack Adjusters Automatic
Hubs & Drums 8 Stud Unimount c/w Cast Drums
Tires 235/75R17.5 16 ply
Wheels Alum. Wheel Pkg. 17.5 (6 steel, 6 polished)

BEAVERTAIL

Length 6 ft. @ 6 Degree Slope, Planked In

RAMPS

Length 38 in. x 76 in. Air Operated Planked
Brackets *NPO*: To hold ramp brace when not in use, 1 per side

GENERAL SPECIFICATIONS

Electrical System Modular, Vapor Proof GROTE Ultra Blue
Front Connector SAE J560 7 Pin
Lights *NPO*: Switch for strobes mounted in toolbox

Lights	Amber Flashing Strobe (Mounted in Ramps)
Finishing	Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
Color	Black
Mudflaps	1 set of BWS at Rear
Toolbox	Full A Frame Mounted with Solid Bottom and Cover
Load Securement	11 Pair of D-rings: 7 pr main deck, evenly spaced; 2 pr on B/T; 1 pr on main beam at headboard, 1 pr on top of A Frame top flange on each side of the toolbox
Fenders	3/16 in. Deck Plate

GVWR Rating is based on standard configuration and a 15% Tongue weight distribution

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.