

HALE

TRAILER

BRAKE & WHEEL



A026121-A026124
VIN: 000118-000121

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Base Weight: 12,100

42 ET2X 42 ft. Tandem Equipment

TRAILER

Overall Length *NPO*: 45 ft.
Overall Width 102 in.
Weight lbs +/- 2% 14176, including options

GOOSENECK

Coupler Weld in King Pin
Coupler Plate 5/16 in. Hi-Tensile, 48 in. Height
Coupler Location 18 in.
Length 10 ft. 6 in.
Cross Members Hi-Tensile 4 in. Jr. I-beam @ 16 in. O/C
Swing Clearance 83 in.
Floor *NPO*: 1 3/8 in. Apitong
Web 1/4 in. Hi-Tensile

DECK

Deck Length *NPO*: 28 ft. 7 in.
Loaded Deck Height 35 in.
Main Frame 3/8 in. x 5 in. Top and Bottom Flanges 100 KSI
Cross Members Hi-Tensile Standard 4 in. I-beam @ 12 in. O/C on Lower Deck w/ Knee Braces
Side Rail 6 in. @ 8.2 Channel
Web 3/16 in. Hi-Tensile
Floor *NPO*: 1 3/8 in. Apitong
Landing Gear Dual 2 Speed
Load Securement 14, Pair of side mounted D-rings: 3 pr GNK, 2 pr B/T, 9 pr main deck, evenly spaced

SUSPENSION/AXLES

Axles 25,000 lbs Capacity
Spread 49 in.
Suspension Ridewell RAR 260 U/S 6 1/2 in. Air Ride 25,000 lbs - includes air gauge and dump valve in enclosure
Brakes Quick Change 12 1/4 in. x 7 in.
Brake Chamber #3030, All Axles
Air Brake System 2S/1M
Air Tank(s) Aluminum
Camshafts 28 Spline Non Enclosed
Slack Adjusters Automatic
Hubs & Drums 8 Stud Unimount C / W Cast Drums
Tires *NPO*: Tire Upgrade to 245/70R17.5 Continental HTL2 ECO
Wheels Alum. Wheel Pkg. 17.5 (4 steel, 4 polished)
Pressure equalization *NPO*: 2, Crossfire Dual tire pressure equalization system

BEAVERTAIL

Length 5 ft. @ 8 degree slope, Planked

RAMPS

RAMPS

Rear	* 38 in. x 76 in. Air Operated Planked In
Front	Two Removable Aluminum Ramps to access GNK, 5ft long, Storage under GNK deck

GENERAL SPECIFICATIONS

Electrical System	Modular, Vapor Proof GROTE Ultra Blue
Front Connector	SAE J560 7 Pin
Rear Connector	4 Pin Plug
Lights	LED CMVSS 108 / FMVSS 108
Lights	LED Light Enhancement Package (6 additional lights per side)
Finishing	Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
Color	Black
Mudflaps	1 set of BWS at rear
Fenders	3/16 in. Formed Deck Plate
Tool Box	Alum. (45 in. X 18 in. X 18 in.) + Brackets (Drivers Side): in front of lead axle

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.