

HALE

TRAILER

BRAKE & WHEEL



A026180-A026191
VINS: A5816-A5827

SALES | RENTALS | PARTS | SERVICE

| | | | |
|-------------------|--------------|------------------|--------------|
| Allentown, PA: | 800-383-8894 | Little Rock, AR: | 833-424-8944 |
| Baltimore, MD: | 888-601-7500 | Portland, ME: | 800-325-4253 |
| Concord, NC: | 800-438-2250 | Raleigh, NC: | 833-418-9777 |
| Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |
| Jacksonville, FL: | 800-828-3055 | Walpole, MA: | 800-854-5310 |

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

| Workhorse 55LCC Air Tridem (Flat Level Deck) (Model: WORKHORSE 55LCC) | |
|---|--------------------------|
| WKH55LCC*F*826543 | Est. Wt.: 23,330# +/- 3% |
| TRAILER - GENERAL | |
| Capacity: 55 tons in 13-foot length with 4 axles close coupled; - GAWR and GVWR determine legal payloads | |
| Load Base: 13-foot rigid 2-point load centered in deck area with 4 axles close coupled | |
| Length (Trailer Only): 52 feet 10 inches (with standard deck length and axle spread) | |
| Compatibility: Designed to accept 55/60 rear axle below | |
| Accent Package: None | |
| GOOSENECK | |
| Design: Narrow hydraulic removable non-ground bearing - swing radius of 108 inches (12ft 7in overall gooseneck length) set up for wetline operation | |
| Loaded Fifth Wheel Height: Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal) | |
| Kingpin: Removable kingpin at 89 and 108 inch radius | |
| Power Source: Set up for wet line operation | |
| Tool Box: None | |
| VIN Plate: Bilingual VIN plate | |
| Registration/Document Holder: Registration/document holder installed | |
| Hydraulic Fittings: OEM Standard 1/2 inch | |
| DECK | |
| Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs | |
| Deck Length: Flat Level Deck (FLD) design - standard 26 feet clear deck length- OAL 52 feet 10 inches | |
| Chain Slots: Chain Slots on top flange of siderails | |
| Deck Width: 8 feet 6 inches overall (unless optional deck width is selected) | |
| Loaded Deck Height: 18 inches with 6 inches ground clearance | |
| Crossmembers: On 24 inch centers (nominal) | |
| Flooring: 2 inch nominal wood - side rails only | |
| Front Ramps: Manual front approach ramps included | |
| Extension Brackets: 13 pair - 26 total removable swing type, 2 pair - 4 total heavy duty removable hook-on type (26 swing type, 4 hook-on type on 27 foot deck) | |
| Tool Box: 2 Fully covered trays in front of deck between mainbeams with lockable covers | |
| Hammer Plate: Hammer Plate installed over recessed crossmembers. Perforated plate under hammer plate forming two storage areas. 2 pair lashing ring located in last two deck sections. | |
| REAR BRIDGE | |
| Front Bogie Ramp: Included as standard | |
| Boom Trough: Low Boom Well V-style boom trough with bolt-in V pan | |
| Deck to Bogie Connection: Fixed | |
| Bolsters: Recessed | |
| Covered Rear Bogie: None Standard | |
| Rear Bogie Height: 40 7/8 inches to top flange - 36 5/8 inches to top of bolsters | |
| Connections for Future Axle Attachment: Air and electrical connections to go along with connecting ears | |
| Bumper: Heavy duty V-style rear bumper | |

| AXLES | |
|--|--|
| Number of Axles: 3 axles | |
| Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components. | |
| Axle Spread: 54.5 inches (between axles) | |
| Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount | |
| Spring Brakes: None | |
| Dust Shields: None | |
| SUSPENSION | |
| Suspension: Air ride | |
| ABS: None required | |
| First Axle Lift: None | |
| Third Axle Lift: Air lift | |
| Mechanical Ride Height Control: 7-position mechanical ride height control system | |
| Manual Dump Valve: Manual Dump Valve (Push Pull) | |
| Liquid Filled Gauge: None | |
| Load Scale: None Standard | |
| WHEELS AND TIRES | |
| Wheels: 8.25 x 22.5 LVL One buffed outside/steel inside - hub-piloted | |
| Tires: 275/70R 22.5 OEM standard | |
| Hubodometer: None Standard | |
| Tire Inflation: None Standard | |
| LIGHTING | |
| Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes | |
| Tail Lights: 3 tail light package | |
| Electrical Receptacle: J560 7-pin connector | |
| Marker Lights: 3 marker lights per side including mid turn | |
| Additional Marker Lights: None Standard | |
| PAINT | |
| Paint: Fontaine black polyurethane enamel | |
| MISCELLANEOUS | |
| Lashing Rings: 19 pair - 38 total (with standard deck option) | |
| Flag Holders: Flag holders - 1 pair located at front of deck and on rear bumper | |
| AVAILABLE COMPONENTS | |
| Compatibility: Designed to accept 55/60 rear axle below | |
| Flip Axle: None standard | |
| Hydraulic Flip Axle Option: None Standard | |
| Dust Shields on Flip Axle: None standard | |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.