

HALE

TRAILER

BRAKE & WHEEL



A026231-A026233
VINS: A5808-A5810

SALES | RENTALS | PARTS | SERVICE

| | |
|---------------------------------------|--------------------------------------|
| Allentown, PA: 800-383-8894 | Little Rock, AR: 833-424-8944 |
| Baltimore, MD: 888-601-7500 | Portland, ME: 800-325-4253 |
| Concord, NC: 800-438-2250 | Raleigh, NC: 833-418-9777 |
| Delmar, DE: 866-486-1400 | Scranton, PA: 800-569-1400 |
| Des Moines, IA: 888-673-5011 | Springfield, MA: 800-854-5306 |
| Elkton, MD: 800-544-7127 | Voorhees, NJ: 866-315-0235 |
| Jacksonville, FL: 800-828-3055 | Walpole, MA: 800-854-5310 |

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Renegade XN20 Extendable Deck, Air Tandem, 20 inch Loaded Deck Height, Narrow Hydraulic Gooseneck (Model: RENEGADE XN20)

| | |
|--|--------------------------|
| RENLXT40NF*834542 | Est. Wt.: 23,685# +/- 3% |
| TRAILER - GENERAL | |
| Capacity: 40 tons in 16-foot length - GAWR and GVWR determine legal loads | |
| Load Base: 16-foot rigid 2-point load centered in deck | |
| Length (Trailer Only): 50 feet 1 inch (closed); 71 feet 1 inch (open) | |
| Width: 8 feet 6 inches | |
| Compatibility: Designed to accept optional third flip axle | |
| GOOSENECK | |
| Gooseneck Design: Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11 ft 11 in overall gooseneck length) - set up for wet line operation | |
| Loaded Fifth Wheel Height: Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal) | |
| Power Source: None | |
| DECK | |
| Deck Design: Flat level telescopic deck design | |
| Deck Length: 34 feet 0 inches clear deck length (retracted) - 60 feet 0 inches (extended) **Note when option is selected trailer overall length is 55 ft 1 in | |
| Loaded Deck Height: 20 inches with 6 inches ground clearance | |
| Flooring: 1 3/8 inch nominal wood (full width) | |
| Recessed Floor Mounted D-Ring Package: None | |
| Crossmembers: On 24 inch centers | |
| Front Ramps: None, front of deck sloped top down to assist in loading with traction cleats | |
| Extension Brackets: Outriggers - 14 pair - 28 total removable swing type, 1 pair - 2 total removable hook-on type | |
| Front Bogie Ramp: Sloped steel bogie ramp (full width) | |
| Deck to Bogie Connection: Fixed | |
| AXLES | |
| Number of Axles: 2 | |
| Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components. | |
| Axle Spread: 54.5 inches spread (between axles) | |
| Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount | |
| Dust Shields: None | |
| Spring Brakes: Spring brakes on 2 axles | |
| SUSPENSION | |
| Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs | |
| Suspension: Air ride with automatic controls | |
| First Axle Lift: Chain lift included on first axle when 34ft deck is selected | |
| ABS: 4S/2M system without diagnostic tool and cable | |
| Load Scale: None Standard | |
| WHEELS AND TIRES | |
| Wheels: 8.25 x 22.5 LVL One buffed outside/steel inside - hub-piloted | |

| | |
|--|--|
| Tires: 255/70R 22.5 H ply OEM Standard | |
| Hubodometer: None Standard | |
| Tire Inflation: None Standard | |
| REAR BRIDGE | |
| Covered Rear Bogie: Rear bogie platform with 1 1/8 inch wood floor | |
| Rear Bogie Height: 41 inches | |
| Bumper: 3 tail light package | |
| Mini Boom Trough & Traction Cleats: None | |
| Connections for Future Axle Attachment: Air and electrical connections to go along with connecting ears | |
| Liquid Filled Gauge: Included | |
| Accent Package: Stainless steel bumper insert | |
| LIGHTING | |
| Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes | |
| Electrical Receptacle: J560 7-pin connector | |
| Marker Lights: 8 marker lights per side including mid-turn | |
| Additional Marker Lights: None Standard | |
| PAINT | |
| Paint: Fontaine black polyurethane enamel | |
| MISCELLANEOUS | |
| Lash Rings: 12 pair - 24 total | |
| Flag Holders: 2 pair flag holders | |
| VIN Plate: Bilingual VIN plate | |
| Registration/Document Holder: Registration/document holder installed | |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.