

# HALE

## TRAILER

### BRAKE & WHEEL



**A026256-A026257**  
**VIN: 134-135**

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b>	<b>800-383-8894</b>	<b>Little Rock, AR:</b>	<b>833-424-8944</b>
<b>Baltimore, MD:</b>	<b>888-601-7500</b>	<b>Portland, ME:</b>	<b>800-325-4253</b>
<b>Concord, NC:</b>	<b>800-438-2250</b>	<b>Raleigh, NC:</b>	<b>833-418-9777</b>
<b>Delmar, DE:</b>	<b>866-486-1400</b>	<b>Scranton, PA:</b>	<b>800-569-1400</b>
<b>Des Moines, IA:</b>	<b>888-673-5011</b>	<b>Springfield, MA:</b>	<b>800-854-5306</b>
<b>Elkton, MD:</b>	<b>800-544-7127</b>	<b>Voorhees, NJ:</b>	<b>866-315-0235</b>
<b>Jacksonville, FL:</b>	<b>800-828-3055</b>	<b>Walpole, MA:</b>	<b>800-854-5310</b>

haletrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

**Base Weight:** 12,300

#### 30ANR 30 Ton Tridem Air Tilt/No Ramp Tags

<b>TRAILER</b>		
Overall Length	37 ft. 6 in.	
Overall Width	102 in.	
Weight lbs +/- 2%	13024, including options	
A-Frame	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam	
Hitch	3 in. pintle eye, adjustable 7 position, 15 in. to 28 1/2 in.	
<b>DECK</b>		
Deck Length	24 ft.	
Loaded Deck Height	34 in.	
Main Frame	Hi-Tensile Wide Flange 14 in. @ 30	
Cross Members	Hi-Tensile 6 in. Channel @ 8.2	
Side Rail	Hi-Tensile 8 in. Channel @ 11.5 open on inside	
Air Tilt Deck	* 4 Air Bags	
Floor	1 3/8 in. x 7 in. Keruing Shiplapped	
Rear	Wedge Style bumper with air assisted tilt deck for ground loading	
Landing Gear	*NPO*: Dual 2 Speed , Galvanized Landing Gear	
Step	*NPO*: Bolt on, Located on Front Corner of deck, Driver side and 1 on Passenger side ahead of lead axle	
<b>SUSPENSION/AXLES</b>		
Axles	25,000 lbs Capacity 77.5 in. Track ,1 Lift Axle with Control Box	
Spread	49 in.	
Suspension	Heavy Duty spring ride., 1 Ridewell RAR 260 Underslung Air ride 25,000lbs. (includes air gauge)	
Alum Air Tank	*NPO*: Drain plug with cable	
Brakes	Quick Change 12 1/4 in. x 7 in.	
Brake Chamber	#3030, All Axles	
Air Brake System	2S/1M	
Air Tank(s)	Aluminum	
Bearings	Oil Bath	
Slack Adjusters	Automatic	
Hubs & Drums	8 Stud Unimount C / W Cast Drums	
Tires	235/75R17.5 16 ply	
Wheels	Alum. Wheel Pkg. 17.5 (6 steel, 6 polished)	
<b>BEAVERTAIL</b>		
Length	6 ft. @ 8 degree slope, Self Cleaning Outside , Planked in inside	
<b>GENERAL SPECIFICATIONS</b>		
Electrical System	Modular, Vapor Proof GROTE Ultra Blue	
Front Connector	SAE J560 7 Pin	
Lights	LED CMVSS 108 / FMVSS 108	
Lights	Amber Flashing Strobe Lights(Mounted in Bumper)	
Color	Galvanized	

**GENERAL SPECIFICATIONS**

<b>Mudflaps</b>	1 set of BWS at rear
<b>Toolbox</b>	Full A Frame mounted with solid bottom and aluminum cover
<b>Load Securement</b>	11 pair of D-rings: 7 pr on main deck, evenly spaced, 2 pr B/T, 1 pr on top of main beam at headboard; 1 pr on top of A frame top flange, one on each side of toolbox (Ref - wo#10015744-47)
<b>Fenders</b>	3/16 in. Deck plate

GVWR Rating is based on standard configuration and a 15% Tongue weight distribution

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.