

# HALE

## TRAILER

### BRAKE & WHEEL



A026258-A026260

VIN: 00130-00131

& 00140

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Little Rock, AR: 833-424-8944

Baltimore, MD: 888-601-7500

Portland, ME: 800-325-4253

Concord, NC: 800-438-2250

Raleigh, NC: 833-418-9777

Delmar, DE: 866-486-1400

Scranton, PA: 800-569-1400

Des Moines, IA: 888-673-5011

Springfield, MA: 800-854-5306

Elkton, MD: 800-544-7127

Voorhees, NJ: 866-315-0235

Jacksonville, FL: 800-828-3055

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 \*FINANCING AVAILABLE

Base Weight: 9,000

## 22.5NTT 22.5 Ton Tandem Non Tilt Tags

### TRAILER

Overall Length	34 ft. 8 in.
Overall Width	102 in.
Weight lbs +/- 2%	10000, including options
A-Frame	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
Hitch	3 in. pintle eye, adjustable 7 position, 19 in. to 33 in.

### DECK

Deck Length	21 ft.
Loaded Deck Height	34 in.
Main Frame	Hi-Tensile Wide Flange 14 in. @ 26
Cross Members	Hi-Tensile 5 in. Channel @ 6.7
Side Rail	Hi-Tensile 7 in. Channel @ 9.8 open on inside
Floor	1 3/8 in. x 7 in. Keruing Shiplapped
Landing Gear	*NPO*: Dual Holland Mark V 2 Speed
Step	*NPO*: Bolt on, Located on Front Corner of deck, Driver side and 1 on Passenger side ahead of lead axle

### SUSPENSION/AXLES

Axles	25,000 lbs Capacity 77.5 in. Track
Spread	49 in.
Suspension	Heavy Duty spring ride
Alum Air Tank	*NPO*: Drain plug with cable
Brakes	Quick Change 12 1/4 in. x 7 in.
Brake Chamber	#3030, All Axles
Air Brake System	2S/1M
Air Tank(s)	Aluminum
Bearings	Oil Bath
Slack Adjusters	Automatic
Hubs & Drums	8 Stud Unimount C / W Cast Drums
Tires	235/75R17.5 16 ply
Wheels	Alum. Wheel Pkg. 17.5 (4 steel, 4 polished)

### BEAVERTAIL

Length	6 ft. Beavertail, Planked
--------	---------------------------

### RAMPS

Length	* 38 in. x 76 in. Wood Filled Air Operated Ramp
Ramp Support	*NPO*: Ramp Support
Brackets	*NPO*: To hold ramp brace when not in use, 1 per side

### GENERAL SPECIFICATIONS

Electrical System	Modular, Vapor Proof GROTE Ultra Blue
Lights	LED CMVSS 108 / FMVSS 108
Lights	*NPO*: Amber Flashing Strobe Lights(Mounted in Ramps)
Lights	*NPO*: Switch for strobes mounted in toolbox

**GENERAL SPECIFICATIONS**

<b>Front Connector</b>	SAE J560 7 Pin
<b>Finishing</b>	Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
<b>Color</b>	Black
<b>Mudflaps</b>	1 set of BWS at rear
<b>Toolbox</b>	Full A Frame mounted with solid bottom and cover
<b>Load Securement</b>	11 pair of D-rings: 9 pr on main deck, evenly spaced, 1 pr on top of main beam at headboard, 1 pr on top of A Frame top flange, one on each side of toolbox
<b>Fenders</b>	3/16 in. deck plate

**GVWR Rating is based on standard configuration and a 15% Tongue weight distribution**

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.