

BODY:		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	TRIAXLE-REAR LIFT
LENGTH (FEET)	48	TYPE	SINGLE	TYPE	ALUM SUB FRAME
HEIGHT (INCHES)	104	STYLE	GENESIS	AXLE TO AXLE	60" - 60"
SIDE MAT'L (OUTBOARD)	"GENESIS"	MAT'L THICKNESS	0.150	REAR AXLE SETTING	54"
FRON	Г 0.150	S / S HINGE ON	PASS. SIDE 4-3-4	5TH WHEEL HT	49"
MIDDLE	E 0.150	GATESEAL	YES	PIN SETTING	36" W/ 3/8" KP PLATE
REAR	R 0.150	GATE LADDER	CENTER-LADDER	SUSPENSION	AAT30K/E2-1
POLISHED SIDES	YES+TG+REAR PKT	TARP HOOKS	NONE	SPRINGS	AIR (9)(10(12)
ROOF	NONE	WINDERS	ONE-D/S	AXLES	TP - HXL-5
ROOF MAT'L	NONE	GATE GUIDE	YES	BRAKES	16-1/2" x 7"
BULKHEAD	3/16"BUFFED(1)(5)	GATE CONTROL	MECH - BOLT CLAW	DUSTSHIELDS	YES
TARP HOOKS	NONE	POCKETS	EXTRUDED	BRAKE CHAMBERS	STD
TARP BASKET	NONE	CROSSPIPE (S)	TWO - (8)	ABS	2S / 1M
TARP	NONE		MIDDLE-SPRING	HUBS	10 S STEEL-GREASE
CATWALK YES-INTERMEDIATE			REAR-TUBE	DRUMS	CAST
B.H. LADDER	D/S-LADDER	COMPACTOR:		WHEELS	8.25 X 24.5 (13)
CROSSMEMBER	"I"BEAM- 12" C/L	SIDE LATCH	N/A		6 STEEL/6 HP
FLOOR MAKE	KEITH-3.5" DRIVE	CENTER LATCH		TIRES	11R 24.5 R268
FLOOR MAT'L	2299 (6)(15)	PIN DIA.			ECOPIA 16PLY (14)
WEARPADS	CWS			DOLLIES	2 SPD JOST A451
TAPE COLOR	BLACK IN TOP RAIL	HYDRAULICS:		LOCATION	D/S CRANK (4)
LIGHT PANEL	LED IN TAILGATE	HOSES	TWO-4000 PSI	BUMPER	EAST UNDERRIDE
MARKER LIGHTS	LED (7)	LENGTH	108"	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	YES - LED	FITTINGS	WINGNUT	PUSH BLOCKS	YES
MUDFLAPS	STD	HP	1" FEMALE	PAINT	EAST BLACK
HOSE HANGER	YES-0N BULKHEAD	LP	1" MALE (3)(11)		
TIRE CARRIER	NONE	HOSE LOCATION	P/S-REF 89223 (2)		
		AIR & ELECTRICAL	CENTER-REF 89223		

REMARKS:

- 1. NO INSIDE BULKHEAD STEPS.
- 2. AUXILIARY ISO 7 WAY PLUG
- 3. POLYCARNOATE BOX FOR FRAME SWITCHES OLD STYLE
- 4. ADD TRUCKLITE REGISTRATION HOLDER TO D/S LANDING GEAR BRACKET.
- 5. MANDOOR IN CENTER OF BULKHEAD
- 6. T-BLOCKS @ REAR. DRIVE UNIT FLOOR OPENING MOVED FORWARD FOR TRIDEM. MAKE SURE DRIVE UNIT OPENING MISSES ALL AXLES 54" REAR AXLE SETTING
- 7. 5 PR TOP & BOTTOM NO PROTECTORS TOP ROW 16" DOWN FROM TOP OF TOP RAIL
- 8. REAR CROSSPIPE MOVE FORWARD 1' FROM STANDARD PLACEMENT.

13.25

- 9.AAT30K MAIN TANDEM w/AAL30K/R3 LIFT AXLE BEHIND TANDEM.LIFT AXLE TO HAVE SWITCH IN BOX AND ELECTRIC CAB CONTROL OPERATIONS)
- 10. GALVANIZED SUSPENSION HANGERS
- 11. RIGHT WEIGH OIL FILLED GAUGE IN LBS. FLUSH MOUNTED IN BULKHEAD ON D/S RADIUS FOR DRIVER VISIBILITY-REF 89223
- 12. LIFT AXLE TO HAVE BRAKE RELEASE.

OVERALL HEIGHT (FT)

- 13. STEEL INSIDE / ALUM OUTSIDE. USE WHEEL GUARD INSULATOR BETWEEN STEEL AND ALUMINUM WHEELS.
- 14. HENDRICKSON TIRE MAXX PRO ALL AXLES.
- 15. KEITH SPLASH GUARD HOLD DOWN BEARINGS

EMPTY WEIGHT (#) 20,333 (EMPTY WEIGHT VARIANCE +/- 3%)

CUBIC YARDS

<u>125</u>