

HALE TRAILER BRAKE & WHEEL



A026688-A026697

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Little Rock, AR: 833-424-8944

Baltimore, MD: 888-601-7500

Portland, ME: 800-325-4253

Concord, NC: 800-438-2250

Raleigh, NC: 833-418-9777

Delmar, DE: 866-486-1400

Scranton, PA: 800-569-1400

Des Moines, IA: 888-673-5011

Springfield, MA: 800-854-5306

Elkton, MD: 800-544-7127

Voorhees, NJ: 866-315-0235

Jacksonville, FL: 800-828-3055

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

XL SPECIALIZED TRAILERS

XL 55 MFG: Mini-Deck

OVERALL LENGTH 53'
OVERALL WIDTH 102"
CAPACITY 55,000 LB DISTRIBUTED
WEIGHT +/- 3% 0,000 LB

GOOSENECK

LENGTH 9' 6" FULL-WIDTH NECK
KINGPIN SETTING 16"
SWING CLEARANCE 78"
5TH WHEEL HEIGHT 50"

SHIMMABLE NECK - SHIMS INCLUDED
 QUICK COUPLER ON FRONT OF MAIN DECK
 GLAD HANDS ON THE SIDE OF THE UPPER DECK
 WELD HOSE CAGE TO SIDE OF GOOSENECK

DECKING 1 1/8" ALUMINUM DECKING WITH 1-1/8" APITONG NAILER FLUSH
CHAIN SLOTS (5) TK STYLE CHAIN SLOTS IN LIEU OF LIGHTING HOLES
D-RINGS NO BENT PER SIDE
D-RINGS (2) PAIR OF PAN STYLE D-RINGS ONE IN EACH CORNER
MUD FLAPS ALUMINUM MUD FLAPS SET FORWARD
TOOLBOX TOOLBOX AT REAR OF GOOSENECK WITH CHAIN RACK, NO LIGHT

MAIN DECK

(3) BEAM DESIGN
 RADIUS PER ENGINEERING
LENGTH 34' 11" (33' 11" CLEAR)
LOADED DECK HEIGHT 12" W 4" GROUND CLEARANCE
 1/4" WEAR PLATE FULL LENGTH ON BEAMS
DECKING STEEL DECKING BETWEEN MAIN BEAMS WITH DURBAK
 1 3/8" APITONG DECKING, RAISED BETWEEN MAIN BEAMS AND OUTER BEAMS
 (3) TUBES ON OUTSIDES OF MAIN BEAM (ADDS ABOUT 730 LBS.)
CROSSMEMBER 4" JR. I-BEAM ON 18" CENTERS
BEAMS (3) 8" FAB BEAMS
TIE DOWNS 3/8" STIFFENERS ON 18" CENTERS WITH 1/2" X 2 1/2" BAR UNDER FLANGE
CHAIN DROPS CHAIN DROPS ON 18" CENTERS - NO LIGHTS BELOW
OUTRIGGERS NONE
RAMPS TAPERS TO 4"
 HOSE CAGE PLATE ON MAIN DECK

REAR DECK

LENGTH 8' 7"
LOADED DECK HEIGHT 42" - SET RIDE HEIGHT 2" HIGHER THAN STANDARD
AXLES (2) 25,000 LBS. NOMINAL (5/8" WALL)
SUSPENSION HENDRICKSON / 25,000 CAPACITY / AIR RIDE
AXLE SPACING 49"
ABS 4S2M WITH SPRING BRAKES ON (2) AXLES
TIRES 255 / 70R / 22.5 (H)
WHEELS 8.25 X 22.5 10-HOLE PILOT MOUNT POLISHED ALUMINUM OUTSIDE, MILLED ALUMINUM INSIDE DISC
BRAKES 16 1/2" X 7"
DRUMS OUTBOARD
ELECTRICAL 12V SEALED GROTE SYSTEM WITH (3) TAIL LIGHT ALUMINUM PACKAGE
 4" AMBER STROBE TO BE USED AS 3RD TAIL LIGHT

DECKING	1 1/8" ALUMINUM DECKING WITH 1-1/8" APITONG NAILER FLUSH
D-RINGS	(0) BENT D-RINGS PER SIDE
D-RINGS	(2) PAIR OF PAN STYLE D-RINGS ONE IN EACH CORNER
D-RINGS	(2) BENT D-RINGS IN TAIL CHANNEL
PAINT	BLACK
ADDITIONAL	TRIPLE DONUT FRONT CONNECTOR PLATE, WELD INDICATORS NUMBERS ON THE HOLES
	MANUAL RIDE HEIGHT CONTROL
	NO AXLE STOPS
	(9) TOTAL TRUCKLITE LIGHTS AND CONNECTORS
	(2) ON UPPER DECK, (4) ON MAIN DECK AND (2) ON REAR DECK (REAR CLEARANCE LIGHTS TO BE BEEHIVE LOOK
	LOOM AROUND TRUCKLITE LIGHTS AND CONNECTORS
	LIGHTS AND WIRING ABOVE CROSSMEMBERS
	CLOSE FRONT TROUGH SECTION UNDER GOOSENECK BETWEEN MAIN BEAMS W/ DRAIN HOLES
	NYLON LIMIT STRAPS
	RAISE AND LOWER VALVE
	GREASE HUBS IN LIEU OF OIL
	ADD FORMED 3/8" PLATE TO FRONT 6" OF MAIN DECK TO DEFLECT DECK OVER OBSTACLES
	SPACE OUT STIFFENERS ON THE MAIN DECK WITH THE CHAIN DROPS, ADD A STIFFENER AT THE REAR OF THE MAIN DECK
	(2) TK STYLE CHAIN SLOTS IN LIEU OF LIGHTING HOLES IN WHEEL AREA
	(1) SINGLE CHAIN SLOT AR REAR OF WHEEL AREA NEAR ABS LIGHT
	(4) SINGLE CHAIN DROPS IN CENTER OF TRANSITION OF THE WHEEL AREA
	LIQUID FILLED AIR GAUGE
	4-WAY AT REAR
	REF 24455

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.