

HALE

TRAILER

BRAKE & WHEEL



A026825-A026826
VIN: 656118-656119

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Body -- L2 Stainless

Length:	48'
Belt Width:	(2025) 48"
Sheet Metal:	16 Ga. Stainless
Trailer Width:	102"
King Pin Setting:	30"
Sidewall Height:	61-1/4"
Top Rail Type:	Double Flush
Top Rail Material:	12 Ga. Stainless
SideFrame Material:	12 Ga. Stainless
HD Structural Bow:	2
Tarp Bow Mount Quantity:	9

Extensions

Aluminum Side Extensions:	No
---------------------------	----

Body Options

Glad Hand Mounting:	Standard Offset
Landing Legs:	Atlas 55
Rear Funnel Mounts:	Yes
Front Seal Options:	Reinforced Front Seal
Tail Fin Options:	Standard Tail Fins
Enclosed Triangles:	Yes
Front Ladder:	Yes
Side Ladder Type:	Aluminum
Side Ladder Mounting:	Road Side Only
Rear Ladder Type:	Removable Maintenance Ladder

Lighting

Light Rows:	Single Row Marker Lights
Marker Light Type:	Standard LED
Tail Lights:	3 Tail Lights per Side
Tail Light Mounting:	Standard Rubber Grommet
Turn Signal Color:	Red
Tail Light Ice Guards:	Yes
Work Lights:	LED Work Lights
Work Lights Mounting:	Mounted at Rear and Center of Trailer
Number of Work Lights:	4
Auxiliary Wiring:	Lights & Lifts to Socket
Auxiliary Socket:	4 Pin

Rear Door

Door Type:	Top Hinge
Lower Door Function:	Slide Up
Opening Function:	Hydraulic
Slide Up Door Composite:	Aluminum
Upper Door Seal:	Rubber P-Seal
License Plate:	On Door

Suspension

Number of Axles:	3
Overall Spread:	8'-3"
Axle Spacing:	Equal Spacing
Suspension Type:	23K Air Ride Suspension
Brake Type:	Cast Brake Drums
Front Axle:	AAL23K Lift Axle (HXL5)
Middle Axle:	AAT23K Non Lift Axle (HXL5)
Rear Axle:	AAT23K Non Lift Axle (HXL5)
Suspension Frame Height:	Tall Mount
Axle Ahead:	24"
Rear Bumper Options:	Rear Impact Guard

Suspension Options

Front Axle Lift Control:	AKAD2010 - Equalizing Pressure
Lift Control Wiring:	Connect Wiring From Lift Control(s) to Front
Load Scale:	Std. Hendrickson Enclosed Gauge (PSI)
Dump Valve:	Integrated
Scale/Dump Mounted:	Above Rear Fender - Roadside
ABS Type:	Meritor Wabco 4S2M
Slack Adjuster Type:	Automatic
Full Width 3/16 HMW Belt Return	

Fender and Mud Flap

Fender Type:	Smooth Mill Finish Aluminum
Mud Flap Type:	Standard Mud Flaps
Front Mud Flap:	On Front Fenders (2 Flaps)



Unload System

PTO Unload:	Yes
Male Coupler:	Pioneer Style (1")
Female Coupler:	Pioneer Style (1")
Return Side Coupler:	Female Coupler
Couplers Mounted:	On Hoses to Tractor
Hyd. Valves:	LX6 Manifold
Hyd. Motor Size:	240
Hydraulic Oil:	Standard
Number Of Chains:	2
Chain Type:	AL88C - Heavy Duty
Chain Bar Type:	Formed Eagle Bar

Tarp System

Tarp Style:	Shur-Loc Style
Tarp Operation:	Electric with Remote
Tarp Material:	22 ounce
Tarp Primary Color:	Black
Primary Bow Style:	Radius Tarp Bows
Primary Bow Quantity:	5
Front Cap:	Aluminum
Rear Cap:	Fabric
Tarp Stops:	6" Offset
Tarp Latch Plate:	Top Mount (Standard)

Tires and Wheels

Tires and Wheel Style:	Duals
Tire Size:	11R22.5 (Tall 22)
Tire Tier/Use/Load:	Tier 2, Highway (G)
Tire Qty:	12
Wheel Size:	8.25 x 22.5
Outside Wheel Type:	Aluminum - Mill Finish
Outside Wheel Qty:	6
Inside Wheel Type:	Aluminum - Mill Finish
Inside Wheel Qty:	6

Liner Options

Floor Liner:	1/4" Thick UHMW
Side Liner:	3/16" Thick HMW
Side Liner Height:	High (20"-34" Above Slope)

Paint Options

Paint Color:	BK-1 Black
Bolt-On Acc. Color:	Body Match
Polyurethane Bin Sealant:	Yes

Trailer Specifications

Front Top Rail Height (ft):	12.38w/47" 5th Wheel
Rear Top Rail Height (ft)	12.2
Interior Bin Height (in):	92
Capacity(Cu. Yards):	103.35
Estimated Weight:	17,113
BTE (Internal Use):	35.5
FAB TE (Internal Use):	113.5

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.