

HALE

TRAILER

BRAKE & WHEEL



A027323-A027327
VIN: 87299-87303

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Weight 12103 lbs. ***

LOAD LINE

LOAD LINE QTY	NONE
LOAD LINE LOCATION #1	NONE
LOAD LINE LOCATION #2	NONE

BODY

REGION	DOMESTIC
	DUP 80801 (DO NOT INSTALL CANADIAN EXTRA INTERNAL SUPPORT BETWEEN HOPPERS SO LOAD CAN DISTRIBUTE FROM MIDDLE)
LOAD PROFILE	107K
VESSEL THICKNESS	0.190 5454-H32 ALUMINUM
	.219 HOPPERS AND END END CONES,
CUBIC FT CAPACITY	1250
	HD 12" C-CHANNEL FRAME RAILS
COMMODITY	CEMENT
MODEL SUB TYPE	NONE
TRAILER OPERATION TYPE	PNEUMATIC
FOOD GRADE	NONE
VESSEL FINISH	MILLED
LENGTH	44 FT. / 12.80 M.
WIDTH	102
OPERATING TEMPERATURE	185 F / 85 C
OPERATING PRESSURE	14.7 PSI / 101.35 KPA
COMPARTMENT OPTIONS	SINGLE COMPARTMENT
LOWER HOPPER CONES	WELD-ON 45 DEG (STANDARD)
MANLID QUANTITY	3
MANLID LOCATION LAYOUT	OVER EACH HOPPER
FIRST MANLID TYPE	KNAPPCO 20IN. ALUMINUM MANLID
SECOND MANLID TYPE	KNAPPCO 20IN. ALUMINUM MANLID
THIRD MANLID TYPE	KNAPPCO 20IN. ALUMINUM MANLID

AERATION

AERATOR FORMAT	3 PER HOPPER (STANDARD)
AERATOR TYPE	BTI SPIN FLOW AERATION KIT W/ WEAR PLATES AND 2 IN. BTI BLACKMAXX INDIVIDUAL AERATION CONTROLS AT EACH HOPPER
AERATION LOCATION	DRIVER SIDE
AERATOR LINE CONTROL	3" BTI BLACKMAXX BUTTERFLY VALVE
AERATOR SEAT	WHITE RUBBER (FOOD GRADE) SEAT
AERATOR DISK	ALLOMAXX DISC

AERATOR HANDLE TYPE	ALUMINUM
AERATOR HANDLE POSITION	MANUAL 10 - POSITION

AIR INLET

AIR INLET SIZE	3 IN. SCH. 10 ALUMINUM PIPE
AIR INLET LOCATION	DRIVER SIDE
CHECK VALVES	(2) BTI OPTIMA CHECK VALVES - (1) AT AIR INLET & (1) UP STREAM OF FRONT HOPPER DISCHARGE
AIR INLET SILENCER	NONE

PROP / PRES CONTROL VALVE

CONTROL VALVE HOUSING	3" BTI BLACKMAX BUTTERFLY VALVE
CONTROL VALVE DISK	ALLOMAXX DISC
CONTROL VALVE HANDLE TYPE	ALUMINUM
CONTROL VALVE HANDLE POSITION	MANUAL 10 - POSITION

BLOW DOWN LINE

BLOW DOWN LINE HOUSING	3" BTI BLACKMAX BUTTERFLY VALVE
BLOW DOWN LINE DISK	ALLOMAXX DISC
BLOW DOWN LINE SEAT	WHITE RUBBER (FOOD GRADE) SEAT
BLOW DOWN LINE HANDLE TYPE	ALUMINUM
BLOW DOWN LINE LOCATION	DRIVER SIDE FRONT
	DS REAR
BLOW DOWN LINE HANDLE POSITION	MANUAL 10 - POSITION
BLOW DOWN RELIEF PRESSURE	15 P.S.I.

TOP AIR

TOP AIR VALVE HOUSING	3" BTI BLACKMAX BUTTERFLY VALVE
TOP LINE LOCATION	DRIVER SIDE FRONT

PRODUCT & DISCHARGE

PRODUCT / DISCHARGE LINE SIZE	4 IN
PRODUCT / DISCHARGE LINE MATERIAL	ALUMINUM
PRODUCT / LINE MATERIAL GAUGE	SCHD.40
PRODUCT VALVE SIZE	5" BTI BLACKMAXX BUTTERFLY VALVES
PRODUCT VALVE SEAT	WHITE RUBBER (FOOD GRADE) SEAT
PRODUCT VALVE DISK	ALLOMAXX DISC
PRODUCT LINE CONNECTIONS FR & RR	BTI VICTAULIC COUPLERS -BOLT ON
PRODUCT/DISCHARGE LINE CONNECTION	MAC Rubber Sleeves with Stainless Worm Gear Clamp
PRODUCT VALVE HANDLE TYPE	ALUMINUM
PRODUCT VALVE HANDLE POSITION	MANUAL 5 - POSITION
PRODUCT TEE TYPE	5 X 4 ALUMINUM STRAIGHT TEE
REAR DISCHARGE LOCATION	EXTEND THROUGH AXLES TO REAR
NO. OF GAUGE ENCLOSURE	1
GAUGE LOCATION	Driver Side -Rear- Forward of Tandem

PRIMARY AXLES

MODEL	TRI-AXLE
NO. OF PRIMARY AXLES	3
SUSPENSION	HEND. INTRAAX AAT W/ RAISED AXLE - TP SPINDLE
	23K GAWR
NO. OF LIFT KITS	0
AXLES	77.5" AXLES
LIFT KIT	NONE
LIFT CONTROLS	NONE
WHEEL END PACKAGE	YES (HXL5)
	BRAKE LINING TO BE NAB-456 FOR 25K RATING
BRAKES	7 IN. XL, W/ 30-30 CHAMBERS
	LONG STROKE CHAMBERS WITH 6" AUTO SLACKS
CAM GUARDS	HEND. INTRAAX

HUB AND DRUM CENT W/ DURALITE HUB HP OB 10 STUD TP, LS, 7 IN.

CAST STEEL DRUMS

TIRES	CONTINENTAL HSR2 11R 22.5 16 PLY
WHEELS	ALUMINUM HP 22.5X8.25 - ALL POLISHED (XP)
PRIMARY AXLE TIRE INFLATION SYSTEM	NONE

CHASSIS

5TH WHEEL PLATE	BLACK POWDER COATED STEEL, ADJUSTABLE
5TH WHEEL PLATE HEIGHT	48 IN. HIGH
SUSPENSION CONTROL	AUTOMATIC DUMP ON EMERGENCY GLADHAND
SCALE SYSTEM	LOAD GAUGE - DRIVER SIDE REAR
ABS FOR TRAILER	(1) 4S2M MERITOR / WABCO
SLACKS	AUTO
HUBODOMETER_	NONE
AXLE LUBRICATION	NONE
DOLLIES - LANDING GEAR - LANDING LEGS	JOST - 5 YEAR NO LUBE- D.S.

HOLLAND MARK V LANDING GEAR - DS CRANK

AIR TANKS	ALUMINUM TANK
-----------	---------------

LIGHTS

LIGHT TYPE	GROTE L.E.D. W/ GROMMET
REAR I.D. LIGHTS	(3) I.D. LIGHTS TOP
	3 PENNY LIGHTS ADDED TO SECOND RUNG FROM BOTTOM
LIGHT PANEL	(TURN) (STOP) (STOP) - (STOP) (STOP) (TURN)
STD. MARKER LIGHTS	2 EACH SIDE FRONT & REAR
MID-TURNS	(2 PAIR) LED-BOXED IN

3- PENNY LIGHTS AS MID TURNS PER SIDE

BACK-UP LIGHTS	NONE
BACK-UP LIGHT LOCATION	NONE
BACK UP LIGHT CONTROLS	NONE
AUXILIARY CABLE	NONE
NO. OF WORK LIGHTS	2
WORK LIGHT MODEL	L.E.D. CUBE WORK LIGHTS
WORK LIGHT LOCATION	(2) MOUNTED HIGH REAR
WORK LIGHT SWITCH LOCATION	OUTSIDE

PAINT

SUSPENSION COLOR	MAC BLACK
MAC MACHINE FINISH LOGOS	BLACK (931716)

ACCESSORIES

FOLDING LADDER RAIL	NONE
FOLDING LADDER RAIL OPERATION TYPE	NONE
TOE RAIL	FULL LENGTH ON BOTH SIDES

TOP RAIL

CABINET	NONE
CENTER WALKWAY	ADHESIVE BACKED, SKID-RESISTANT TAPE BETWEEN TOE RAILS
HOSE STORAGE TUBE	(1) 8 IN. X 21 FT. MOUNTED ON CS
GAUGES	1 - LINE P.S.I. / 1 TANK P.S.I. - (INSIDE ILLUMINATED ENCLOSURE)
MUD FLAPS	ANTI-SAIL FLAPS (REAR OF FRONT FENDERS AND REAR OF BACK FENDERS)
PRODUCT DISCHARGE HOSE	NONE
FENDERS_	ALUMINUM ROLLED EDGE - SINGLE CONTOUR AT FRONT, DOUBLE CONTOUR AT REAR
DOCUMENT HOLDER	LOCATED DRIVER SIDE NEAR LANDING GEAR
AIR INLET ACCESSORIES	PTO HOSE HOLDER, MAST, HOOK AND DUMMY ADAPTER LOCATED DRIVER SIDE ABOVE FRONT FENDER

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.