

A027359-A027365 VIN: 090277-090283

SALES PARTS SERVICE RENTALS Allentown, PA: Little Rock, AR: 833-424-8944 800-383-8894 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Raleigh, NC 833-418-9777 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Springfield, MA: Des Moines, IA: 888-673-5011 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

800-232-6535 *FINANCING AVAILABLE

BODY: "GENESIS"		TAILGATE:		CHASSIS: THREE FIXED	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	TRIDEM (6)(7)(8)
LENGTH (FEET)	50	TYPE	SINGLE	TYPE	ALUM SUB FRAME
HEIGHT (INCHES)	104	STYLE	GENESIS	AXLE TO AXLE	49" - 49" - 49"
SIDE MAT'L (OUTBOAR	D) "GENESIS"	MAT'L THICKNESS	0.150	REAR AXLE SETTING	55"
FRONT 0.150		S / S HINGE ON	P/S 4-3-4	5TH WHEEL HT	51" (10)
MIDDLE 0.150		GATESEAL	NONE	PIN SETTING	36" w / 3/8" PLATE
F	REAR 0.150	GATE LADDER	CENTER-LADDER	SUSPENSION	REYCO 21-B (11)
POLISHED SIDES	YES+TG+REAR PKT	TARP HOOKS	NONE	SPRINGS	SINGLE LEAF
ROOF	NONE	WINDERS	ONE - D/S	AXLES	TP - 23,000 GAWR
ROOF MAT'L	NONE	GATE GUIDE	YES	BRAKES	16-1/2" x 7"
BULKHEAD	3/16" BUFFED (1)(3)	GATE CONTROL	MECH	DUSTSHIELDS	YES
TARP HOOKS	NONE	POCKETS	EXTRUDED	BRAKE CHAMBERS	STD
TARP BASKET	NONE	CROSSPIPE (S)	TWO	ABS	2S / 1M HXL-5
TARP	NONE		MIDDLE - SPRING	HUBS	10 S STEEL-GREASE
CATWALK	YES-74" INTERMDTE		REAR - TUBE	DRUMS	CAST
B.H. LADDER D/S-LADDER		COMPACTOR:		WHEELS	8.25 x 24.5
CROSSMEMBER	"I"BEAM- 12" C/L	SIDE LATCH	N/A		12 STEEL DISC
FLOOR MAKE	KEITH 3.5" Drives(9)	CENTER LATCH		TIRES	11R 24.5 R268
FLOOR MAT'L	2299 1/2" IMPACT	PIN DIA.			ECOPIA 16PLY BS
WEARPADS	CWS			DOLLIES	JOST 2 SPD HX151
TAPE COLOR	NONE	HYDRAULICS:		LOCATION	D/S CRANK
LIGHT PANEL	IN GATE LED (4)	HOSES	TWO-4000 PSI	BUMPER	UNDERRIDE GUARD
MARKER LIGHTS	3 PR BTM ONLY(2)	LENGTH	144"	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	MODEL 60	FITTINGS	PUSH-PULL	PUSH BLOCKS	YES
MUDFLAPS	STD	HP	1" MALE	PAINT	SILVER
HOSE HANGER	YES	LP	1" FEMALE		
TIRE CARRIER	NONE	HOSE LOCATION	CENTER		
		AIR & ELECTRICAL	CENTER (5)		

REMARKS: PRICING SUBJECT TO CHANGE 12 WEEKS PRIOR ESTIMATED BUILD DATE.

- 1. NO INSIDE BULKHEAD STEPS
- 2. 3 PAIR PER SIDE BOTTOM ONLY W/ PROTECTORS.
- 3. MANDOOR IN THE CENTER OF THE BULKHEAD W/ STEP FOR MANDOOR STEP
- 4. ADD 1 PR NON LED BACK UP LIGHTS WIRED TO AUXILIARY IN THE TAILGATE OOX ooo XOO
- 5. AUXILIARY 6-WAY PLUG (LOCATED NEAR STD 7 WAY) WIRED INTO JUNCTION BOX AT REAR JUST AHEAD OF MOST FORWARD AXLE
- 6. RUN ALUMINUM SUBFRAME TO THE BACK OF THE LANDING GEAR.

13.25

- 7. MOVE DRIVE UNIT FORWARD TO MISS TIRES OF FRONT AXLE OF FUTURE 4TH STEERABLE LIFT AXLE SPACED 52" AHEAD OF FRONT TRIDEM
- 8. CROSSMEMBERS ONLY FOR FUTURE 4TH IMT/ISS SUSPENSION IMT STEERABLE LIFT AXLE 52" AHEAD OF MOST FORWARD AXLE.
- 9. SPLASH GUARD HOLD DOWN BEARINGS
- 10. REPLACEABLE KING PIN

OVERALL HEIGHT (FT)

11. REYCO GALVANIZED

EMPTY WEIGHT (#) 20,792 (EMPTY WEIGHT VARIANCE +/- 3%)

CUBIC YARDS

130