

HALE

TRAILER

BRAKE & WHEEL



A027374-A027401
VIN: 78780-78807

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Infinity Drop Deck 48' Wide Spread Air (Model Code: HAICD12WSA)

Length / Width: 48 feet x 102 inches
Suspension Type: Wide spread air
Deck Lengths: 10 feet front and 38 feet rear
Frame Rating: 80,000 lbs distributed - 55,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads
Rear Deck Height: 40 inches - loaded
Flooring: 1 1/8 inch aluminum with 4 wood nailer strips
Crossmembers: 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel
Single Coil Hauling Package: Included
Side Rails: Exclusive Revolutionary RASR Rail Technology -- one piece routed aluminum designed for strength and impact
Chain Cargo Tie Downs: 15 pair recessed in siderails
Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)
Rubrail: Integrated with siderail
Main Beams: 130K load bearing flanges; Approximately 3/4" Camber n Lower Deck (+/-1")
Kingpin: 18 inches
Loaded Fifth Wheel Height: 49 inches
Landing Gear: OEM standard
Knee Braces: Fabricated on approx. 60 inch C/C
Bulkhead Pockets: 4 DOT type bulkhead pockets only - welded to front
Bulkheads: None standard
Number of Axles: 2
Axle Spindle: Tapered
Brakes: Spring brakes, auto slacks
Air Line Filters: (2) Meritor In-line type installed
ABS: Meritor Wabco iABS 4S/2M - no cable or tool
Axle Spread: 122 inches - set at rear
Hub and Drums: 10-hole hub-piloted with outboard cast drums
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***
Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD
Tires: 255/70R 22.5 16PR OEM standard
Tire Inflation System: None standard
Suspension Detail: AANL23K Intraax air ride
Auto Glad Hand Dump : Installed
Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle
Air Lift: None Standard
Front Corners: Tapered
Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD
Paint: Black urethane on steel parts with Infinity decals - STANDARD
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails
Bumper: Weld-on type - meets underride requirements - painted steel
Mudflaps: 2 sets America Mighty Warriors; Spring loaded brackets behind front axle (Must Choose Decal Package Below)
Winch Track: Full length integrated double L type aluminum on both sides where possible -- STANDARD
Sliding Winches: 12 total, 2 front deck and 10 rear deck: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers -- STANDARD
27 foot Winch Straps: None standard
30 foot Winch Straps: Winch Straps - 30 feet x 4 inches installed - EACH - Qty: 12
Dock Bumpers: 1 pair rubber on rear
Spare Tire Carrier: 1 standard - mounted between lower gooseneck beams at drop
Hubodometer: None standard
Registration Holder: Install registration holder - OEM standard
Tool Box: None standard
VIN Plate: Bilingual US/Canadian VIN plate
Unit Numbers & Decals: Patriot and America Mighty Warriors Decals Installed (Must Also Pick AMW Mud Flap Option Above)

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.