



A027447-A027448 VIN: 087524-087525

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: Little Rock, AR: 800-383-8894 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: Raleigh, NC 833-418-9777 800-438-2250 Delmar, DE: 800-569-1400 866-486-1400 Scranton, PA: Des Moines, IA: 888-673-5011 Springfield, MA: 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer f 🤇

800-232-6535 *FINANCING AVAILABLE

1050C PNEUMATIC DRY BULK TANKER

Model # TNAR42NF0-2026

Weight 9057 lbs. *** Cubic Feet 1050

LOAD LINE		
LOAD LINE QTY	NONE	
LOAD LINE LOCATION #1	NONE	
LOAD LINE LOCATION #2	NONE	

RODA	
REGION	DOMESTIC
REF80766	
LOAD PROFILE	72K
VESSEL THICKNESS	0.190 5454-H32 ALUMINUM
CUBIC FT CAPACITY	1050
COMMODITY	CEMENT
MODEL SUB TYPE	NONE
TRAILER OPERATION TYPE	PNEUMATIC
FOOD GRADE	NONE
VESSEL FINISH	MILLED
LENGTH	42 FT. / 12.80 M.
WIDTH	96
OPERATING TEMPERATURE	185 F / 85 C
OPERATING PRESSURE	14.7 PSI / 101.35 KPA
COMPARTMENT OPTIONS	SINGLE COMPARTMENT
LOWER HOPPER CONES	WELD-ON 45 DEG (STANDARD)
MANLID QUANTITY	2
MANLID LOCATION LAYOUT	FRONT & CENTER
FIRST MANLID TYPE	KNAPPCO 20IN. ALUMINUM MANLID
SECOND MANLID TYPE	KNAPPCO 20IN. ALUMINUM MANLID
THIRD MANLID TYPE	NONE

AERATION	
AERATOR FORMAT	3 PER HOPPER (STANDARD)
AERATOR TYPE	BTI SPIN FLOW AERATION KIT W/ WEAR PLATES AND 2 IN. BTI
	BLACKMAXX INDIVIDUAL AERATION CONTROLS AT EACH
	HOPPER
AERATION LOCATION	DRIVER SIDE
AERATOR LINE CONTROL	3" BTI BLACKMAX BUTTERFLY VALVE
AERATOR SEAT	WHITE RUBBER (FOOD GRADE) SEAT
AERATOR DISK	ALLOMAXX DISC
AERATOR HANDLE TYPE	ALUMINUM
AERATOR HANDLE POSITION	MANUAL 10 - POSITION

IR INLET	
AIR INLET SIZE	3 IN. SCH. 10 ALUMINUM PIPE
TEATHER DUST CAP ON INLET	
AIR INLET LOCATION	DRIVER SIDE
CHECK VALVES	(2) BTI OPTIMA CHECK VALVES - (1) AT AIR INLET & (1) UP STREAM
	OF FRONT HOPPER DISCHARGE
AIR INLET SILENCER	NONE

PROP / PRES CONTROL VALVE	
CONTROL VALVE HOUSING	3" BTI BLACKMAX BUTTERFLY VALVE
CONTROL VALVE DISK	ALLOMAXX DISC
CONTROL VALVE HANDLE TYPE	ALUMINUM
CONTROL VALVE HANDLE POSITION	MANUAL 10 - POSITION

BLOW DOWN LINE	
BLOW DOWN LINE HOUSING	3" BTI BLACKMAX BUTTERFLY VALVE
BLOW DOWN LINE DISK	ALLOMAXX DISC
BLOW DOWN LINE SEAT	WHITE RUBBER (FOOD GRADE) SEAT
BLOW DOWN LINE HANDLE TYPE	ALUMINUM
BLOW DOWN LINE LOCATION	DRIVER SIDE FRONT
DRIVER SIDE REAR	
BLOW DOWN LINE HANDLE POSITION	MANUAL 10 - POSITION
BLOW DOWN RELIEF PRESSURE	15 P.S.I.

TOP AIR		
TOP AIR VALVE HOUSING	3" BTI BLACKMAX BUTTERFLY VALVE	
TOP LINE LOCATION	DRIVER SIDE FRONT	

4 IN
ALUMINUM
SCHD.40
5" BTI BLACKMAXX BUTTERFLY VALVES
WHITE RUBBER (FOOD GRADE) SEAT
ALLOMAXX DISC
BTI VICTAULIC COUPLERS -BOLT ON
MAC Rubber Sleeves with Stainless Worm Gear Clamp
ALUMINUM
MANUAL 5 - POSITION
5 X 4 ALUMINUM STRAIGHT TEE
EXTEND THROUGH AXLES TO REAR
1
Driver Side -Rear- Forward of Tandem

PRIMARY AXLES	
MODEL	TANDEM
NO. OF PRIMARY AXLES	2
SUSPENSION	HEND. INTRAAX AAT W/ RAISED AXLE - TP SPINDLE
NO. OF LIFT KITS	0
AXLES	71.5" AXLES
LIFT KIT_	NONE
LIFT CONTROLS	NONE
WHEEL END PACKAGE	YES (HXL5)
BRAKES	7 IN. XL, W/ 30-30 CHAMBERS
CAM GUARDS	HEND. INTRAAX
HUB AND DRUM	CENT W/ DURALITE HUB HP OB 10 STUD TP, LS, 7 IN.
TIRES	GENERAL RA 11 R 22.5 16 PLY
WHEELS	ALUMINUM HP 22.5X8.25 - ALL POLISHED (XP)
PRIMARY AXLE TIRE INFLATION SYSTEM	NONE
PREP AXLES FOR TIRE INFLATION SYS	TEM

5TH WHEEL PLATE	BLACK POWDER COATED STEEL, ADJUSTABLE
5TH WHEEL PLATE HEIGHT	48 IN. HIGH
SUSPENSION CONTROL	AUTOMATIC DUMP ON EMERGENCY GLADHAND
SCALE SYSTEM	LOAD GAUGE - DRIVER SIDE REAR
ABS FOR TRAILER	(1) 4S2M MERITOR / WABCO
SLACKS	AUTO
HUBODOMETER_	NONE
AXLE LUBRICATION	NONE
DOLLIES - LANDING GEAR - LANDING LEGS	JOST - 5 YEAR NO LUBE- D.S.
HOLLAND HARK V LANDING GEAR - DS CRANK	
AIR TANKS	ALUMINUM TANK

LIGHT TYPE GROTE L.E.D. W/ GROMMET REAR I.D. LIGHTS (3) I.D. LIGHTS TOP 3 PENNY LIGHTS ADDED TO SECOND RUNG FROM BOTTOM LIGHT PANEL (TURN) (STOP) (STOP) - (STOP) (TURN) STD. MARKER LIGHTS 2 EACH SIDE FRONT & REAR MID-TURNS (2 PAIR) LED-BOXED IN 3 PENNY LIGHTS AS MID TURNS PER SIDE BACK-UP LIGHTS NONE BACK-UP LIGHT LOCATION NONE BACK UP LIGHT CONTROLS NONE	
3 PENNY LIGHTS ADDED TO SECOND RUNG FROM BOTTOM LIGHT PANEL (TURN) (STOP) - (STOP) (STOP) (TURN) STD. MARKER LIGHTS 2 EACH SIDE FRONT & REAR MID-TURNS (2 PAIR) LED-BOXED IN 3 PENNY LIGHTS AS MID TURNS PER SIDE BACK-UP LIGHTS NONE BACK-UP LIGHT LOCATION NONE	
LIGHT PANEL (TURN) (STOP) (STOP) - (STOP) (TURN) STD. MARKER LIGHTS 2 EACH SIDE FRONT & REAR MID-TURNS (2 PAIR) LED-BOXED IN 3 PENNY LIGHTS AS MID TURNS PER SIDE BACK-UP LIGHTS NONE BACK-UP LIGHT LOCATION NONE	
STD. MARKER LIGHTS 2 EACH SIDE FRONT & REAR MID-TURNS (2 PAIR) LED-BOXED IN 3 PENNY LIGHTS AS MID TURNS PER SIDE BACK-UP LIGHTS NONE BACK-UP LIGHT LOCATION NONE	
MID-TURNS (2 PAIR) LED-BOXED IN 3 PENNY LIGHTS AS MID TURNS PER SIDE BACK-UP LIGHTS NONE BACK-UP LIGHT LOCATION NONE	
3 PENNY LIGHTS AS MID TURNS PER SIDE BACK-UP LIGHTS NONE BACK-UP LIGHT LOCATION NONE	
BACK-UP LIGHTS NONE BACK-UP LIGHT LOCATION NONE	
BACK-UP LIGHT LOCATION NONE	
BACK UP LIGHT CONTROLS NONE	
AUXILIARY CABLE NONE	
NO. OF WORK LIGHTS 2	
WORK LIGHT MODEL L.E.D. CUBE WORK LIGHTS	
WORK LIGHT LOCATION (2) MOUNTED HIGH REAR	
WORK LIGHT SWITCH LOCATION OUTSIDE	

PAINT		
SUSPENSION COLOR	MAC BLACK	
MAC MACHINE FINISH LOGOS	BLACK (931716)	

ACCESSORIES	
FOLDING LADDER RAIL	NONE
FOLDING LADDER RAIL OPERATION TYPE	NONE
TOE RAIL	FULL LENGTH ON BOTH SIDES
CABINET	NONE
CENTER WALKWAY	ADHESIVE BACKED, SKID-RESISTANT TAPE BETWEEN TOE RAILS
HOSE STORAGE TUBE	(1) 8 IN. X 21 FT. MOUNTED ON CS
GAUGES	1 - LINE P.S.I. / 1 TANK P.S.I (INSIDE ILLUMINATED ENCLOSURE)
MUD FLAPS	ANTI-SAIL FLAPS (REAR OF FRONT FENDERS AND REAR OF BACK FENDERS)
PRODUCT DISCHARGE HOSE	NONE
FENDERS_	ALUMINUM ROLLED EDGE - SINGLE CONTOUR AT FRONT, DOUBLE CONTOUR AT REAR
DOCUMENT HOLDER	LOCATED DRIVER SIDE NEAR LANDING GEAR
AIR INLET ACCESSORIES	PTO HOSE HOLDER, MAST, HOOK AND DUMMY ADAPTER LOCATED DRIVER SIDE ABOVE FRONT FENDER