

# HALE

## TRAILER

### BRAKE & WHEEL



A027464-A027466  
VIN: A6130-A6132

#### SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



**800-232-6535** \*FINANCING AVAILABLE

Magnitude 55H DSR Air Tridem (Drop Side Rail) (Model: MAGNITUDE 55H DSR)	
MAG55H***D*926543	Est. Wt.: 22,917# +/- 3%
TRAILER - GENERAL	
<b>Capacity:</b> 55 tons in 12-foot length with 4 axle close coupled or single axle stinger - GAWR and GVWR determine legal payloads	
<b>Length (Trailer Only):</b> 52 feet 0 inches (with standard deck length and axle spread)	
<b>Compatibility:</b> Designed to accept 55/60 rear axle, spreader and/or 35 inch flipbox	
<b>Accent Package:</b> None	
GOOSENECK	
<b>Gooseneck Design:</b> Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11ft 11in overall gooseneck length) set up for wetline operation	
<b>Loaded Fifth Wheel Height:</b> Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal)	
<b>Swing Radius:</b> 102 inches (11 feet 11 inches overall gooseneck length) - NGB	
<b>Alternate Kingpin:</b> Dual kingpin at 81 inch and 102 inch radius	
<b>Power Source:</b> Set up for wet line operation	
<b>VIN Plate:</b> Bilingual VIN plate	
<b>Registration/Document Holder:</b> Registration/document holder installed	
<b>Hydraulic Fittings:</b> OEM Standard 1/2 inch	
DECK	
<b>Framework:</b> All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
<b>Deck Length:</b> Drop Side Rail Deck (DSR) design - 26 feet clear deck length Standard OAL 52 feet 0 inches	
<b>Loaded Deck Height:</b> 14.5 inches at side rails, 22 inches at main beams with 6 inches ground clearance	
<b>Crossmembers:</b> On 24 inch centers (nominal)	
<b>Deck Width:</b> 8 feet 6 inches overall (unless optional deck width is selected)	
<b>Flooring:</b> 1.5 inch nominal wood - side rails only	
<b>Extension Brackets:</b> 13 pair - 26 total removable swing type, 1 pair - 2 total heavy duty removable hook-on type	
<b>Tool Box:</b> 2 Fully covered trays in front of deck between mainbeams with lockable covers	
<b>Hammer Plate:</b> None	
REAR BRIDGE	
<b>Front Bogie Ramp:</b> Included	
<b>Boom Trough:</b> Low Boom Well V crossmembers with bolt-in V pan	
<b>Deck to Bogie Connection:</b> Fixed	
<b>Bolsters:</b> Recessed	
<b>Covered Rear Bogie:</b> None	
<b>Rear Bogie Height:</b> 40 7/8 inches	
<b>Connections for Future Axle Attachment:</b> Air and electrical connections to go along with connecting ears	
AXLES	
<b>Number of Axles:</b> 3	
<b>Axle Capacity:</b> 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
<b>Axle Spread:</b> 54.5 inches (between axles)	

<b>Dust Shields: None</b>	
<b>Brakes:</b> 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
<b>Spring Brakes: None</b>	
<b>SUSPENSION</b>	
<b>Suspension:</b> Air ride	
<b>First Axle Lift:</b> Chain lift axle	
<b>Third Axle Lift:</b> Air lift	
<b>Mechanical Ride Height Control:</b> 7-position mechanical ride height control system	
<b>Manual Dump Valve:</b> Manual Dump Valve (Push Pull)	
<b>Liquid Filled Gauge: None</b>	
<b>Load Scale: None Standard</b>	
<b>WHEELS AND TIRES</b>	
<b>Wheels: 8.25 x 22.5 LVL One buffed outside/steel inside - hub-piloted</b>	
<b>Tires:</b> 275/70R 22.5 OEM Standard	
<b>Hubodometer: None Standard</b>	
<b>Tire Inflation: None Standard</b>	
<b>LIGHTING</b>	
<b>Electrical System:</b> DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
<b>Tail Lights:</b> 3 tail light package	
<b>Electrical Receptacle:</b> J560 7-pin connector	
<b>Marker Lights:</b> 3 marker lights per side including mid turn	
<b>Additional Marker Lights: None Standard</b>	
<b>PAINT</b>	
<b>Paint:</b> Fontaine black polyurethane enamel PN 51172000/G02BC0001	
<b>MISCELLANEOUS</b>	
<b>Lash Rings:</b> 14 pair - 28 total	
<b>Flag Holders:</b> 2 pair flag holders installed	
<b>AVAILABLE COMPONENTS</b>	
<b>Flipbox: None included</b>	
<b>Spreader: None</b>	
<b>Flip Axle: None</b>	
<b>Hydraulic Flip Axle Option: None Standard</b>	
<b>Dust Shields on Flip Axle: None</b>	

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.