



A027483-A027486 VIN: P3547-P3550

## SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Raleigh, NC 833-418-9777 Delmar, DE: Scranton, PA: 800-569-1400 866-486-1400 Des Moines, IA: 888-673-5011 Springfield, MA: 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: 800-828-3055 Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer f 👽 庙 🎯 🛗

**800-232-6535** \*FINANCING AVAILABLE

Magnitude 452 Jeep for Magnitude 65, 75 or 80 models (jeep as 2-axle or 2	-axle plus 3rd flip axle
configuration) (Model: 452JEEP)	axic plus of a hip axic
ž /\	
A A A C I E D A E O A A A C I E D A E O A A A A C I E D A A A A A C I E D A A A A A C I E D A A A A A C I E D A A A A A A A A A A A A A A A A A A	
MAGJEP453****602	Est. Wt.: 8,280# +/- 3%
TRAILER - GENERAL	
Capacity: 45 tons GAWR and tire rating determine legal loads	
Length (Jeep Only): 29 feet 5 inches	
Width: 8 feet 6 inches	
Compatibility: Magnitude 65 75 80 ton trailers	
GOOSENECK	I
Gooseneck Design: Fixed narrow	
Loaded Fifth Wheel Height: 50 inches	
Swing Radius: 104 and 80 inches (removeable)	
DECK	I
Deck Design: Beam design	
Fifth wheel: Sliding fifth wheel with a 55 inch fifth wheel height (54 inch slide)	
Deck to Bogie Connection: Fixed	I 
AXLES	
Number of Axles: 2	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined	<u> </u>
by suspension type, brakes, tires and other components.	
Axle Spread: 60 inches (between axles)	I 
<b>Brakes:</b> 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums -	
outboard mount	
Dust Shields: None	
SUSPENSION	I
Suspension: Air ride	
Framework: All main longitudinal members fabricated with 100,000 PSI minimum	
yield steel flanges with 50,000 PSI webs	
ABS: Not required	
Load Scale: None Standard	
WHEELS AND TIRES	1
Wheels: 8.25 x 22.5 lvL One buffed/steel disc inside - hub-piloted	
Tires: 275/70R 22.5 H ply OEM Standard	
Hubodometer: None Standard	I 
Tire Inflation: None Standard	
LIGHTING	I
Electrical System: DOT sealed beam and harness	
Electrical Receptacle: J560 7-pin connector	I
Additional Marker Lights: None Standard	
PAINT	
Paint: Fontaine black polyurethane enamel	
AVAILABLE COMPONENTS	I
Flip Axle: None Standard	
MISCELLANEOUS	I
Registration/Document Holder: Registration/document holder intalled	