

HALE

TRAILER

BRAKE & WHEEL



Resale Inventory
A027514-A027515
VIN: 005468-005469

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer
800-232-6535 *FINANCING AVAILABLE

Six Axle Self Steer Dolly

<input type="checkbox"/>	1)	Capacity	60 Ton capacity. GAWR & tire rating determine legal loads.
<input type="checkbox"/>	2)	Width	10' wide
<input type="checkbox"/>	3)	Booster spread	16'1" spread
<input type="checkbox"/>	4)	Power tower	Hydraulic power tower with 10" lift operated off of steering power pack.
<input type="checkbox"/>	5)	Bolster	Optional.
<input type="checkbox"/>	6)	D-rings	Four D-rings on steer dolly for picking up to stack.
<input type="checkbox"/>	7)	Steering	Mechanical self steering, with adjustment for tracking for different length loads, and adjustment for different steering radius. Includes manual hydraulic over-ride powered by 13 hp Honda power pack. Includes wireless remote control. <i>+ ADD 25' OR 50' WIRED TETHER FOR BACKUP</i>
<input type="checkbox"/>	8)	Over-steer alarm	Over-steer alarm mounted on steer dolly. Wireless audio alarm with visual lights included for tractor cab.
<input type="checkbox"/>	9)	Pusher Bar	Included. <i>→ SLIGHTLY REDESIGNED</i>
<input type="checkbox"/>	10)	Tow Bar	Optional.
<input type="checkbox"/>	11)	Wide load sign	Wide load sign on rear of booster.

<input type="checkbox"/>	12)	Flag holders	Flag holders at rear of steer dolly.
<input type="checkbox"/>	13)	Suspension	Ridewell Model 240 Air Ride suspension, 60" axle spacing, cut-off valves and lift chains on front 3 axles.
<input type="checkbox"/>	14)	Air Controls	Automatic/Manual ride height control system with pressure gauge. Manual regulator can be set based on load and locked to a specific pressure. Manual dump valve standard.
<input type="checkbox"/>	15)	Axles	Six, round with 3/4" wall, tapered spindles, 25,000 lb capacity, 98" track. <i>USE PURCHASED CONTROL BOXES</i>
<input type="checkbox"/>	16)	Hubs	8 Stud, hub piloted, long studs, steel hubs.
<input type="checkbox"/>	17)	Drums	Cast drum
<input type="checkbox"/>	18)	Seals	Stemco oil seals.
<input type="checkbox"/>	19)	Brakes	12 1/4 X 7 1/2 Air. Parking brakes on front 3 axles with brake release valve included.
<input type="checkbox"/>	20)	ABS	None
<input type="checkbox"/>	21)	Slack adjusters	Automatic slack adjusters.
<input type="checkbox"/>	22)	Wheels	Steel disc wheels, 6.75 X 17.5 painted white
<input type="checkbox"/>	23)	Tires	OEM 245/70R17.5 (Low Profile) radial tires.
<input type="checkbox"/>	24)	Wheel covers	Poly wheel fenders to protect tower section.
<input type="checkbox"/>	25)	Mud flaps	Black Anti-Spray with Kalyn Siebert Logo.
<input type="checkbox"/>	26)	Finishing (Paint & trim)	Shot blasted prior to paint. Epoxy primer and black polyurethane paint. Air, electrical and hydraulic lines installed after painting is completed. ✓
<input type="checkbox"/>	27)	Lights & electrical	LED light with mid turn signal, 12 volt. 7-way plug. With amber flashing strobe lights in rear bumper and at the front of dolly where it steers out from load.
<input type="checkbox"/>	28)	Conspicuity Tape	Discontinuous on sides
<input type="checkbox"/>	29)	Weight	_____ ± 3% tolerance. For trailers other than standard specification, weight and dimensional drawing will be provided by plant after order is received and accepted.

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.