

HALE TRAILER BRAKE & WHEEL

Resale Inventory
A028036-A028038
VIN: 49370, 49372, 49373

POLAR

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

STAINLESS STEEL, ROUND, JACKETED, 3-A SANITARY TRAILER (SRJ3)

BARREL DESCRIPTION:

CODE:	3A Sanitary
CAPACITY:	6250 Gallons (Shell full).
SHAPE:	Round
COMPARTMENTS:	One
SHELL MATERIAL:	T304 Stainless steel, 12 gauge, #4 finish. Two piece barrel with one circumferential weld.
HEAD MATERIAL:	T304 Stainless Steel #4 finish, 12- gauge
OPERATING PRESSURE:	Atmospheric.
DESIGN TEMPERATURE:	212 degrees F. (Temperature rating of 212 degree F. With standard fiberglass insulation. The use of other insulations may decrease the maximum temperature rating for this trailer. See insulation for maximum temperature rating change.)
OVERALL LENGTH:	42'6"
PRODUCTS:	Various

OTHER BARREL INFORMATION

HEAT:	None
Plumbing:	None
Intransit:	None
Weld Finish:	W-5 inside

CONSTRUCTION:

Rings and Longerons:	Stainless Steel Channel
Frame:	Stainless Steel
Dam:	None
Dam Drains:	None

Cleanout overturns:	None
Manhole:	Polar 18" stainless steel lid with dust cover, 4 hold down. Stainless steel sanitary deck around manhole.
Gasket:	3A black nitrile D50 gasket in cover.
Insulation:	Fiberglass, 5" compressed to 4"
Thermometer:	None
Jacketing:	22 gauge stainless steel bright finish
Jacket Heads:	18 gauge stainless steel bright finish
Underlayment:	.090" aluminum full length
Static Cable:	No static cables installed

HOSE CARRIERS:

	Aluminum tube 8" diameter x 21' long
	8" aluminum door, at rear
Location:	Mounted curbside rear

LIGHTS & WIRING:

Lights:	12-volt, Truck/Lite LED grommet mount lights. Combination center marker/turn signals.
Wiring:	Plug in style harness system.
Rear Lights:	Enclosed in stainless steel light boxes
Nose Box:	Standard 7-way, J560 receptacle without circuit breakers

UNDERCARRIAGE:

Upper 5 th Wheel:	5/16" Heavy duty with A.A.R. style double hubbed kingpin.
Paint:	Fifth wheel plate painted black.
Landing Gear:	Jost A400 telescopic load bearing, 2-speed.(Jost 5 year warranty)
Frame:	Stainless Steel Construction.
Bracing:	Stainless Steel, with cross brace.
Crank Location:	Roadside
Tire Carrier:	None
Suspension:	Hendrickson Intraax AANT23K, 23,000 lb., tandem axle with standard 49" axle spacing. 5 3/4" diameter Hendrickson integrated axles.
Dump Valve:	AK-54 automatic Stainless steel hangers with soft coat applied to axle and trailing arm. (Weld-on suspension only)
Subframe:	3/16" stainless steel, bolt on, (no under ride required, wheels back exempt.)
Beam:	Straight
Track	71 1/2" track
Spindle:	P spindles (parallel) same inner and outer bearing
Wheel Seals:	Stemco Guardian

Hub & Drums:	Walther EMC, hub piloted, Dura-light hub with cast drum
Miscellaneous:	None
BRAKES:	S-cam, 16 1/2" x 7", Extended Service
Anti-Lock/Roll Stability:	Meritor 4S/2M with "RSS-Plus", tandem axle roll stability support system for air-ride suspension
Brake Chambers	TSE 3030.
Brake Lining	Extended Service/Non-Asbestos
Slack Adjusters	MERITOR Automatic.
Valves	Sealco.
Gladhands	TRAMEC.
Air System:	To D.O.T. specifications. Single mild steel tank system, 2800 cu. In.
Wheels:	Alcoa "LvL one" clean buff, 22.5 x 8.25 aluminum disc
Tires:	Long Haul Radial 11R-22.5, Load range G 14 ply
Mud Flaps:	White plastic with Polar Logo, mounted front and rear.

FENDERS:	
Front:	Aluminum contour
Rear:	Aluminum contour

VALVING AND PIPING:

Seal Provisions:	On all openings
Sump:	3" stainless steel sanitary drain with mounting ring in rear head.
Pipe	
Discharge Location:	Rear of trailer.
Outlet Valve:	3" Thomsen stainless steel 60 TTF valve with aluminum dust cover, attached to mounting ring.

VENTING AND CLEANOUTS:

Vacuum:	Run-O-Vent in manhole cover.
Cleanouts:	3" stainless steel ACME threaded ferrule with cap, nut and dust cover Installed forward of the manhole.

WALKWAY AND LADDER:

Top Center:	None
Ladder:	(2) Stainless steel tubular with grip steps and large platform step, bolt on.

CABINET: None. No Cabinet installed.

PUMP SYSTEM:

Meter: None
Meter Installation: None

MISCELANEOUS:

Decals: Standard warning and safety package
Conspicuity Tape: Discontinuous Tape
Customer Logo: None
Document Holder: Truck Lite #97960
Calibration: Theoretical paper chart, in ¼" increments based on innage
Paint: None. No paint installed on trailer.
Passivate: None
Warranty: Polar standard two year
Tests: Standard testing

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.