








A028051-A028056  
TEMP VIN: S026993-S026998



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 \*FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE APPLICATION	SEMI-TRAILER, STEEL PLATFORM LEGEND SD GALVANIZED SEE SECTION
DIMENSIONS LENGTH WIDTH HEIGHT	40'-0". 102", 97" between side rails. Floor, approximately 59 1/2" high at front and 54" at rear.
COUPLING COUPLER PLATE KING PIN LOCATION COUPLER HEIGHT	3/8", plug welded structure. 30" from front. 48".
STRUCTURE FLANGES WEB  GOOSENECK CROSSMEMBERS FLOOR FLOOR FASTENING SIDE RAILS SIDE BOXES  RUB RAILS CORNERS X BRACES	44" c/c frame with "CAMBER". 3/8" x 5", 100 000 psi steel. 1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel. 27" high at the peak. with holes, parachute shaped, to lighten trailer. 11 1/4" high, with integrated nose ramp and 48" straight behind king pin. I beams, 4" @ 3.2 lbs/ft, 80 000 psi steel, galvanised, 12" c/c. Aptitong or equivalent, 1 1/8" thick shiplap finished, no preservative. Screws 10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" height. 3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions). Cargo pockets. 3/8" x 2 1/2" shaped steel. Bevelled. Between main beams, full length.
ENDS FRONT RAIL BUMPER  HEADBOARD  POCKETS BUMPER REAR RAIL	Formed steel, bolted. CMVSS 223-RIG approved (in accordance with Canada & USA regulation). Galvanized (G164) steel, bolted uprights to frames, 4" x 4" cross bar formed tubing at a maximum height of 22" from under tubing to ground. 48" high, steel, 4 uprights and top made of tubing and 11 gauge steel plate installed inside with retroreflective tapes. (this bulkhead is NOT D.O.T.) *** Galvanized *** 2 bolted galvanised pockets at front for removable headboard. 2 rubber dock, at the end of rear rail. Formed steel.
ELECTRICAL FRONT CONNECTOR ELECTRICAL SYSTEM MAIN SYSTEM  FLASHERS	7 way (SAE J560). Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, sealed beams, tail lights, markers lights "Dot", identification lights (2 1/2" dia.), licence light. Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber.



ITEM	DESCRIPTION
TAIL LIGHTS	Sealed beams (Grote DEL #54332) red. Qty: 1 additional each side. From outside, tail lights and flasher, flasher with parking, brake with parking.
LANDING GEAR	Holland, Mark V (LGS-4F010), with mounting plate, solid axles. *** galvanized ***
SAND SHOES	18" x 18".
CRANK	Road side.
BOGIE BASIC MECHANICAL BOGIE	Slider, Hutch H-9000, "UHMV" slider plastic pads, 4 locking pins, For 49" spread tandem spring suspension. 6" c/c between locating holes, (48" travel).
MECHANICAL (GROUND AXLES) SUSPENSION U-BOLTS SPRINGS AXLE(S) CAM SHAFTS TRACK DUST SHIELDS BRAKES BEARINGS SLACK ADJUSTERS SEALS	Hutch H-9700, tandem, under mount, 49" spread. With nuts at bottom. 3 leaves, model TRA 2741, 12 000 lbs capacity. Meritor, TN 467_L, 22 500 lbs. capacity. 28 splines. 77 1/2". None (Meritor axles). 16 1/2" standard, FRAS-LE MA212Q+ extended life lining. HM 218248 and HM 212049 Meritor, automatic, 28 splines. MFM, "Miles Free Maintenance System". Including National "Gold" seals, Axilok spindle nuts, National hub caps, with "Gearlube" mineral oil, SAE 80W90. (5 years warranty for parts and labor).
BRAKE CHAMBERS	T.S.E. brake, "Omnibrake" (30-30). (4 years warranty by T.S.E. for parts only).
HUBS AND DRUMS	10 stud disc hubs, balanced drums outboard mount, 285.75mm B.C., single flange nuts. For dual aluminum wheels.
RIMS	24.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes.
TIRES	Continental, 11 R 24.5 HSR-2                      16 ply                      (43.5")
MANUAL STOP BAR	One, Hutch.
AIR SYSTEM GLAD HANDS AIR VALVES	With filter. Meritor Wabco, IABS, 2 sensors 1 modulator.
ACCESSORIES REGISTRATION HOLDER MUD FLAPS SLIDING TRACK WINCHES	One plastic, Betts-PS-1 or equivalent. One set, rubber with moose logo and vertical grooves to reduce spray. Full length, "LL" extruded aluminum, road side. Qty: 12, ANCRA #49207-137-XZ, zinc plated slider (low profil 5 7/8").



ITEM	DESCRIPTION
<b>FINISHING</b>	
<b>PAINT</b>	Ready for Galvanized plateform.
<b>BOGIE</b>	One coat of epoxy primer and one acrylic urethane top coats, Color: GREY metallic, code: Q37-939514. Axles (wheel end) included. (Tandem). Axle line type: Color: GREY metallic, code: Q37-939514.
<b>RETROREFLECTIVE TAPES</b>	Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar.
<b>WHEELS OR RIMS</b>	White (power top coat).
<b>PAINT</b>	Vin plate to be made of metal. Pre-drill the web prior to galvanizing
<b>ADDITIONAL OPTIONS</b>	ref. U#231836 As you are certainly aware, the recent economic and political climate have presented several challenges, including continued uncertainties surrounding existing and potential future tariffs. These uncertainties have had in impact on costs of raw materials and components used in the manufacturing of our semi-trailers.
<b>GALVANIZED CHOICES</b>	Galvanized choices.
<b>PLATFORM</b>	Galvanized plateform. (no paint) ** WARNING: holes parachute shaped required for dripping **
<b>CROSSMEMBERS</b>	Galvanized
<b>FRONT RAIL</b>	Galvanized
<b>SIDE RAIL</b>	Galvanized
<b>REAR RAIL</b>	Galvanized
<b>BUMPER</b>	Galvanized
<b>CONFORMITY</b>	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.