

Model:Axle AttachmentCapacity in tons:55

1. DESIGN PARAMETERS	
Туре	Flip-up & removable
Framework	Fabricated
Suspension	Ridewell air
Axle attachment connections	Attachment to be equipped with top and bottom connecting ears, pin tubes with bolts and nuts, shims, chrome tapered connecting pins, air and electrical connections
Axle capacity	25,000# - GAWR 24,700#
Brakes	16-1/2" x 7" air actuated
Wheels	Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil seals, inner wheels steel with outer aluminum wheels polished
Anti-lock brake system	None
Tires	Four (4) 275/70R22.5 (H) 16PR radials
Bridge width	8'-6"
Axle frame height	41" frame; 37" bolster
Half bolster	With flag holder slots
Lash rings	2 at rear bent style
Lights and wiring	12 volt system with the following:
	All lights to be LED excluding license plate light
	All marker/I.D. lights to be 3/4" bullet style
	4 combination (2 PER SIDE) stop/turn/tail and back-up lights, back-up lights wired
	to switch on marker light circuit
	Strobe lights with switch at rear
	Wire for battery back-up
Paint	Valspar standard Talbert black, R-Cure 800 series paint with ZINC RICH primer
Mudflaps	Talbert anti-sail
Additional design specifications	1) 2 rubber bumpers on top
	2) 54" axle spacing
	3) Over ride chains
	4) Estimated empty weight: 2,850#
Compatibility	With existing Talbert Trailer, 55SA or 55CC
Compationity	white Austing Tubert Hundr, 555/4 01 5500

DISCLAIMER