

# HALE

## TRAILER

### BRAKE & WHEEL



A028090-A028095  
VIN: 75967-75972

#### SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

Trailer Model:	FB8X45SS-OTR-70H	Ship To:	TBD
Axle:	30,000 lb.	GVW:	70,000 lbs.
Tire:	295/75R-22.5	Wheel:	Dual
Color:	Red Black	Pinstripes:	None

#### Special Instructions:

Crane counterweight trailer  
Custom fabricated main beam construction (80 KSI web w/ 100 KSI beam flanges)  
45' overall length  
102" wide x 10' long upper wood deck w/ rub rail and stake pockets  
33' lower open deck  
(2) 30,000 lb. AXN air brake axles  
Hutch 9700 spring suspension w/ 54.5" axle spacing  
Upgrade to 295/75R-22.5" dual tire and wheel assemblies  
Bendix ABS air kit  
40" deck height  
3 lb. grating welded on lower deck in areas not occupied by counterweights  
(2) bolt-on steps for accessing lower deck - (1) on each side  
(2) sets of pin housings to lock counterweights all on lower deck w/ high locking position only - housings in front and rear  
(12) 1" bent D-rings on lower deck - (2) sets for each counterweight location  
(2) Boom rests - (1) at rear of upper wood deck and (1) at rear of lower deck  
Single poly fenders on rear axles  
Dual Jost A420 semi-style landing gears **w/ low-profile sand shoes**  
Axles, 71.5" Track w/ 54.5" Closed Axle Spacing

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.