

HALE

TRAILER



BRAKE & WHEEL



A028139-A028140
VIN: 46616 & 46617

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Base Model #: CCW53 x 102 Air Spread
 Serial #: 46616 - 46617
 components description
 CAPACITY 53FT 2Axle GVWR 69,000LBS
 OVERALL LENGTH 53'
 OVERALL HEIGHT FRONT 13'-6"
 OVERALL WIDTH 8' 6" - 53ft
 UPPER COUPLER HEIGHT 48"
 UPPER COUPLER PLATE 5/16" Plate With Pick Up Eye - Stainless Bulkhead and Pickup Plate
 KING PIN SETTING 36"
 SWING CLEARANCE 90"=36KP
 LANDING GEAR Two Speed With 12" Channel Foot
 SUSPENSIONS Air Ride - Hendrickson Intraax 23K- 2 Axle (Manual Dump)
 SUSPENSION LOCATION Set Rear Axle As 50ft Trailer Setting
 AXLES (2) 22,500K Capacity - Type 30 Chambers - Auto Slacks - ABS
 AXLE SPACING 10'2" Wide Spread
 LIFT AXLE Air Lift Front Axle - Air Ride
 DUST SHIELDS None
 WHEELS Disc - Steel - Hub Piloted- 22.5 - (Steel)
 TIRES 295/75R 22.5- Firestone FS560
 FRONT TYPE 10" Diagonal
 FRONT MATERIAL Stainless Steel .035 - Front Corners - Mirror Finish
 LADDERS None
 REAR DOOR TYPE Heavy Duty Barn Style Doors - Top Half Open for Blow In - Mesh
 REAR DOOR MATERIAL Heavy Duty Galvanized Mesh
 SIDE SHEET MATERIAL .063 Aluminum Smooth
 SIDE POST Extruded Aluminum on 12" Centers
 SIDE SHEET COLOR Pre Painted White
 LOWER RAIL Heavy Duty - Aluminum Lower Rail
 SIDE VENTS 12 Per Side- 22" in Height and Framed - Expanded Metal Vent Screen for 12" Post Spacing
 FRONT VENT None
 INSIDE LINING Front - H.D. Aluminum Chip Sheild & 60"x30'.026 Galvanized Sht Top/Center
 ROOF ASSY .063 Alum Smooth Sheet W/ Exp. Bows 16/16/16 CTRS
 FLOOR Keith Walk Floor Sys - 3/16"(2188)- STD Deck - Alum. Sub-53'
 Parker 6100-16 Wing Type Series Fittings.
 Male on Pressure Side and Female On Return Side.
 FLOOR SILLS 4" Steel - Wax-Dipped I-Beam w/ Undercoating
 LOAD BREAKERS No Load Breakers - Walking Floor Design
 SILL SPACING 12"/12"/12" Heavy Duty / Live Floor
 ANTI-SAIL MUD FLAPS Behind Rear Axle
 BUMPER H.D. 3" x 4" Non-Push Bumper(Flush Rear Frame)
 LIGHTS Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear
 CUSTOM LIGHTS None
 PAINT Black Undercoat - Fifth Wheel and Rear Frame Stainless
 UNDERCOAT Black Corrosion Resistant
 PICK UP EYE FRONT None CUSTOM 1 Stainless Rear Frame

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
 Equipment availability, prices and specifications are subject to change without notice.