

# HALE

## TRAILER

### BRAKE & WHEEL



A028273-A028287  
TEMP VIN: S027207-  
S027221

#### SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 \*FINANCING AVAILABLE

#### Infinity Drop Deck 53' Rear Axle Slide (Model Code: HAICD22RSA)

**Length / Width:** 53 feet x 102 inches

**Suspension Type:** Rear axle slide

**Deck Lengths:** 11 feet front and 42 feet rear

**Frame Rating:** 80,000 lbs distributed - 55,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads

**Rear Deck Height:** 40 inches - loaded

**Flooring:** 1 1/8 inch aluminum with 4 wood nailer strips

**Crossmembers:** 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel

**Single Coil Hauling Package:** Included

**Side Rails:** Exclusive **Revolutionary RASR Rail Technology** -- one piece routed aluminum designed for strength and impact

**Chain Cargo Tie Downs:** 17 pair recessed in siderails

**Stake Pockets:** Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)

**Rubrail:** Integrated with siderail

**Main Beams:** 130K load bearing flanges

**Kingpin:** 30 inches

**Loaded Fifth Wheel Height:** 49 inches

**Landing Gear:** OEM standard

**Knee Braces:** Fabricated on approx. 60 inch C/C

**Bulkhead Pockets:** 4 DOT type bulkhead pockets only - welded to front

**Bulkheads:** None standard

**Number of Axles:** 2

**Axle Spindle:** Tapered

**Brakes:** Spring brakes, auto slacks

**Air Line Filters:** (2) Meritor In-line type installed

**ABS: Meritor Wabco iABS 2S/1M Basic System Requested by Customer- no cable or tool**

**Axle Spread:** 122 inches open - 61 inches closed: Meets California, Canadian RTAC and BC dimensional specifications in closed position

**Hub and Drums:** 10-hole hub-piloted with outboard cast drums

**Wheel Ends:** Grease in hubs - \*\*\* 5-year wheel end warranty \*\*\*

**Wheels: 22.5 x 8.25 (4) Outer Aluminum, (4) Inner steel disc wheels - pre-painted white; 4 Spacers**

**Tires: 255/70R 22.5 16PR GENERAL HT+**

**Tire Inflation System:** None standard

**Suspension Detail:** Hendrickson AANL23K and AAZL23K buttoned-up Intraax air ride axles

**Air Assist Slide Box Pins:** Standard mount of controls on slider frame

**Auto Glad Hand Dump :** Installed

**Electric Dump Valve:** Wired to 7-way auxiliary socket to dump rear axle

**Front Corners:** Tapered

**Electrical System:** LED: 3 lights/side, 3 lights/side on rear - STANDARD

**Paint:** Black urethane on steel parts with Infinity decals - STANDARD

**Conspicuity Tape:** Per NHTSA specs - installed in recess on rubrails

**Bumper:** Weld-on type - meets underdrive requirements - painted steel

**Mudflaps:** 1 set OEM standard behind rear axle only

**Winch Track:** Full length integrated double L type aluminum on both sides where possible -- STANDARD

**Sliding Winches:** 12 total, 2 front deck and 10 rear deck: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers -- STANDARD

**27 foot Winch Straps:** None standard

**30 foot Winch Straps:** None standard

**Dock Bumpers:** 1 pair rubber on rear

**Spare Tire Carrier:** 1 standard - mounted between lower gooseneck beams at drop

**Hubodometer:** None standard

**Registration Holder:** Install registration holder - OEM standard

**Tool Box: Install (1) 18" x 18" x 60" Aluminum Double Door T-Lock Style Road Side Behind Drop**

**VIN Plate:** Bilingual US/Canadian VIN plate

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.