



A028288-A028329 **TEMP VIN: S027222-**S027263

## SALES RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Little Rock, AR: 833-424-8944 Baltimore, MD: 888-601-7500 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Raleigh, NC 833-418-9777 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Springfield, MA: Des Moines, IA: 888-673-5011 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235 Jacksonville, FL: Walpole, MA: 800-828-3055 800-854-5310

haletrailer.com | @haletrailer (f)





800-232-6535

\*FINANCING AVAILABLE

## Velocity 48' Wide Spread Air (Model Code: HAVSF12WSA)

Suspension Type: Wide spread air Length / Width: 48 feet x 102 inches

Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads

Flooring: 1 1/8 inch wood

Crossmembers: 12 inch centers - 4 inch jr. I-steel

Single Coil Hauling Package: Included Side Rails: 6 inch structural channel @ 6.5 lbs/ft Stake Pockets: 3/16 inch steel on 24 inch centers

Pipe Spools: Double between stake pockets Rubrail: 3/8 inch x 2 1/2 inch steel Main Beams: 130K load bearing flanges

Kingpin: 30 inches

Loaded Fifth Wheel Height: 49 inches

Landing Gear: OEM Standard with Forward & Rear Bracing

Knee Braces: Fabricated on approx. 60 inch C/C

Bulkheads: Removable aluminum bulkhead - no turnback - 48 inches high

Bulkhead Pockets: 4 - F-5 DOT-type steel

Number of Axles: 2 Axle Spindle: Tapered

Brakes: Spring brakes, auto slacks

Air Line Filters: (2) Meritor In-line type installed ABS: Meritor Wabco iABS 4S/2M - no cable or tool

Axle Spread: 122 inches - set at rear

Hub and Drums: 10-hole hub-piloted with outboard cast drums Wheel Ends: Grease in hubs - \*\*\* 5-year wheel end warranty \*\*\* Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD

Tires: 295/75R 22.5 14PR OEM standard tires - STANDARD

Tire Inflation System: None standard

Suspension Detail: Hendrickson AANT23K Intraax air ride

Auto Glad Hand Dump: Installed

Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle

Air Lift: None standard

Front Corners: Tapered

Electrical System: LED: 3 lights/side, 3 lights/side on rear - STANDARD

Paint: Black urethane with Velocity decals - STANDARD Conspicuity Tape: Per NHTSA specs - installed on rubrails Bumper: Weld-on type - meets underride requirements

Mudflaps: 2 sets OEM standard; Spring loaded brackets behind front axle

Spare Tire Carrier: None standard Winch Track: Steel on road side

Sliding Winches: (12) ZINC on Road Side

27 foot Winch Straps: None standard 30 foot Winch Straps: None standard Dock Bumpers: 1 pair rubber on rear Hubodometer: None standard

Registration Holder: Install registration holder - OEM standard

Tool Box: None standard

VIN Plate: Bilingual US/Canadian VIN plate

## DISCLAIMER