



A028332-A028341

TEMP VIN: S027266-S027275



SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Baltimore, MD: 888-601-7500

Concord, NC: 800-438-2250

Delmar, DE: 866-486-1400

Des Moines, IA: 888-673-5011

Elkton, MD: 800-544-7127

Jacksonville, FL: 800-828-3055

Little Rock, AR: 833-424-8944

Portland, ME: 800-325-4253

Raleigh, NC: 833-418-9777

Scranton, PA: 800-569-1400

Springfield, MA: 800-854-5306

Voorhees, NJ: 866-315-0235

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

We propose to furnish the following described equipment, material and services at prices, terms and delivery set forth below:

PEERLESS TRANSPORT SEMI: Dual Axle, Live Floor, 45' Length, 12.9 Units

STANDARD SPECIFICATIONS: CTSSF-45 (South Specs) (2026 Model)

Type: Peerless dual axle, transport semi-trailer, 45 degree front

Design: Box design, flat floor, end dump, live floor

Construction: Skin stressed .063 natural aluminum with aluminum exterior posts (14.5" centers), skins to extend to bottom of lower rail

Unloading Time: Approximately 8 minutes

Capacity: 12.9 units (96 cu yd)

Dimensions: 45' long, 8' wide, 12'6" high, 37" king pin location, 36" rear axle from rear of trailer

Tires: Eight (8) 11:00 x 24.5 radial tires

Wheels: Eight (8) 24.5 x 8.25 - 10 hole, 11 1/4" B.C. hi-tensile steel, Unimount

Axles: 22,500# cap. , 71 1/2" track, 10 stud, 11 1/4" B.C. hubs, outboard drums, oil seals, quick change brake shoes, auto slacks

Brakes: 16 1/2" x 7" air, CM18 lining, type 3030 air chambers, DOT relay emergency system

A.B.S.: 2 sensor - 1 module

Suspension: Four spring three leaf tandem (Hutch H9700T with slider)

Landing Gear: Two speed, crank on driver's side (Holland Atlas 55), channel bracing

King Pin: Standard SAE, heat treated, 37" setting, 49" height, 3 I-beams with 5/16" plate

Cross Sills & Decking: Keith 7/32", 3.0" cylinders, 24" wear strips (one end) 4" Jr I-Beams on 12" centers with aluminum sub-deck,

Top: Flat design, open top, single center tie

Top Cover: Shur-lok roll over tarp, black in color, rear crank, 6" arched tarp bows, Flex-handle and telescoping pole, handles on both sides

Rear Door: Full opening, side hinged, solid freight door with four (4) latches, low mount, offset hinges



Dump Stands: Two (2) blades at rear for standard Peerless backstop

Screens: **Safety screens on front and under drive**

Ladders: **One located at front and one located at rear**

Rope Hooks: None

Mud Flaps: Legal, rubber

Wiring: Unitized wiring system, 12 volt, air and light plugs on front center

Lights: Four (4) legal DOT combination stop, tail and directional lights. Legal DOT clearance lights

Reflectors: Legal DOT

Paint: Aluminum natural, **steel components primed and painted black**

Weight: Approximately 13,700# (+/- 3%)

REF#: #65967

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.