

HALE

TRAILER

BRAKE & WHEEL



A028422-A028423
VIN: 000238-000239

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Base Weight: 10,220

22.5 ANR 22.5 Ton Tandem Air Tilt/No Ramp Tags

TRAILER

Overall Length	34 ft. 7 in.
Overall Width	102 in.
Weight lbs +/- 2%	10543, including options
A-Frame	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
Hitch	3 in. pintle eye, adjustable 7 position, 15 in. to 28 1/2 in.

DECK

Deck Length	21 ft.
Loaded Deck Height	34 in.
Main Frame	Hi-Tensile Wide Flange 14 in. @ 26
Cross Members	Hi-Tensile 6 in. Channel @ 8.2
Side Rail	Hi-Tensile 8 in. Channel @ 11.5 open on inside
Air Tilt Deck	*NPO*: * 4 Air Bags
Floor	1 3/8 in. x 7 in. Keruing Shiplapped
Landing Gear	*NPO*: Holland Mark V, Galvanized Landing Gear
Rear	Wedge Style bumper with air assisted tilt deck for ground loading
Step	*NPO*: Bolt on, Located on Front Corner of deck, Driver side , and 1 Step on Passenger Side in front of Lead Axle

SUSPENSION/AXLES

Axles	25,000 lbs Capacity 77.5 in. Track
Spread	49 in.
Suspension	Heavy Duty spring ride
Alum Air Tank	*NPO*: Drain Plug with Cable
Brakes	Quick Change 12 1/4 in. x 7 in.
Brake Chamber	#3030, All Axles
Air Brake System	2S/1M
Air Tank(s)	Aluminum
Bearings	Oil Bath
Slack Adjusters	Automatic
Hubs & Drums	8 Stud Unimount C / W Cast Drums
Tires	235/75R17.5 16 ply
Wheels	Alum. Wheel Pkg. 17.5 (4 Steel, 4 Polished)

BEAVERTAIL

Length	6 ft. @ 8 degree slope, Self Cleaning Outside , Planked in inside
--------	---

GENERAL SPECIFICATIONS

Electrical System	Modular, Vapor Proof GROTE Ultra Blue
Lights	LED CMVSS 108 / FMVSS 108
Lights	Amber Flashing Strobe Lights (Mounted in Bumper)
Front Connector	SAE J560 7 Pin
Color	Galvanized
Mudflaps	1 set of BWS at rear

GENERAL SPECIFICATIONS

Toolbox	Full A Frame mounted with solid bottom and aluminum cover
Load Securement	9 pair of D-rings: 7 pr on main deck evenly spaced, 1 pr on main beam at headboard, 1 pr on top of A Frame on both sides of toolbox
Fenders	3/16 in. deck plate

GVWR Rating is based on standard configuration and a 15% Tongue weight distribution

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.