



A028513-A028524



SALES | RENTALS | PARTS | SERVICE

| | | | |
|-------------------|--------------|------------------|--------------|
| Allentown, PA: | 800-383-8894 | Little Rock, AR: | 833-424-8944 |
| Baltimore, MD: | 888-601-7500 | Portland, ME: | 800-325-4253 |
| Concord, NC: | 800-438-2250 | Raleigh, NC: | 833-418-9777 |
| Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |
| Jacksonville, FL: | 800-828-3055 | Walpole, MA: | 800-854-5310 |

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

| ITEM | DESCRIPTION |
|-----------------------|--|
| TYPE | TELESCOPIC SEMI-TRAILER, STEEL PLATFORM. |
| DIMENSIONS | |
| LENGTH | 53'-0" closed. |
| LENGTH | 90'-0" open |
| OPENINGS | Located at 53', 58', 63', 68', 73', 78', 83' and 90'. |
| WIDTH | 102", 97" between side rails. |
| HEIGHT | Floor, approximately 61 1/4" high at front and 58" at rear. |
| COUPLING | |
| COUPLER PLATE | 3/8", plug welded structure. |
| KING PIN LOCATION | 18" from front. |
| COUPLER HEIGHT | 49". |
| STRUCTURE | Frame with "CAMBER". |
| FLANGES | Female section, (exterior), 3/8" x 6", 100 000 psi steel, 24" high. |
| FLANGES | Male section (interior), 3/4" x 6", 60 000 psi steel, 16 3/4" high. |
| WEB | 1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel. |
| GOOSENECK | 12" high, with integrated nose ramp and 48" straight behind king pin. |
| CROSSMEMBERS | I beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, galvanized, bolted, 12" c/c. (for bolted construction) |
| FLOOR | Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative. |
| FLOOR FASTENING | Two screws per board at each crossmember. (With galvanized flatbed or crossmembers) |
| SIDE RAILS | Galvanized 10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" high. 3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions). Galvanized front and rear bolted sills. |
| SIDE BOXES | 3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high. (USA Dimensions). |
| RUB RAILS | 3/8" x 2 1/2" shaped steel. |
| CORNERS | Bevelled. |
| DIAGONAL BRACES | 2" x 2" x 3/16" angles, **bolted** in web and to a crossmember, |
| X BRACES | Between main beams, full length, sheet metal with cutting holes at front and rear between male main beams. |
| LOCKS | Air operated with a third glad hand at front. |
| ROLLERS | 4, 2 on female sections of frames and 2 on male sections. |
| SPACERS FOR RUB RAILS | Double between side boxes. |
| ENDS | |
| FRONT RAIL | Formed steel 1/4". |
| BUMPER | CMVSS 223-RIG approved (in accordance with Canada & USA regulations). Uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground. |
| BUMPER | Aluminum plate, bolted between bumper uprights to close rear. |
| POCKETS | 2 welded pockets at front for removable headboard. |
| REAR RAIL | 11" high, 9 gauge formed steel, including 3 boxes at rear and 3/8" x 2 1/2" shaped steel. |



| ITEM | DESCRIPTION |
|----------------------------|---|
| ELECTRICAL | |
| FRONT CONNECTOR | 7 way (SAE J560), Phillips brand. |
| ELECTRICAL SYSTEM | Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. |
| MAIN SYSTEM | Grote Ultra Blue LED, grounded to front connector, sealed beams Grote. (tail lights with male pins #54332, markers #47122, 47233 (2 1/2" dia.), licence light #60280-M, with vapor proof junction box Truck-Lite #50400). |
| TURN SIGNAL | Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber. |
| REAR ADD. CONNECTOR | 4 way. |
| STROBE LIGHTS | Sealed beams (Grote LED #77353 strobe) amber. Qty: (1) each side. toggle switch installed: REAR |
| TAIL LIGHTS | Sealed beams (Grote DEL #54332) red. Qty: 1 additionnal each side. From outside, tail lights and flasher, flasher with parking, brake with parking. |
| LANDING GEAR | Holland, Mark V (LGS-4F010), with mounting plate, full galvanized. |
| SAND SHOES | 18" x 18" galvanized, solid axles. |
| CRANK | Road side. |
| BOGIE | |
| BASIC SUSPENSION | |
| BOGIE | Slider, air ride suspension, tridem, 60" spread.*** galvanized *** Bogie tubing frame for suspension with 9" mounting height. (96" travel) Legal Canada-USA, (applicable for 53'telescopie) |
| SUSPENSION | Hendrickson HT-250US (9), tridem, 60" spread. (Use only with slider bogie) |
| U-BOLTS | With nuts at bottom. |
| SPRINGS | Air. |
| AXLE(S) | Meritor, TQ 467_L, 21 900 lbs. capacity. |
| SPIDERS | Welded. |
| CAM SHAFTS | 28 splines with enclosures, for Meritor axles. |
| TRACK | 77 1/2". |
| DUST SHIELDS | Steel, bolted. |
| BRAKES | 16 1/2" standard, FRAS-LE MA212Q+ extended life lining. |
| BEARINGS | HM 218248 and HM 212049. |
| SLACK ADJUSTERS | Meritor, automatic, 28 splines. |
| SEALS | Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. |
| BRAKE CHAMBERS | T.S.E. brake, "Omnibrake" (30-30). (4 years warranty by T.S.E. for parts only). |
| HUBS AND DRUMS | 10 studs disc hubs, outboard mount, 285.75mm B.C., single flange nuts. For dual steel wheels or single wheels. |
| RIMS | 22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes. For dual alum wheels |
| TIRES | Continental, 11 R 22.5 HT3 ECO-PLUS 14 ply (41.2") |
| MANUAL STOP BAR(S) | Two, Manac heavy duty, 1 5/8" diameter, galvanized. |
| AIR SYSTEM | Aluminum air tank. (tridem) |



| ITEM | DESCRIPTION |
|---|--|
| GLAD HANDS AIR VALVES VALVE VALVE CONTROL BOX AUTOMATIC TIRE INFLATION | Fixed. Meritor Wabco, IABS, 2 sensors 1 modulator. (2) Fast-brake kit. Automatic blow down valve in a control box, including Glycerin filled pressure gauge, in P.S.I., to indicate load with a conversion table. Stainless steel Automatic Tire inflation System Hendrickson Tiremaax PRO. Axles preparation included, dressed axles HN/HP or disc brake. *** Maximum allowable tire pressure for this device is 120psi *** (tridem application, Hendrickson axles, dual tires) Warning lamp TIREMAAX installed on road side front radius. |
| ACCESSORIES REGISTRATION HOLDER WINCHES SLIDING TRACK MUD FLAPS | One plastic, Betts-PS-1 or equivalent. Qty: 12, ANCRA #49207-137-XZ, zinc plated slider (5 7/8"). Full length, "LL" extruded aluminum, road side. One set, rubber with Manac logo and vertical grooves to reduce spray. |
| FINISHING PAINT BOGIE AXLE(S) PAINTED HUBS WHEELS OR RIMS RETROREFLECTIVE TAPES SERIAL PLATE | Galvanized plateform. (no paint) Slider, tandem, galvanized steel. Same color as trailer. Same color as trailer. White. Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar. V.I.N. plate to be stick on an aluminum plate riveted on the frame. (it doesn't stick on galvanized steel) |
| ADDITIONAL OPTIONS R | estimated empty weight is 21,429 LBS +/- 3% same as U#233321 As you are certainly aware, the recent economic and political climate have presented several challenges, including continued uncertainties surrounding existing and potential future tariffs. These uncertainties have had in impact on costs of raw materials and components used in the manufacturing of our semi-trailers. |
| CONFORMITY | This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer. |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.