

# HALE

## TRAILER

### BRAKE & WHEEL



A028560-A028564  
VIN: A6199-A6203

#### SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



**800-232-6535** \*FINANCING AVAILABLE

Workhorse 55 PVR PRO (Model: WORKHORSE 55 PVR PRO)	
WKH55PVRPF*824543	Est. Wt.: 23,590# +/- 3%
TRAILER - GENERAL	
<b>Capacity:</b> 50 tons in 12-foot length or 55 tons in 16-foot with 4 axles close coupled - GAWR and tire ratings determine legal payloads	
<b>Length (Trailer Only):</b> 53 feet 0 inches	
<b>Width:</b> 8 feet 6 inches	
<b>Compatibility:</b> Designed to Accept Optional 51/60 Rear Axle	
GOOSENECK	
<b>Gooseneck Design:</b> Narrow hydraulic removable non-ground bearing - swing radius of 108 inches (12ft 2in overall gooseneck length) set up for wetline operation	
<b>Loaded Fifth Wheel Height:</b> 52 in nominal loaded fifth wheel height with 7 ride height positions	
<b>Kingpin:</b> Removable kingpin at 82 and 108 inch radius	
<b>Power Source:</b> Set Up for Wet Line Operation	
<b>Tool Box:</b> None	
<b>Hydraulic Fittings:</b> OEM Standard 1/2 inch	
DECK	
<b>Framework:</b> All Main Longitudinal Members Fabricated with 100,000# Minimum Yield Steel Flanges with 50,000# Webs	
<b>Deck Design:</b> Flat level deck design (tapered beam design)	
<b>Deck Length:</b> 24 feet 0 inches Clear Deck Length	
<b>Loaded Deck Height:</b> 22 inches with 6 inches Ground Clearance	
<b>Crossmembers:</b> High Density Crossmember Package- Additional stub crossmembers, net spacing of 11 inches	
<b>Flooring:</b> 1.5 inch nominal apitong wood (full width)	
<b>Front Ramps:</b> Apitong Wood Filled Double Hinged Adjustable Width to 44 inches inside to inside (9 degree load angle)	
<b>Center Roller Ramp:</b> None	
<b>Extension Brackets:</b> 12 pair - 24 total removable swing type, 1 pair - 2 total heavy duty removable hook-on type	
<b>Tool Box:</b> 1 fully covered toolbox with lockable lid (front of deck) (When 2-piece center insert is removed, perforated plate under hammer plate becomes additional storage area- rear of deck (Storage area not accessible when standard covered rear bogie is in place)	
<b>Hammer Plate:</b> Hammer Plate installed over recessed crossmembers. Perforated plate under hammer plate forming one storage area; includes 1 pair of D rings (Hammer Plate will not be accessible with the standard removable covered rear bogie)	
REAR BRIDGE	
<b>Front Bogie Ramp:</b> Sloped (17 degree angle)	
<b>Boom Trough:</b> Low Boom Well, with V crossmember with bolt-in V pan	
<b>Deck to Bogie Connection:</b> Fixed w/ ramps outboard mainbeams, apitong wood filled	
<b>Bolsters:</b> Recessed	
<b>Covered Rear Bogie:</b> Load Bearing Wheel Covers- Apitong Wood Filled with 2-piece center insert for full width loading	
<b>Rear Bogie Height:</b> 45 1/4 inches	
<b>Connections for Future Axle Attachment:</b> Air and Electrical Connections to Go Along with Connecting Ears	

<b>Accent Package: None</b>	
<b>AXLES</b>	
<b>Number of Axles: 3</b>	
<b>Axle Capacity:</b> 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
<b>Axle Spread:</b> 50 inches (between axles)	
<b>Brakes:</b> 16.5 inches x 7 inches with 5.5 inches Autoslacks - Heavy Duty Brake Drums - Outboard Mount	
<b>Spring Brakes:</b> Spring brakes on axle 2	
<b>Dust Shields: None</b>	
<b>Hubodometer: None</b>	
<b>SUSPENSION</b>	
<b>Suspension:</b> Air Ride	
<b>ABS: None</b>	
<b>Third Lift Axle:</b> Air Lift Installed on Third Axle	
<b>Chain Lift:</b> First Axle (acts as a limit chain)	
<b>Override Chains:</b> Override Chains Axle 2 & 3	
<b>Ride Height Control:</b> 7-position mechanical ride height control system	
<b>Dump Valve:</b> Automatic/Manual Raise/Lower Control	
<b>Liquid Filled Gauge: None</b>	
<b>Load Scale: None Standard</b>	
<b>WHEELS AND TIRES</b>	
<b>Wheels: 8.25 x 22.5 LVL One Buffed Outside/Steel Inside - Hub-Piloted</b>	
<b>Tires:</b> 275/70R 22.5 H Ply OEM Standard	
<b>Tire Inflation System: None</b>	
<b>Hubodometer: None Standard</b>	
<b>Tire Inflation: None Standard</b>	
<b>LIGHTING</b>	
<b>Electrical System:</b> DOT Sealed Beam and Harness with LED Lights and 4-inch Flush Mounted Battery Powered Amber Strobes	
<b>Tail Lights:</b> 3 Tail Light Package	
<b>Marker Lights:</b> 3 Marker Lights Per Side Including Mid-Turn	
<b>Electrical Receptacle:</b> J560 7-Pin Connector	
<b>Additional Marker Lights: None Standard</b>	
<b>PAINT</b>	
<b>Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001</b>	
<b>PAINT</b>	
<b>MISCELLANEOUS</b>	
<b>Lash Rings:</b> 17 Pair - 34 Total	
<b>Flag Holders:</b> 2 Pair Flag Holders	
<b>VIN Plate:</b> Bilingual VIN Plate	
<b>Registration/Document Holder:</b> Registration/document holder installed	

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.