

SALES	RENTALS		PARTS	SERVICE
Allentown, PA:	800-383-8894		Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500		Portland, ME:	800-325-4253
Concord, NC:	800-438-2250		Raleigh, NC	833-418-9777
Delmar, DE:	866-486-1400		Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011		Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127		Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055		Walpole, MA:	800-854-5310
haletrailer.com @haletrailer f 🎔 🛅 🎯 🛗				
800-232-6535 *FINANCING AVAILABLE				

RENLXT40NF*834542	Est. Wt.: 23,685# +/- 39
TRAILER - GENERAL	
Capacity: 40 tons in 16-foot length - GAWR and GVWR determine legal loads	
Load Base: 16-foot rigid 2-point load centered in deck	
Length (Trailer Only): 50 feet 1 inch (closed); 71 feet 1 inch (open)	
Width: 8 feet 6 inches	
Compatibility: Designed to accept optional third flip axle	
GOOSENECK	
Gooseneck Design: Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11 ft 11 in overall gooseneck length) - set up for wet line operation	
Loaded Fifth Wheel Height: Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal)	
Power Source: None	
DECK	
Deck Design: Flat level telescopic deck design	
Deck Length: 34 feet 0 inches clear deck length (retracted) - 60 feet 0 inches	
(extended) **Note when option is selected trailer overrall length is 55 ft 1 in	
Loaded Deck Height: 20 inches with 6 inches ground clearance	
Flooring: 1 3/8 inch nominal wood (full width)	
Recessed Floor Mounted D-Ring Package: None	
Crossmembers: On 24 inch centers	
Front Ramps: None, front of deck sloped top down to assist in loading with traction cleats	
Extension Brackets: Outriggers - 14 pair - 28 total removable swing type, 1 pair - 2 total removable hook-on type	
Front Bogie Ramp: Sloped steel bogie ramp (full width)	
Deck to Bogie Connection: Fixed	
AXLES	·
Number of Axles: 2	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 54.5 inches spread (between axles)	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Dust Shields: None	
Spring Brakes: Spring brakes on 2 axles	
SUSPENSION	
Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
Suspension: Air ride with automatic controls	
First Axle Lift: Chain lift included on first axle when 34ft deck is selected	
ABS: 4S/2M system without diagnostic tool and cable	
Load Scale: None Standard	
WHEELS AND TIRES	

Tires: 255/70R 22.5 H ply OEM Standard					
Hubodometer: None Standard					
Tire Inflation: None Standard					
REAR BRIDGE					
Covered Rear Bogie: Rear bogie platform with 1 1/8 inch wood floor					
Rear Bogie Height: 41 inches					
Bumper: 3 tail light package					
Mini Boom Trough & Traction Cleats: None					
Connections for Future Axle Attachment: Air and electrical connections to go along with connecting ears					
Liquid Filled Gauge: Included					
Accent Package: Stainless steel bumper insert					
LIGHTING					
Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes					
Electrical Receptacle: J560 7-pin connector					
Marker Lights: 8 marker lights per side including mid-turn					
Additional Marker Lights: None Standard					
PAINT					
Paint: Fontaine black polyurethane enamel PN 51172000/G02BC0001					
MISCELLANEOUS					
Lash Rings: 12 pair - 24 total					
Flag Holders: 2 pair flag holders					
VIN Plate: Bilingual VIN plate					
Registration/Document Holder: Registration/document holder installed					