

XL SPECIALIZED TRAILERS

XL 180 DOUBLE GOOSENECK EXPANDABLE

OVERALL LENGTH	
OVERALL WIDTH	144" TC
CAPACITY	180,000
WEIGHT +/- 3%	

144" TO 240" 180,000 LB DISTRIBUTED

FRONT GOOSENECK

I KONT GOODENEOK	
LENGTH	24' 7 3/4" COLLAPSED LENGTH
KINGPIN SETTING	16", 3.5" KING PIN
SWING CLEARANCE	238"
5TH WHEEL HEIGHT	49"
DECKING	NONE
CYLINDERS	DUAL POSITION FOR CYLINDERS
ΗΑΤ ΒΟΧ	HYDRAULIC HAT BOX IN GOOSENECK WITH 36" OF LIFT
	2 EXPANDABLE CROSS BRACES WITH INDIVIDUAL ADJUSTMENT CYLINDERS- 1 EXPANDABLE GATE HONDA IGX SCU W/ REMOTE START
	1 SET OF GROTE TRILLIANT WORK LIGHT ON TOP OF HEADER BEAM, 1 SET ON POWER TOWER
	(7) FUNCTION WIRELESS REMOTE (REMOTE START FOR SCU, CROSS BRACES, HAT BOX ON TRAILER) MANUAL HYDRAULIC CONTROLS FOR GOOSENECK OPERATION ON DRIVER SIDE
	(3) PAIR OF FLAT D-RINGS ON TOP FLANGE OF THE GOOSENECK, (1) ON REAR OF BASE
	(2) ON TOP FOR BALANCE LIFTING
MAIN DECK	
LENGTH	30' HYDRAULIC EXPANDABLE DECK FROM 12' WIDE TO 20' WIDE (OUTSIDE TO OUTSIDE)
	(10' 2" TO 18' 2" INSIDE TO INSIDE)
LOADED DECK HEIGHT	28" LOADED OUTER BEAMS & 8" LOADED TOP OF CROSSMEMBERS IN LOWEST SETTING
DECKING	NONE
CROSSMEMBER	(6) 4" X 12" FAB EXPANDABLE CROSSMEMBERS - BOLT ON REVERSABLE WITH HOLES 12" O/C CROSSMEBERS TO HAVE 3" INCREMENT ADJUSTMENT
	CROSSMEMBERS RATED FOR 30KLBS EACH WITH LOAD SUPPORTED TO OUTSIDE
BEAMS	(2) 24" PERIMETER FRAME BEAMS
D-RINGS	(10) PER SIDE ON THE OUTSIDE, (1) ON EACH CORNER ON THE INSIDE SHIM STORAGE

REAR GOOSENECK

LENGTH KINGPIN SETTING SWING CLEARANCE 5TH WHEEL HEIGHT DECKING HAT BOX CYLINDERS	24' 7 3/4" COLLAPSED LENGTH ROCKER BOLSTER CONNECTION FOR DOLLY 238" 49" NONE POWER TOWER HAT BOX WITH 36" OF TRAVEL DUAL POSITION FOR CYLINDERS 2 EXPANDABLE CROSS BRACES WITH INDIVIDUAL ADJUSTMENT CYLINDERS- 1 EXPANDABLE GATE HONDA IGX SCU W/ REMOTE START (10) FUNCTION WIRELESS REMOTE (REMOTE START FOR SCU, CROSS BRACES, HAT BOX, STEERING ON DOLLY) MANUAL HYDRAULIC CONTROLS FOR REAR GOOSENECK OPERATION IN GOOSENECK CONTROL BOX (3) PAIR OF FLAT D-RINGS ON TOP FLANGE OF THE GOOSENECK, (1) ON REAR OF BASE (2) ON TOP FOR BALANCE LIFTING
ELECTRICAL	12V SEALED GROTE SYSTEM 1 SET OF GROTE TRILLIANT WORK LIGHT ON TOP OF HEADER BEAM, 1 SET ON POWER TOWER
PAINT	BLACK
ADDITIONAL	(2) PAIR OF FLAG HOLDERS (ONE PAIR EACH END OF DECK) NECKS ABLE TO HOOK TOGETHER
	CLEARANCE LIGHT, MIDTURN, AND STROBE LIGHT ON THE BASE OF THE NECKS 3' FROM BOTTOM
	FLIP DOWN LADDER ON ROADSIDE OF EACH GOOSENECK REMOTE GREASE LINES FOR PINS ON GOOSENECKS GOOSENECK HEIGHT MUST BE UNDER 9' 10" RED/GREEN SCU ON/OFF INDICATOR LIGHT EXPANDABLES GATES HAVE INDICATORS ON THE OPENINGS
	TO FIT TO: 100 JPS 25110 120 DOLLY 25111 CROSSMEMEBERS SO 200777 15' DECK SECTION 200778 25' DECK SECTION 200779

DISCLAIMER