

A110HDG-E (Alpha Series Hydraulic Detachable Extendable)

Capacity 110,000 lbs. Open in 2 point rigid load base

 Concentrated
 110,000 lbs. in 16' Closed

 OAL
 53'
 OAW
 102"

Gooseneck 10' 5" Hydraulic Detachable Sub Frame

51" 5th Wheel Height 14' 1" Long

15" King Pin 39" Loaded Deck Height

80" Swing Clearance
32 Degree Rear Transition
5 Position Ride Height Adjustment
Open Wheels with Bolsters

3' Flip Neck Connection Chain Slots in Each Bolster
3' Flip Neck(116" Swing) 2 Flat D-Rings at Rear

LED Work Light Flag Holders

Main Deck 28' 7" Closed- 50' Open 1 pair Stake Pockets in Tail Channel Frame Reinforcement for Single Axle

14" Fabricated I-Beams
20" Loaded Deck Height

6" Ground Clearance

Cross Members ALT on 12" Centers

8 Bent D-Rings per Side

Chain Slots on 24" Centers each side 1 3/4" Apitong Raised Decking-Full Width

Upper Flange Reinforment

Front Flip Ramps

Full Depth Removable Swingout Outriggers

Air Operated Lock Pin, Deck opens every 2'

Toolbox W/Lid In Rear of Male Deck Section Airweigh Quickweigh Scale

255/70R22.5 Tires

Suspension Controls in Bolster

Axles and Suspension

Grote Ortra Blue-3

2 Pr. Side Markers/1 Pr. Mid-Turn on Deck

2 Tail Light Package with Stainless Steel Covers

Grote Ultra Blue-Seal Wire Harness

Gooseneck

13 hp Honda in base section/Dual Operation

Main Deck

2 Pr Additional Clerance Lights

Paint

Lighting

Black

Sub Frame

275/70R22.5 tires

Polished Aluminum Outer Wheels

3rd tail light package with strobe (no battery)
Battery back for strobe with 4-way plug for FA

Stinger

3 - 25,000 lb Axles

54 1/2" Axle Spacing

Ridewell Suspension

Raise & Lower Valve

Air Lift on 3rd Axle

16 1/2" x 7" Drum Brakes

Spring Brakes on Two Axles

Manual Ride Height Control

Nitrogen Stinger Top Lugs