

A90HDGC-E (Alpha Series Hydraulic Detachable Double Drop Extendable)

90,000 lbs. Open in 2 point rigid load base Capacity

Concentrated 90,000 lbs. in 16' Closed OAL 48' **OAW** 102"

15" King Pin

Gooseneck **Sub Frame**

> 10' 5" Hydraulic Detachable 9' Long 40" Loaded Deck Height

49" 5th Wheel Height

80" Swing Clearance 2 Bent D-Rings Per Side

lighning holes each side platform

5 Position Ride Height

Full Width Platform - 1 1/8" Apitong

Stainless Mudflaps 3' Flip Neck Connection

LED Work Light on Rear Platform

1 Pair Flag Holders 1 pair Stake Pockets in Tail Channel

Two Pair of Chain Drops in Center One Pair of Pan D-Rings at Rear

Full Width Decking - 13/8" Apitong

Frame Reinforcement for

2 Axle Stinger

Main Deck **Axles and Suspension**

28' 7" Closed- 50' Open 14" Fabricated I-Beams 20" Loaded Deck Height 6" Ground Clearance

6"/4" JRI Beam Cross Members ALT on 12" Centers

8 Bent D-Rings per Side

Chain Slots on 24" Centers each side 1 1/8" Apitong Flush Decking-Full Width Front Ramps tpaered to 4" W/Traction Bars

Removable Swingout Outriggers

Air Operated Lock Pin, Deck opens every 2' Toolbox W/Lid In Rear of Male Deck Section

Lighting

2 Tail Light Package with Stainless Steel Covers 2 Pr. Side Markers/ 1 Pr. Mid-Turns in Deck Grote Ultra Blue-Seal Wire Harness

General

4" Amber Strobe Light Aluminum polished wheels out

Paint

DISCLAIMER Black

2 - 25,000 lb Axles 54" Axle Spacing **Cush Suspension**

16 1/2" x 7" Drum Brakes

4S2M ABS

Spring Brakes on Both Axles

Raise & Lower Valve

Manual Ride Height Control Airweigh Quickweigh Scale 8.25 x 22.5 Steel Wheels 255/70R22.5 Tires

Gooseneck

Honda Pony Motor with Stainless Lid

3' Flip Neck

Neck Platform Deduct

Main Deck

33' 7"- 60' Deck

Additional Clearance Light Front and Rear