

HALE

TRAILER

BRAKE & WHEEL



A028827-A028833
VIN: P3621-P3627

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Magnitude 302 Jeep GEN 3 (Model: 302JEEP)

	Est. Wt.: 5865 # +/- 3%
Capacity: 30 tons GAWR and tire rating determine legal loads	
Length (Jeep Only): 17 feet 11 inches	
Width: 8 feet 5 inches	
Compatibility: Magnitude 55H or Magnitude 55L Plus with optional 35-inch flip box	
Gooseneck Design: Fixed Narrow Width	
Loaded Fifth Wheel Height: 48 in.	
Swing Radius 94 in.	
Deck Design: Beam design	
Fifth wheel: OEM Standard, 12 in. slide adjustable, 57.5 inches fifth wheel height	
Number of Axles: 2	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 49 inches (between axles)	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount Spring Brakes on Axle 1	
Dust Shields: None	
Suspension: Air ride	
Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
Supports: Single Telescopic	
ABS: Not required	
Load Scale: None	
Tires: 275/70R 22.5 H ply OEM Standard	
Wheels: 8.25 x 22.5 Outer Lvl one buffed wheels/ steel disc - hub-piloted inside	
Hubodometer: None	
Tire Inflation: Tire Inflation Installed Tiremaxx Pro	
Electrical System: DOT sealed beam and harness	
Additional Marker Lights: None	
Paint: Fontaine black polyurethane enamel	
VIN Plate: Bilingual VIN plate	
Registration/Document Holder: Registration/document holder intalled	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.