

HALE

TRAILER

BRAKE & WHEEL



A029353-A029355
VIN: 000284-000286

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Base Weight: 11,820

30NTT 30 Ton Tridem Non Tilt Tags

TRAILER

Overall Length 37 ft. 7 in.
Overall Width 102 in.
Weight lbs +/- 2% 13352, including options
A-Frame 6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
Hitch 3 in. pintle eye, adjustable 7 position, 19 in. to 33 in.

DECK

Deck Length 24 ft.
Loaded Deck Height 34 in.
Main Frame Hi-Tensile Wide Flange 14 in. @ 26
Cross Members Hi-Tensile 6 in. Channel @ 8.2
Side Rail Hi-Tensile 8 in. Channel @ 11.5 open on inside
Floor 1 3/8 in. x 7 in. Keruing Shiplapped
Landing Gear *NPO*: Dual 2 Speed Holland Mark V, Galvanized Landing Gear
Step *NPO*: Bolt on, Located on Front Corner of deck, Driver side and 1 on Passenger side ahead of lead axle

SUSPENSION/AXLES

Axles 25,000 lbs Capacity 77.5 in. Track ,1 Lift Axle with Control Box
Spread 49 in.
Suspension Heavy Duty spring ride., 1 Ridewell RAR 260 Underslung Air ride 25,000lbs. (includes air gauge)
Alum Air Tank *NPO*: Drain plug with cable
Brakes Quick Change 12 1/4 in. x 7 in.
Brake Chamber #3030, All Axles
Air Brake System 2S/1M
Air Tank(s) Aluminum
Bearings Oil Bath
Slack Adjusters Automatic
Hubs & Drums 8 Stud Unimount C / W Cast Drums
Tires 235/75R17.5 16 ply
Wheels Alum. Wheel Pkg. 17.5 (6 steel, 6 polished)

BEAVERTAIL

Length 6 ft. Beavertail, Planked

RAMPS

Length * 38 in. x 76 in. Wood Filled Air Operated Ramp
Ramp Support *NPO*: Ramp Support
Brackets *NPO*: To hold ramp brace when not in use, 1 per side

GENERAL SPECIFICATIONS

Electrical System Modular, Vapor Proof GROTE Ultra Blue
Lights LED CMVSS 108 / FMVSS 108
Lights *NPO*: Amber Flashing Strobe Lights(Mounted in Ramps)

GENERAL SPECIFICATIONS

Lights	*NPO*: Switch for strobes mounted in toolbox
Front Connector	SAE J560 7 Pin
Color	Galvanized
Mudflaps	1 set of BWS at rear
Toolbox	Full A Frame mounted with solid bottom and aluminum cover
Load Securement	11 pair of D-rings: 9 pr on main deck, evenly spaced, 1 pr on top of main beam at headboard, 1 pr on top of A Frame top flange on each side of toolbox
Fenders	3/16 in. deck plate

GVWR Rating is based on standard configuration and a 15% Tongue weight distribution

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.