

HALE

TRAILER

BRAKE & WHEEL

EAST GENESIS UNLOADER

OPEN TOP



A029358-A029361

VIN: 91163-91166

SALES | RENTALS | PARTS | SERVICE

| | | | |
|-------------------|--------------|------------------|--------------|
| Allentown, PA: | 800-383-8894 | Little Rock, AR: | 833-424-8944 |
| Baltimore, MD: | 888-601-7500 | Portland, ME: | 800-325-4253 |
| Concord, NC: | 800-438-2250 | Raleigh, NC: | 833-418-9777 |
| Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |
| Jacksonville, FL: | 800-828-3055 | Walpole, MA: | 800-854-5310 |

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

| BODY: "GENESIS" | | TAILGATE: | | CHASSIS: | |
|-----------------------|---------------------------|------------------|------------------|-------------------|-------------------------|
| WIDTH (INCHES) | 102 | HEIGHT | FULL | MODEL | TRIAxLE-2 FIXED-1 LIFT |
| LENGTH (FEET) | 50 | TYPE | SPLIT VAN DOORS | TYPE | ALUM SUB FRAME |
| HEIGHT (INCHES) | 104-107 WEDGE(5) | STYLE | GENESIS | AXLE TO AXLE | 60" - 60" |
| SIDE MAT'L (OUTBOARD) | "GENESIS" | MAT'L THICKNESS | 0.100 | REAR AXLE SETTING | 54" (9)(10)(11)(12) |
| FRONT 0.135 | | S / S HINGE ON | BOTH 4-3-4 | 5TH WHEEL HT | 50" |
| MIDDLE 0.135 | | GATESEAL | RUBBER | PIN SETTING | 36" + 3/8" KP PLATE |
| REAR 0.135 | | GATE LADDER | N/A | SUSPENSION | AAT30K/E-1-2 L LIFT-E-3 |
| POLISHED SIDES | YES+TG+REAR PKT | TARP HOOKS | NONE | SPRINGS | AIR |
| ROOF | NONE | WINDERS | N/A | AXLES | TP -GREASED |
| ROOF MAT'L | NONE | GATE GUIDE | N/A | BRAKES | HEND. MAXX 22T |
| BULKHEAD | 3/16" BUFFED(1)(2)(4) | GATE CONTROL | DBL LOCK RODS | DUSTSHIELDS | YES |
| TARP HOOKS | NONE | POCKETS | EXTRUDED | BRAKE CHAMBERS | ADB |
| TARP BASKET | NONE | CROSSPIPE (S) | TWO | ABS | 2S / 1M |
| TARP | NONE | | MIDDLE -TUBE TYP | HUBS | 10 S LW STEEL |
| CATWALK | YES-74" INTRMDTE | | REAR - TUBE TYPE | DRUMS | HXL-5 |
| B.H. LADDER | D/S-LADDER | COMPACTOR: | | WHEELS | 8.25 X 24.5 6HP/6MP |
| CROSSMEMBER | "I"BEAM- 12" C/L | SIDE LATCH | N/A | | |
| FLOOR MAKE | KEITH - 3.5" DRIVES | CENTER LATCH | | TIRES | 11R 24.5 R268 (14) |
| FLOOR MAT'L | #2295-24" WEAR STRIP | PIN DIA. | | | 16PLY ECOPIA BS |
| WEARPADS | REAR + FILLER STRIP FRONT | | | DOLLIES | 2 SPD JOST HX151 |
| TAPE COLOR | NONE | HYDRAULICS: | | LOCATION | D/S CRANK (16) |
| LIGHT PANEL | LED IN BODY(7) | HOSES | TWO-4000 PSI | BUMPER | STEEL UNDERRIDE |
| MARKER LIGHTS | LED (8) | LENGTH | 144"W/ BOX ON BH | TOW HOOK(S) | TWO |
| MIDMOUNT SIGNALS | LED - MODEL 60(15) | FITTINGS | WINGNUT | PUSH BLOCKS | YES |
| MUDFLAPS | STD (13)(17) | HP | 1" MALE | PAINT | BLACK |
| HOSE HANGER | YES | LP | 1" FEMALE | | |
| TIRE CARRIER | NONE | HOSE LOCATION | P/S-REF 90169 | | |
| | | AIR & ELECTRICAL | CENTER (3)(6) | | |

REMARKS: PRICING SUBJECT TO CHANGE 12 WEEKS PRIOR ESTIMATED BUILD DATE.

CHANGE 1

1. NO CAST STEPS INSIDE OF BULKHEAD OPPOSITE OUTSIDE LADDER ON D/S
2. RIGHT WEIGH OIL FILLED GAUGE (LBS.) MOUNTED ON NOSE TOWARDS D/S- REFERENCE PIC BELOW.
3. ADD AUXILIARY ISO 7 WAY PLUG LABELED '7 WAY ISO'.
4. MANDOR IN CENTER OF BULKHEAD.
5. TOP RAIL SECTION 99246 - LIGHT WEIGHT TOP RAIL
6. JUNCTION BOX LOCATED ON INSIDE OF FRAME RAIL DIRECTLY OPPOSITE CONTROL BOX W/ WIRING HARNESS RUN TO IT.
7. LIGHT PANEL IN BODY AND TO HAVE LED BACK UP LIGHTS OOOX ooo XOOO
8. LED-5 PR OF 30385Y/R MARKER LIGHTS BOTTOM & TOP -NO PROTECTORS. TOP ROW 16" DOWN FROM TOP OF TOP RAIL. EVENLY SPACED.
9. AAT30K FOR AXLES #1 & #2 AND AAL30K LIFT AXLE AS AXLE #3 (REAR AXLE) - ALL AXLES TO EQUALIZE.

10. REAR LIFTING AXLE TO HAVE BRAKE RELEASE VALVE - REAR AXLE ACTUATED WITH FRAME SWITCH + ELEC CC (WIRED THROUGH AUX. PLUG)
11. ALL CONTROLS IN POLY. BOX AHEAD OF AXLE #1 AND WIRED FOR CC THROUGH AUX PLUG-REF.87082 - OLD STYLE, NOT AIR IN THE BOX-REF PIC BELOW
12. GALVANIZED SUSPENSION HANGERS.
13. 16" BLACK MUDFLAPS AHEAD OF TIRES FOR AXLE #1, #2, #3
14. TIREMAXX PRO ON ALL AXLES.
15. ONE PAIR OF LED BOXED IN BACK UP LIGHTS LOCATED AHEAD OF SUSPENSION SHINING REARWARD AND WIRED WITH OTHER B/U LIGHTS
16. C/L OF LANDING GEAR TO END OF THE FLOOR TO BE APPROXIMATELY 34'.
17. ADD CENTER BLACK MUDFLAP AHEAD OF AXLE #1, ADD CENTER REAR CHASSIS BLACK MUDFLAP-REF PIC, MOVE REAR MUDFLAPS FORWARD SO THEY ARE INLINE WITH THE CENTER FLAP-REF PICS
18. ADD ONE 24" X 24" X 48" 1/8" MATERIAL EXTREME WEATHER TOOLBOX WITH CAMLOCK DOUBLE DOOR; D/S AHEAD OF SUSPENSION
19. INSTALL PHILLIPS TRACKER SPRING KIT(PRT# 17-1488) TO HYDRUALIC HOSES & CATWALK
20. GALVANIZED 5TH WHEEL W/ REPLACEABLE KINGPIN
21. ROUND BETTS REGISTRATION HOLDER @ D/S LANDING GEAR.

OVERALL HEIGHT (FT)

#VALUE!

EMPTY WEIGHT (#) **20,426**
EMPTY WEIGHT VARIANCE +/- 3%)

CUBIC YARDS

#VALUE!





DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.